

THE Scientific American.

MUNN & COMPANY, Editors & Proprietors.

PUBLISHED WEEKLY AT NO. 37 PARK ROW (PARK BUILDING), NEW YORK.

O. D. MUNN, S. H. WALES, A. E. BEACH.

Messrs. Sampson Low, Son & Co., Booksellers, 47 Ludgate Hill, London, England, are the Agents to receive European subscriptions or advertisements for the SCIENTIFIC AMERICAN. Orders sent to them will be promptly attended to.

VOL. XI. NO. 21....[NEW SERIES.]....*Twentieth Year.*

NEW YORK, SATURDAY, NOVEMBER 19, 1864.

Contents:

(Illustrations are indicated by an asterisk.)

*Old's Lumber Measure.....	321	Sweet's System of Screw Bolts, etc.....	326
John Fitch wanted Four Hundred Dollars.....	321	Preparing Furs for Market.....	326
Discovery of an Iron Mountain Saving Silver by Photographers.....	322	An Inventor's Experience.....	327
A Smokeless Furnace.....	322	The Way to make Black Ink.....	327
Effects of the Excessive Use of Sugar on the System.....	322	Useful Application of "Slag".....	327
The Use of Fuzes.....	322	*Porter's Boot-blackening Case.....	328
India-rubber Clothes Wringer.....	323	*Cornelius & Baker's Electric Bracket.....	328
Link Motion—The Relative Proportions of Slides and Steam-ports.....	323	Converting Iron into Steel.....	328
Gen. Butler's Canal at Dutch Gap.....	323	The Way to Prepare Tripe.....	328
Value of a Patent.....	323	*Bourne's Heating and Shaving Apparatus.....	328
Special Notice.....	323	Extension of Patents—for whose Benefit Granted.....	329
Miscellaneous Summary.....	323	The Citizen's Great Duty.....	329
Osborne's Process of Photographing.....	324	Is Gunpowder Liable to Spontaneous Combustion?.....	329
Bismuth.....	324	The Avery Engine.....	329
Ginseng.....	324	Petroleum.....	329
Fatal Explosion of Fumigating Mercury.....	324	Concerning Valves.....	330
New English Rock-Drilling Machine.....	324	Grease Balls.....	330
The Ames Union Gun.....	325	Expansion of Liquids.....	330
Practical Triumph.....	325	Finest for not Working.....	330
Preserving Potatoes in Molasses—Government Vinegar.....	325	Beware of Raw Pork.....	330
Repeating Rifles.....	325	Blowing Up of the "Albemarle".....	330
Tool for Scaling Boilers Wanted.....	325	Patent Claims.....	331, 332, 333
		Notes and Queries.....	334
		*Stott's Fulling-mill Stop-motion.....	336
		*Frost's Railway Truck.....	336

EXTENSION OF PATENTS—FOR WHOSE BENEFIT THEY ARE GRANTED.

There seems to be an impression among inventors that since the law of March 4, 1861, went into force, the previous law, in respect to extending patents for seven years, was abrogated. This is not so in regard to cases which were patented under the old law. Any patent which was granted prior to March 4, 1861, may be extended for seven years on proper application to the Patent Office, provided the patentee has not already been amply remunerated for his invention, and proves to the satisfaction of the Commissioner that he has used proper diligence in attempting to realize gains from his patent. The patentees of 1851 should lose no time in making out a statement of their profits and losses in consequence of their patents, and in seeing counsel in regard to an extension, if they wish the term of these expiring patents continued for another seven years.

It is often the case that the extended term of a patent produces to the patentee a ten-fold profit over the amount realized during the first fourteen years of its existence. The assignees of a patent cannot obtain this extension: it must be done at the instance of the inventor—or, if deceased, his heirs may apply for the extension, but in either case ninety days' notice of their intention should be given—for whose sole benefit it is granted.

For full particulars concerning extension, address  
MUNN & CO.,  
Editors and Proprietors of the SCIENTIFIC AMERICAN,  
37 Park Row, New York.

THE CITIZEN'S GREAT DUTY.

ABRAHAM LINCOLN, of Illinois, has been re-elected President of the United States by a large popular majority; and ANDREW JOHNSON, of Tennessee, has been chosen Vice President, to succeed Hannibal Hamlin, of Maine. The election passed off peaceably and without the necessity of military interference; and it now becomes citizens of all parties to yield a willing and cheerful obedience to the authorities thus constituted by the popular suffrages. Under our constitutional Government such obedience is absolutely requisite to the permanent safety and prosperity of the Republic; for unless this Government be upheld by the united strength of the people its destruction will ensue; order will give place to anarchy, and anarchy will be succeeded by a despotic power supported by military force and violence.

We have already witnessed the direful consequences of a rebellion against the rightfully-chosen leaders of the nation, the sad effects of which will exist for a generation at least. We therefore exhort our readers to put aside all partisan bitterness and yield unwavering devotion to the Government. This war would, in our judgment, come to a speedy end if citizens of every class would unite in strong determination to succeed. We have a country and a government worth saving, and it cannot be rescued from destruction by sharp partisan conflicts, such as we have now most happily passed through. We could find fault with the Administration—it has committed grievous errors; but we are forced to believe that the Chief Magistrate has endeavored to do his duty manfully and faithfully, and it is no fault of his if he has not the mental power of a Burke or a Webster. Let statesmen now forget their political aspirations and apply their wisdom to great questions affecting our civil government; let financiers busy their brains with such schemes as will best support the national exchequer. Soldiers will then stand by their arms, and, with the moral power of the nation to sustain them, will battle with and [defeat the enemy; ministers will preach "of righteousness, temperance and a judgment to come," not forgetting that "without charity we are nothing;" farmers will toil at the plow and in the harvest field; mechanics will be busy in the workshop and the manufactory, while the inventor with his keen perception of the great necessities of the Government and the people for labor-saving machinery, will tax his fertile brain to meet these necessities; and, altogether, we will join hearts and hands in lending our moral and financial support to the Government, believing that thus, and thus only, can we save the goodly heritage of our fathers.

IS GUNPOWDER LIABLE TO SPONTANEOUS COMBUSTION?

The recent terrible explosion near London has led some of the ablest of the English journals to suggest the liability of gunpowder to spontaneous combustion, and the location of large magazines in the vicinity of some of our cities makes this suggestion of great interest to us.

There are four processes by which substances are set on fire spontaneously:—1st, by the rapid absorption of oxygen from the atmosphere; 2d, by fermentation; 3d, by the development of heat in the change from the solid to the liquid state; 4th, by the condensation of gases on the surface of solids.

1st. There is a class of oils called drying oils, from the fact that when exposed to the atmosphere the oxygen of the air enters into chemical combination with them, and converts them from liquid oils to solid resins. This property adapts these oils to use as paint. When oils of this class are spread out in a way to offer a very large surface to the action of the atmosphere, the combination of oxygen with them is sometimes so rapid as to set them on fire. The largest surface of oil in proportion to the mass can be obtained by spreading it over the minute fibers of cotton, linen, or wool, and the great majority of cases of spontaneous combustion have resulted from saturating some of these fibers, either in the mass or in cloth, with linseed oil.

2d. When damp straw or manure takes fire from fermentation, the heat results in this case also from the absorption of oxygen from the atmosphere.

3d. When water is brought in contact with quick lime the two substances enter into chemical combination with each other, forming hydrate of lime. The water is changed from the liquid to the solid state, and its heat of fluidity is converted from latent to sensible heat. When the change is sufficiently rapid the heat given up will set fire to any dry wood with which the lime is in contact. Much property has been destroyed by this process of spontaneous combustion.

4th. Charcoal, in common with some other substances, has the property of attracting gases to its surface with such force that the gases are condensed, and the condensation of course develops heat. In some cases this condensation is sufficiently rapid to set the charcoal on fire.

If gunpowder ever takes fire spontaneously, it must be by the process last described; but this is in the highest degree improbable. It is only freshly burned charcoal that has the property of condensing

gases on its surface; by being wet it loses the property. As the several ingredients of gunpowder are mixed together in the form of a moist paste, the susceptibility of the charcoal in it to spontaneous combustion must be destroyed. We have never known an instance of gunpowder taking fire spontaneously and we expect never to know of one.

THE AVERY ENGINE.

We have had many inquiries in relation to this engine, and we will undertake to answer them all in one article. The Avery engine is simply Hero's engine with sword-shaped arms. Hero lived at Alexandria, in Egypt, 120 years before the Christian era, and among his numerous inventions was the first steam engine ever constructed. It was formed by connecting a tube with a steam pipe in such manner that it could revolve, and having a second tube crossing the first at right angles, with the interiors in open communication. Small holes were then made in the second tube near its ends and on opposite sides. As the pressure of the steam against the interior walls of the tubes was exerted on all parts except the holes, the pressure opposite to these holes caused the apparatus to revolve. Two thousand years afterwards an Englishman by the name of Barker attached his name to Hero's engine, and it is now generally known among the English as Barker's mill.

In order to obtain the full power of the steam from Hero's engine it is necessary that the parts where the steam escapes should move with a velocity equal to that with which the steam issues from the orifices. This high velocity causes great resistance from the air, and to diminish this resistance Mr. Avery conceived the idea of making the cross tube or arms sword-shaped. He obtained a patent for this improvement, and Hero's engine with sword-shaped arms is known in this community as the Avery engine.

Thirty years ago there was a large saw mill in Atorney street, in this city, driven by an Avery engine. The arms extended about five feet, and the engine was run about 3,000 revolutions per minute, making the velocity at the ends of the arms about equal to that of a cannon ball. As the specific gravity of steam at the atmospheric pressure is less than that of air, the resistance would be less if the engine were run in steam than if it were run in air; it was accordingly surrounded by a box with a small opening for the escape of the steam but which confined it sufficiently to exclude the air. The openings in the arms were very minute, if we remember rightly only one sixty-fourth of an inch area, and the steam was worked at a very high pressure.

In order to resist the great centrifugal force resulting from such rapid rotation the arms were made of cast steel. On one occasion a new engine was started which proved to have a flaw near the end of one of the arms; the piece came off and went up through two or three floors with a force equal to that of a cannon shot.

By long use deep furrows were worn in the edge and sides of the revolving arms, giving a jagged edge like an irregular saw. These furrows were probably first started by particles of dust, and the wearing was continued by the friction of the steam.

After this engine had been in use some twenty years it was taken out, and a cylinder engine was substituted. We have been told that the proprietors regretted the change after it was made, finding on trial that they did not like the cylinder engine as well as the old revolver.

A locomotive was constructed in this State with an Avery engine, but did not prove a success. The high velocity with which the arms revolve causes great resistance to any change, however slight, in the plane of rotation, and this unfits the Avery engine for locomotive purposes either on railways or steamboats. Every passage of a curve on the railroad, and every roll of a steamboat would change the plane in which the arms were revolving, and the resistance offered by the high velocity to this change of plane would rack the supports of the engine to pieces.

PETROLEUM.

Like all other great staples of the country this oleaginous one requires machinery to aid in bringing it to the surface and to market. Its cost of production

can thus be very much lessened, and the profits of well owners, brokers, and all concerned, correspondingly increased. Pumps are wanted, boring tools and engines are required, besides a host of minor auxiliaries not necessary to specify. Let oil men make their wants known in this particular and they can be supplied with any machine required. Ingenious men connected with operations of the character in question should keep their eyes open. Fortunes have been pumped up out of the ground in a week, out there are a good many above ground still, and those who shall seek shall find.

#### CONCERNING VALVES.

When a feed pump becomes deranged the first thing the engineer thinks of examining is the valve seats. They are so universally a cause of trouble that the ingenuity of inventors has been exhausted to facilitate the inspection of these parts. Bolts are made ready to cast off at a moment's notice, and bonnets are so contrived that they may be quickly disengaged. The trouble with valve seats frequently arises from imperfect construction. Valves are of so many different kinds, however, that some discussion of the several varieties may not be out of place. The ordinary circular brass valve with a brass seat, sometimes called a clack valve, is one generally used in small pumps for feeding boilers, and other uses. They are sometimes made with flat seats, but are oftener conical in form, and when thus made are frequently defective from bad proportion. The taper is made too slight, so that in rising and falling the valve becomes jammed in its seat, and refuses to work. Valves with spindles often leak from the spindle being bent; a very slight bend, not visible except by putting the valve in the lathe, is enough to disable the pump. Muddy water is also a source of trouble in this respect. These valves work very well in pumps where not over four or five inches in diameter, but beyond that size a better substitute is found in a vulcanized india-rubber disk. The disk in use varies from half an inch in thickness to two and a half inches, according to the area of the passage; and the seat is simply a grating, with the sharp edges rounded so that the valve will not be cut by them. In spite of this precaution, however, the valves wear rapidly when large, by reason of the heavy pressure from above. This objection has been measurably overcome by employing a number of small valves instead of a single large one. This plan, again, has the disadvantage of necessitating small bolts and narrow openings in large pumps and heavy buckets, so that the small fixtures are often knocked off and broken by the violence of the water in meeting, or passing through them. These small valves and openings also churn the water into foam, so that the pump is much less effective than when lifting a solid column.

Of old the ponderous metallic butterfly valves were used in marine steam engines for foot valves, outboard delivery valves, and the valves at the nozzle of the air pump, where it delivers its contents to the hot well. These valves weighed upward of 200 pounds each, on heavy engines, and the thumping and pounding when they were at work may be imagined. It was a great improvement when they were deposed by rubber valves, as they now are universally. Force pumps on screw engines and locomotives have usually much larger valves and openings than common pumps, and in marine engines they are invariably of vulcanized rubber. Ball valves were formerly much used, but are not now in modern steam engines. The objection to valves of this form is that they fill the water ways above, unless a side passage be made for the water in the valve chamber. When made of rubber it answers well in small pumps. Metallic balls are used, but they are costly to make, and are not always tight; they are also heavy, and batter the seats.

Much ingenuity has been expended in making valves in complicated forms, but such methods are, in our opinion, wrong. Simplicity of construction in a steam engine is the first requisite, for from it generally arises other good qualities. The puppet valves of marine engines were first made of cast-iron, and were single disks. Intelligent engineers, however, prefer to use double beat, or balanced valves instead, not only on account of the reduced labor in handling the engine, but also from the decreased wear and tear of the parts which operate them. Mere force can as well be

applied to a single disk valve as to raise an anchor, but it requires no judgment to apply it, and is a simple question of areas. Instead of being iron they are now brass and iron, in such proportions that the greater expansion of the softer metal is compensated for by its reduced quantity. When this proportion is observed the valves are perfectly tight, and will remain so with proper care.

#### GREASE BALLS.

Mr. Gilbert Valentine, engineer at Messrs. Harper & Bros., in this city, recently called at this office with some balls of grease which had collected in the exhaust pipe of his engine to such a degree that the opening was practically closed. These balls were sixteen in number, and we are informed that there were six more. They are about an inch and three-quarters in diameter, in appearance black, and of the nature of black-lead in consistency and fracture. They cut easily and leave a shining mark under the knife. Mr. Gilbert informs us that he uses nothing but tallow in his cylinder. The formation of such balls is not unusual in steam engines, and we have seen them taken from locomotive cylinders and other engines in localities where hard water was used. They are principally composed of tallow, which combines with the impurities in the water carried over by the steam, together with such foreign matter as may accidentally be introduced to the cylinder. The wear of the surfaces in contact, such as the packing and the cylinder, is also carried off by the grease, so that a portion of iron is contained in them. These balls often accumulate in the bottom of the cylinder ports, and, where the clearance is great behind the piston, or before it, have been known to knock out the head by being blown out of the port into the cylinder. Balls formed in engines operating in limestone regions, or where the water is unusually calcareous, are frequently as hard as stone. Those which Mr. Valentine brought us are the largest we have ever seen.

Some engineers use black-lead in cylinders that have been badly scratched, and the presence of this mineral is exceedingly favorable to the formation of grease balls. The existence of them shows the necessity of frequent examination of all parts of steam engines, especially the pistons and ports, or those points where such accumulations are likely to occur. The passage of the exhaust pipe alluded to was almost stopped by the presence of eighteen solid balls nearly two inches across.

#### EXPANSION OF LIQUIDS.

In a former article we treated of the degrees of expansion of certain metals and other solids. Gases and liquids expand also, but in different ratios. The same liquid, water for instance, expands unequally at different temperatures; but the law for its changes as well as for those of other liquids cannot be laid down with certainty. As a general rule, however, the fluids which expand the most are those which boil at a low temperature, as alcohol and some of the more volatile essences. The amount of force generated in the expansion of liquids is enormous, and this is taken advantage of by practical men in testing steam boilers with little or no labor, and with great certainty and safety. The plan is to fill the boiler as full of water as it will hold, close all apertures, and load the safety valve to the greatest amount the boiler will ordinarily bear. A fire is then kindled in the furnaces, as usual, and the heat causes the liquid to expand, long before it reaches its boiling point, with great force. Water expands very irregularly, with equal increments of temperature, between the freezing and boiling points; the whole amount of its expansion between the two degrees just mentioned is comparatively small, its coefficient of expansion being less than that of any other liquid, except mercury. The most noticeable irregularities in the expansion of water occur between 32° and 40°, and, what is most singular, while all other fluids have the greatest density at their freezing points, that of water is shown at 39°.2 Fah., and either above or below this point it expands. This fact is fully proved by experiments made with apparatus devised for the purpose, and it explains why but a comparatively thin coating of ice, compared to the body of water, is formed on the surface of rivers and

lakes, even in winters of great severity; for although water freezes at 32°, before that temperature can be reached the water on the surface expands, and although colder is specifically lighter than the warmer and larger bulk below on which it floats. Ice is then formed on the surface; and, being a bad conductor, prevents the water below from freezing to a great thickness by checking radiation.

#### FINED FOR NOT WORKING.

It seems that the race of Gradgrinds, that Charles Dickens speaks of in "Hard Times," is not yet extinct in England. An apprentice to an iron-founder in England, who lately plead guilty of having absented himself for one day from his work, was sentenced to one month's imprisonment, at hard labor.

That must have been a cheerful service which the youth rendered after this punishment. Employers are often foolish. Compulsion is no part of a youth's instruction in a trade; if he do not take to it cheerfully and naturally he is useless, and might better be out of the shop than in it. Apprentices are no longer bound in this country, and this reform has instituted itself. The character of our apprentices is too high to admit of even seeming vassalage, and when master and apprentice cannot agree it is time, for the self-respect of both, that they should part.

There is something to be said for both sides. Boys will be boys, and to expect a youth to come into a shop and lay aside forever all his youthfulness and become the sober journeyman is unnatural. A boy without spirit is no boy at all, and he must have recreation at proper times and seasons.

Eye service is useless. A boy that works while his foreman is present, and goes into ground and lofty tumbling when he is absent, is better out of the shop, for he wastes his own time and sets a bad example to others. Out of the shop the employer has nothing to do with him, and his time is his own; his morality and his accountability for misdeeds are also his own; he alone must answer for them.

If a youth wishes to learn a trade he will apply himself; it is his interest to do so; and if his master is wise he will encourage, but never enforce, attention. Keep boys apart. Recruits in the army are put with veterans, and soon make good soldiers. Fun is contagious, and one joker will infect a dozen steady fellows. Boys have their places in the shop as well as in the world, and they make journeymen as well as members of society. It is no part of the law of good sense or kindness to misuse them or be hard upon them.

#### BEWARE OF RAW PORK.

A few days since we observed a butcher tasting some raw sausage meat in his shop, and the act was immediately associated in our mind with a singular-looking bottle which Dr. Hallett, of Brooklyn, has standing on the table in his office. When we first saw this bottle we supposed that it contained strips of some white bark very nicely prepared. But Dr. Hallett informed us that it was a tape worm, which he had recently taken from the bowels of a man who contracted it by eating raw pork in California.

The old readers of the SCIENTIFIC AMERICAN will remember that the origin of tape worms in raw pork was pointed out in the pamphlet of Dr. Weinland, which was noticed on page 100, Vol. V., new series. As we have several thousand new readers we repeat the caution. Fortunately the tape worm is very rare, but when it does occur it is caused by eating raw pork.

#### BLOWING UP OF THE "ALBEMARLE."

The rebel ram *Albemarle* was destroyed on the 28th ult., by a torpedo, which was placed in position by a method that has been frequently recommended in the SCIENTIFIC AMERICAN. This method is to attach the torpedo to a boom extending forward from the bow of a swift vessel. It was demonstrated by Fulton that any vessel could be destroyed by the explosion of 100 lbs. of gunpowder in contact with her bottom. The difficulty has been to get the torpedo against the vessel's bottom and explode it there. Plans for floating torpedos down by the tide very rarely if ever succeed, and even when they are placed on the bottom vessels usually pass over them with impunity. But when a brave officer has a torpedo