

being short, dry, and cute; while this one of Morrison is long, soft, and kinky.

**Cannon**—J. C. Haddan, of "Cannon Row," London, patentee.—This invention consists in lining the interior of old and new cannon with rifled or plain tubes to fit the bore. They are inserted into the cannon after it is cast, and are made in one, two, or more pieces, longitudinally or transversely. Such tubes for cannon are intended to be renewed from time to time as they wear out, so that the body of the cannon may serve for a long period, and not as they are constructed at present, the whole gun having to be laid aside as useless on account of the worn bore.

The above-named place, where the inventor of this improvement resides, harmonizes with the character of his invention.

#### Silver and its Uses.—Concluded.

A great quantity of silver is used for articles of domestic use among the more wealthy classes; but although such articles pass under the name of "silver plate," they are all alloyed more or less with copper. In our country there is a great difference in the quality of articles which pass for silver, owing to their degrees of alloy. In England, on the other hand, there is a standard for plate silver, and in order to prevent fraud, all silver vessels are required to be inspected and stamped. The alloy is composed of 111 parts silver to 9 of copper, by weight. In France, the standard for plate is 19 parts silver to 1 of copper. The addition of a small quantity of copper to silver, while it increases its hardness to a wonderful degree, scarcely diminishes its whiteness. The greatest degree of hardness is obtained by using of copper one-fifth the weight of the silver. With equal weights—copper and silver—the alloy is a good white. Articles formed of alloyed silver are subjected to a process to remove the baser metal from the surface. They are heated nearly to redness, then plunged while hot into warm water acidulated with sulphuric acid, which removes the oxyd of copper (formed while heating the article) from the surface, leaving it of a blanched appearance, called *dead silver*. Alloyed silver articles are sometimes boiled in bi-sulphate of potash to produce a like effect. Those parts of plate requiring to be burnished are polished with proper tools.

The most important salt of silver is the "nitrate;" it is prepared by dissolving silver in nitric acid, and evaporating the solution to dryness, or until it is sufficiently concentrated to crystallize on cooling. The crystals are colorless and transparent, readily soluble in water and alcohol. If these crystals be heated in a crucible, they fuse like niter, and are formed into sticks, called *lunar caustic*. This salt blackens by exposure to the sun. Ivory, marble, &c., may be stained black by soaking them in a solution of this salt, and exposing them to the sun's rays. It is used for making indelible writing ink. The article to be marked, is first moistened with carbonate of soda, then dried, then written upon with a weak solution of the nitrate, and exposed to the sun; it soon assumes a black appearance. It is also much employed for dyeing the hair of those who wish to conceal the marks of age. A weak solution of it applied to the hair, is all that is required to color it black, or deep brown. Care must be exercised not to touch the skin with it. The cyanide of potassium will remove nitrate of silver stains.

When nitrate of silver is taken as a medicine, it gives to those parts of the body exposed to the light, a leaden gray color. In a weak solution, it is used by some oculists as a wash for inflamed eyes, but it should be avoided if possible, as it greatly discolors the white part of the eye. A weak solution of it is often applied by physicians for curing diseases of the throat.

The nitrate of silver is much used in preparing daguerreotype plates, and photographic paper; it plays an important part in sun painting. Its sensitiveness to light, and other substances, is the reason of this. A plate of clean copper introduced into a solution of it, produces a brilliant crystalline deposit of silver; a stick of phosphorus placed in it soon becomes encrusted with tree-like crystals of the metal. Mercury poured into a solution of it produces that beautiful crystalline deposit

of the metal known by the name of *arbor Diana*.

The chloride of silver is formed by mixing together a solution of nitrate of silver with a solution of common salt; it is termed *horn silver* when found native. This salt is soluble in ammonia, and in a solution of the cyanide of potassium; it is much used in photography. By introducing a solution of potash or soda into one of nitrate of silver, a protoxyd is formed; it falls to the bottom of the vessel in the form of an olive colored powder. If this be digested in a strong solution of ammonia, a black substance is produced, which is terribly explosive—fulminating silver. It explodes under water when heated to 212°, and when it is dry, the touch of a feather, or the rolling of a carriage across the street explodes it. Fulminating silver is also obtained by the action of warm alcohol on nitrate of silver. The iodide of silver is formed by adding nitrate of silver to the iodide of potassium. It is easily decomposed by light, and it therefore forms the basis of the film of photographic pictures. Silver solder is composed of 667 parts of silver, 233 of copper, and 100 of zinc.

Silver was early applied to the purposes of ornamenting by plating, that is, covering an inferior metal, like copper, brass, and iron, with a skin or coating of silver. The articles to be plated were scoured bright, then heated to a point just below that at which the metal changes color, the silver in thin leaves then laid on and the adhesion produced by a burnisher.

The best method of fire silver plating is that pursued in Sheffield and Birmingham, England, which is to make plated ingots, and from them manufacture the articles. Ingots of copper or brass are carefully filed, then the silver in thin sheets is neatly laid on them, their edges joined together and brushed with a solution of borax. They are then tied with wire and introduced into a furnace heated with charcoal. The ingots are laid on the red-hot charcoal and submitted to heat until the silver is observed to draw into the copper. The attendant who watches the process now withdraws the ingots, for if suffered to remain longer the silver would become amalgamated with the copper. Although electro-silver plating has recently become so common we have been assured that the business of fire-silver plating has in no wise diminished.

Electro-silver plating is now carried on to a great extent. The silver is deposited from a solution of the argento-cyanide of potassium on the articles to be plated by a galvanic current generated in a battery. White metal, or a composition of tin and copper, is the best basis for silver plating, because when the plating wears off, the white metal underneath is not so readily noticed. Electro silver plating is an art only a few years old, yet owing to its flexible character—the facility with which so many articles can be covered with a coat of this beautiful metal—it is the most interesting of all others for which silver is used

#### Notes on Ancient and Curious Inventions.—No. 3.

**Linen and Duck**—Previous to the invention of the cotton gin, and while cotton was a dear material, linen was most generally employed for all the purposes of domestic and personal use, now fulfilled by cotton cloth. The manufacture of linen was therefore sought to be early encouraged in the Colonies, and a Bill was introduced into the Connecticut Legislature in 1735, to pay a bounty on every yard of fine linen made. The bill, however, was not passed, and to this day no *fine* linen has yet been made in America. In 1724, Richard Rogers, of New London, Conn., manufactured excellent duck for sails, and obtained a patent for its exclusive manufacture in the year following.

**Silk, Flax, and Hemp**—The Legislature of Connecticut early offered encouragement to those who would cultivate hemp and flax, and raise silk. In 1784 a bounty was offered for every ounce of silk raised from cocoons.

**Pins**—As early as 1775, a factory for manufacturing pins was proposed to be erected at Wethersfield, Conn., by Leonardus Chester, but until 1812—during the last war with England—our country received all its pins from across the Atlantic. In that year their price rose to one dollar per paper, when some pin

makers came to New York from England, and commenced business, at which they continued until the war ceased, when they abandoned it. The first patent for manufacturing pins by machinery was obtained by L. Morse, of Boston, in 1813. The *solid* headed pin, the one now in common use, which has entirely superseded the old separate headed pin, was invented by Lemuel W. Wright, of Haverhill, N. H. He obtained patents for America and England, in 1825, and went to the latter country to sell and introduce his machinery for their manufacture. A working machine was in operation in 1826, in London, and the inventor made and sent out two machines to his own country, but these were never set in operation. His machines were defective in forming the pin points, owing to the difficulty of arranging and keeping the rotary files in order for this purpose, consequently his machines were, at last, only employed to take the wire from a reel, straighten, cut it into lengths, then head and deliver it to be pointed by hand. This inventor, like J. Perkins, took up his residence in England, where he was living three years ago, and was highly esteemed for his mechanical genius and integrity. The names of the inventors of the steam engine, cotton gin, steamboat, and telegraph, are often mentioned with enthusiasm and respect, because of the benefits they have conferred upon mankind by their inventions, but who ever heard of the name of Lemuel W. Wright, of the Old Granite State being toasted as an inventor, and yet his invention was a most useful, and ingenious one. Like many other good inventions, however, the authorship of the solid-headed pin is disputed. On page 381, Vol. 9, SCIENTIFIC AMERICAN, there is a notice of the solid-headed pin having been made fifty years ago by D. F. Taylor, of Birmingham, Eng., whose brother now manufactures them at the rate of 200 per minute. In 1832 a patent was granted to John J. Howe, for a pin machine, and in 1835 a Company was formed in this city to carry on the manufacture under his patent. The machine formed the head of a coil of fine wire by dies, and the pin so made did not differ from the English diamond pin. In the same year Samuel Slocum, of Rhode Island, obtained a patent in England for machinery to make solid-headed pins, and in 1838 a factory for their manufacture was set in operation at Poughkeepsie, N. Y.; he did not obtain an American patent; the machinery was operated in secret. In 1838, J. Howe also obtained a patent on improved machinery for making solid-headed pins, and the "Howe Pin Manufacturing Co." at Birmingham, Conn., are now making pins by his machine. "The American Pin Manufacturing Co.," of Waterbury, Conn., bought out Slocum's machine, at Poughkeepsie, in 1848. The weekly manufacture of pins by these two companies amounts to about 9 tons. At one time all the pins were inserted into their papers by hand, but machinery has been employed for a number of years to execute this work, so that from first to last, the manufacture of pins, as at present conducted—from the wire until they are ready for market—is performed by self-acting machinery. The American improvements in pin making, and sticking the pins, have been in use for several years, we understand, in England.

#### Railroads; Speed; Grades, and Curves.

We are indebted to the Superintendent—D. C. McCallum, Esq., for a copy of a very complete report of the New York and Erie Railroad for 1855. There are some matters of a scientific nature in this report, a brief review of which will be interesting to a number of our readers.

The whole length of track—including double and branch tracks—belonging to the Company, is 769 miles; and the tracks are 6 feet gauge. It is a stupendous railroad, involving the use of an immense amount of property, and employing a vast number of persons; therefore, as it does a great amount of business, its affairs require to be managed with great circumspection.

**Speed**—In the transaction of a passenger traffic great speed forms an important item of cost. The expense of running a train is stated to be increased nearly as the square of the speed. Delays and accidents are the attendants of high speeds. The report says:—

"When the time-table is so arranged as to

call for speed nearly equal to the full capacity of the engine, it is very obvious that the risks of failure in making time, must be much greater than at reduced rates, and when they do occur, the efforts made to gain time must be correspondingly greater and uncertain. A train whose prescribed rate of speed is thirty miles per hour, having lost five minutes of time, and being required to gain it, in order to meet and pass an opposing train at a station ten miles distant, must necessarily increase its speed to forty miles an hour; and a train whose rate of speed is 40 miles per hour, under similar circumstances, must increase its speed to 60 miles per hour."

The liability to collisions on a single track, with high speeds, are thus clearly set forth, and moderate speeds are recommended.

**The Telegraph**—It is stated, in the report, that a single track railroad may be rendered more safe and efficient by a proper use of the telegraph, than a double track railroad without its aid. The double track obviates collisions on trains moving in opposite directions, but not in the same direction; and it is asserted to be a well established fact, that collisions between trains moving in the *same direction*, "have proved by far the most fatal and disastrous." We have always entertained a different opinion to this. Mr. McCallum asserts that a single track, with proper turn-outs, and the use of the telegraph, is a more safe and profitable investment than a double track without a telegraph. "In the moving of trains by telegraph, nothing is left to chance." Those railroads, therefore, which do not use the telegraph, exhibit a great want of sagacity and good management.

**Resistance of Grades and Curves**—The report also contains an account of a series of experiments for determining the effect of resistance of grades and curves. These took place in the month of September last, and were made with a view to determine the relative power required upon the several Divisions of the road for the transportation of heavy freight.

A single locomotive was run the entire distance from Dunkirk to Piermont with trains varying to suit the ruling grades of the different divisions. The engine selected for this purpose weighed 40,050 lbs. on the driving wheels, it had cylinders of 17-inch bore and 24 inches stroke; driving wheels 5 feet in diameter, and an effective steam pressure of 125 lbs. on the square inch.

The traction of the engine was 14,485 lbs., that is, the total resistance it could overcome with steam at the above pressure; its friction without load was 347 lbs. It has been customary to estimate the friction of cars on 30-inch wheels with journals 3 inches in diameter at 7 lbs. per ton, but the experiments demonstrated this to be too high. The friction of such cars was demonstrated to be only 4 1-2 lbs. per 2000 lbs., the resistance of curves 1-2 lb. per ton per degree of curvature the 100 feet. The adhesion of the engine was 36 per cent. of the insistant weight; this has heretofore been estimated to be from 12 1-2 to 25 per cent. A train consisting of 100 loaded cars, weighing totally 1765 tons was taken over a mile of road on an ascent of 6. 14 feet, and a curve of 1° 5730 feet radius in 11 1-2 minutes.

The following were the resistances overcome. Friction of engine and tender 347 lbs., cars at 4 1-2 lbs. per ton, 7702 lbs., gravity of engine and train 4104 lbs. Resistance of curve 882 lbs., and additional friction 1410, making a total of 14,445 lbs., or 40 lbs. less than the estimated traction of the engine. On a grade of 60 1-2 feet ascending and a curve of 5° 1146 feet radius, with a train of 429 tons total weight the resistance was 14,363 lbs., or only 82 lbs. less, while the load drawn was less than a fourth of that on the low 6 feet grade and the one degree curve. This was done in six minutes and a half, but it shows the great amount of power consumed in ascending inclines, because the whole train, as it were, takes as much power as would lift its entire weight to that height—60 1-2 feet in the second example. No experiments were made test the increase of resistance with an increase of speed, but it is very evident that the Superintendent is of opinion that, with the exception perhaps of friction, they increase according to the square of the speed.