# Rew Inventions.

276

Improvements in Sculpture. The London Atheneum gives an account of some new inventions of our countryman in Italy, Hiram Powers, the sculptor, in the art to which he has added so much renown by his genius and skill. Thus, in finishing the limbs of his figures with that extreme nicety for which he is celebrated, Mr. Powers adopts the following bold and novel mode :--He has invented a vise, which is set upon a ball and socket joint, and has, by virtue of raising and depressing screws, every possible variety of motion. This instrument is said to be the perfection of ingenuity.

# Electrical Protection of Metals.

We stated in our last number, that according to the law of electrical affinities, when two oxydizable metals are connected together and exposed to a moist atmosphere or water, the negative is protected at the expense of the positive. Thus iron, which is very liable to oxydize, is prevented from rusting when connected with copper or lead, it rusts more rapidly; it is the positive metal when thus related. Iron may be used as the positive metal, as well as zinc, for a galvanic agent, and we understand it is so used in what is termed "the Maynooth battery," but it is inferior to zinc for such a purpose. Sir Humpbrey Davy was the discoverer of this law, and he entertained great hopes of its being so applied as to protect the sheathing of ships permanently. Iron lightning rods have been protected from rusting by connecting them at the foot with pieces of zinc placed in the moist earth. The wrought iron bolts, &c., of water wheels have been prevented from rusting by heing connected with strips of zinc, which were easily renewed from time to time This application of the law of electrical affinities is very useful for protecting the iron of various machines or articles that may be exposed to water or a moist atmosphere.

Iron appears to undergo no change in dry air, and is incapable of decomposing pure water at ordinary temperatures. In the ordinary rusting of iron a hydrated sesquioxyd is formed. Iron rust always contains ammonia, In solutions of the alkalies, and in lime water, iron remains bright, these appear to protect it from rusting. All acid salts, on the other hand, rust it rapidly. These facts should not be overlooked by those who employ steam boilers, they should use pure soft water, and no other kind for generating steam.

# Machine for Paging Books.

There are several machines in use for printing the proper figures on each page of blank books, but the one here illustrated possesses some advantages peculiar to itself. It was invented by F. O. Degener, of this city, to whom Letters Patent for a paging machine were granted July 24, 1855.

This machine, as also every other intended for the same purpose, requires the leaves to be separated by hand, and to be presented in turn on the bed or platen to receive the impression. With this exception, the operation is entirely automatic, the changing of the figures and the inking of the same after each impresson being admirably and perfectly performed. The machine may be worked by power if desired, but is here shown as working by the foot lever, M.

A is the table of the machine, on which the book is laid. B B are racks attached thereto. C C and D represent very obvious means of raising and lowering the same. E is a small flat platen, made suitably soft at its upper side to receive the impressions, and provided with suitable gages to aid in laying the corner of each leaf in the same position as its fellows, so that all the figures shall appear at the same distance from the corner of its respective page.

F is the wheel carrying the figures, and is pressed down upon E at each movement of the foot lever, M. This wheel is compounded of a number of disks, capable of revolving in- get bewildered when a great variety of pat- a few at once.

disk one notch, aud so on, to any extent re-

quired. Four figures, will, of course, in-

clude any number up to 9999, which is more

G is a roller supplied with ink in the usual

manner from other rollers. The ink is dis-

tributed at first by grasping the crank repre-

sented, and turning it for a short period; but

after the machine is in operation G is partly

rotated at each motion of the foot, so that

the crank is unnecessary. The compound

wheel, F, is carried in the stout lever, K, and

derives its motion from a connection of the

latter to the foot lever, M, by the link or rod,

L. The part denoted by J is not fixed to the

Choosing Printed Paper for Walls.

purchase paper for the walls of their houses

are never satisfied unless they overhaul a

best among the lot-and this course, in ordi-

nary business, has a common sense appear-

ance about it. But a rule of conduct, ex-

Most persons when they go into a store to

than is ever required in practice.

dependently of each other, but ingeniously con- one-tenth of a revolution after each impression, nected by pawls and notches, so that each and after having presented its figure 9, premoves the next, one notch, at each complete sents 0, and gives a movement of one notch revolution. The motion of these disks is to the next disk, after which the disk repanalogous to those of ordinary counting de- resenting tens remains stationary, until the vices, and results in changing the number unit disk has completed another revolution, nication we have received on the subject we printed by one unit at each impression. The when it starts along another notch. When are convinced that many persons are not acfirst disk represents units, and turns regularly the second disk has thus slowly completed a

MACHINE FOR PAGING, BOOKS.

Scientific American.

full revolution its next step moves the third | framing of the machine, and as K vibrates, an arm of the lever, I, travels in the crooked slot represented in J, and moves the small inking roller attached to I, first allowing it to rest on G. and turn with it to receive ink therefrom, and then as the wheel, F, rises, moving rapidly forward, and applying the adhesive coloring matter to the types or raised figures, and again withdrawing, ready for the next impression.

The machine is represented to be capable of working easily at the rate of 1,500 pages per hour, and can, of course, number checks, bills, tickets, or other sheets or cards, with the same facility.

Further information relating to the same can be obtained by addressing Messrs. Doane lever, K, but is a portion of the stationary & Co., 96 Fulton st., this city.

terns are passed before them, that they frequently choose the poorest design of the lot. This is not surprising; indeed, it is in exact accordance with the laws of vison. It great number of patterns. Their object is to has been conclusively shown by M. Chevreul, select the prettiest style they can find-the the distinguished chemist in Paris, that the eve, in looking at color after color, is gradually undergoing ehange, so that the character of each color is altered; in short, the color is cellent and correct in the pursuit of one vitiated. An analogous result is unquestionobject, may be totally wrong in following ably produced in the form of the patterns, as after that of another, and this is the case in well as in their colors and proportions. The examining a great number of samples of best way to select good and agreeable patprinted paper at once. Many are so liable to terms of paper, therefore, is to examine only

When Patents Expire. A natent taken out in any foreign country and afterwards secured in the United States, expires with the foreign patent. This is according to our patent law. From a commu-

quainted with this feature of our patent code. The English patent of E. P. Morewood for galvanized iron, mentioned in our last issue, expired on the 3d inst., thirteen years only from the date of his American patent, but fourteen from May 3d, 1843, the date of the English patent.

#### Elevators for Steamboats.

The Pittsburgh (Pa.) Journal states that Robert Lea, engineer of that city, has constructed an elevator for the steamer City of Memphis, for lowering into and raising cargo from its hold, and it has been found very convenient. It is rigged in the hatchway, and occupies the whole space, except about two feet, sufficient for a plank on each side for walking up and down. It consists of end-, less chains, which revolve on two rollers, attached to each end of the frame, at the deck, and in the hold. On these endless chains, or belts, at regular distances, are fastened cross pieces of wood, to support barrels ascending or descending, and the machine is kept continually in motion by the engine, or can be worked by hand.

In the hold, at the base of the elevator, where the freight is removed, or put on, as the case may be, is erected an inclined plane down which the goods are taken by men when loading, or up which they are rolled and dropped on the helt, when unloading the boat. And on the deck likewise, are planks placed, a little above the belt, forming a gentle declivity towards the gangway. The hatchway, instead of being open, as a trap for the unwary, is cased with doors in front.

No such elevator, so far as we know, is employed on any of our steam or sailing ships, and we think it would be a great improvement if they were all to adopt it. Our common passenger river steamboats do not require them, as they carry their cargoes on deck and have no hold room. Elevators for unloading grain from vessels are in common use, but they are different in their construction from the one on the City of Memphis.

### Machine Horse and Mule Shoes.

Messrs. Burden & Sons, iron manufacturers at Troy, N. Y., have concluded a large contract with the Government to supply the horse and mule shoes used in the United States service. These shoes are to be made by a machine, which turns them out at the rate of fifty a minute, or ten tuns a day. They are swedged between dies, and are as uniform in weight and form as coin.

## fron ships with Iron Rigging.

The Baltimore papers state than the British iron ship Santiago has recently arrived in that city from Africa. She is a clipper of fine model, and besides the hull being of iron, the rigging is mostly composed of wire ropes. The compass is placed on the mizzen topmast, to prevent local attraction, and the top sails can be furled by the men on deck.

## Varalsh for Rustic Garden Seats.

First wash the woodwork with soap and water, and when dry do it over on a hot sunny day with common boiled linseed oil; leave that to dry for a day or two, and then varnish it once or twice with what is commonly termed hard varnish." If well done it will last for and will prevent any approvance from insects. Now is the time for varnishing such seats

#### American Balance Docks in Austria.

The Austrian Government, convinced of the superiority of our balance and sectional docks, intend to erect such structures for its navy, and J. S. Gilbert, of this city, inventor of the balance dock, is employed at Trieste in building one.

Obed Hussey's Reaping Machine has been introduced into New Zealand by an English man, and has been used with gratifying success.