

Scientific American.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT
NO. 37 PARK ROW (PARK BUILDING), NEW YORK.

O. D. MUNN. S. H. WALES. A. E. BEACH.

The American News Co., Agents, 121 Nassau street, New York.
The New York News Co., 8 Spruce street, New York.

VOL. XXIV., NO. 8. [NEW SERIES.] Twenty-sixth Year.

NEW YORK, SATURDAY, FEBRUARY 19, 1871.

Contents:

(Illustrated articles are marked with an asterisk.)

Improved Water Grate and Steam Generator	Hartford Steam Boiler Inspection	115
Baltimore Oyster Industry	Centent from Gas Lime	117
How Eyes are made	Fortunes in Scraps	117
Enameling Wood Work	The Use of Glue	117
Birmingham Bell-making	A California Railroad Pier	117
A New Stone	Obituary—The late H. Steinway	117
Roller Explosions	The Hudson River R.R. Accident	117
The Domestic Silk Trade	Improved Ore Washer	118
Extract from the Diary of Isaac I. K. Brunel, in 1855	Patent Weatherboard Bracket	118
Remarkable Cave in Georgia	To Prevent the Adhesion of Gold Leaf	118
Manufacture of Glycerin in Cincinnati	Improvements of Plows	118
Exercising Club	The Curled Hair Trade	118
The Present and the Past	Kerosene Murder	119
Aerial Temperature	Organic Matter in Water	119
Black Copper	Stone Cutting by Machinery	119
Knaps' Fluting and Flat Iron	The Electro Deposition of Copper	119
Polishing Collars and Shirts	The Uses of Apatite	120
Not a bad Idea	The Average City Dwelling House	120
Agricultural Patents of the Year	Annual Report of Commissioner of Patents	121
Perpetual Motion	Business and Personal	122
Ingenious Use of Nails	Inventors Patented in England by Americans	122
American Gas Wells	Answers to Correspondents	122
What a Woman Thinks of Modern Microscopists	Applications for the Extension of Patents	123
The Manufacture of Irish Poplin	List of Patents	123
Industrial Competition	Recent American and Foreign Patents	123
Luminosity of Cloth when torn	Old Confidence in Superstition	123
Illustrious Inventors	Steam Boiler Legislation	123

KEROSENE MURDER.

It is a matter of growing astonishment that the almost daily record of loss of life and property, through kerosene explosions, does not provoke some sort of special legislation upon the sale of dangerous fluids vended under different names throughout the length and breadth of the land. Petroleum has proved to be of vast and varied importance in the arts, but its more volatile products, have been made the instrument of the most heartless and wicked frauds; and these frauds are still daily perpetrated, and their authors go unhung, though their victims—called to meet the most horrible death known to man—constantly increase in number.

These victims are for the most part women, who, if they escape death, are obliged to undergo what is hardly less cruel to a young and beautiful woman, disfigurement for life.

It would seem in this case that the pecuniary risks involved would stimulate the fire insurance companies to action, though the public at large remain indifferent.

Our readers may recollect the case of Mary Gibson, who, only a short time since was burned to death by an explosion, of Danforth's (so-called) "Non-explosive Oil." This same material has figured before in other disasters. Its dangerous character was exposed in a former issue of this paper, yet still its sale is unblushingly continued.

We are now struck with horror at the disaster at Kenosha, in which the Halliday Hotel was destroyed, seven persons burned to death, and others fatally injured, the fire originating in a kerosene explosion; while from Baltimore comes another sad story of the burning to death of a child six years old, from the same cause.

If we chose, we might fill this column with the list of disasters which occurred last year from the explosions of petroleum fluids.

The public ought to know (surely it has been often enough told) that there is such a thing as safe kerosene, and that the dangerous fluids are either more volatile liquids, or kerosene mixed with more volatile liquids to increase the profits on its sale.

Most of these mixtures are sold under fanciful names, and are recommended by their manufacturers as better than kerosene. Now, when any manufacturer or dealer makes such a recommendation, he utters knowingly a wilful falsehood, to cheat innocent customers into buying a spurious dangerous article. No petroleum fluid more volatile than kerosene is a safe article for promiscuous and general use, and the man who sells it, is as criminal in so doing as a man who should knowingly introduced arsenic into table salt and sell it to his customers as an improved article. Let purchasers beware of these fancy names. In nine cases out of ten they are adopted as a cloak to cover cheating.

As to legislation upon this subject, it is perhaps not our province to propose measures to reach the root of the evil, but it certainly is a fact that the scoundrels who peddle death in the shape of burning fluids, are neither imprisoned nor hung. It would seem not a very difficult thing to frame a law that should bring to condign punishment such offenders.

ORGANIC MATTER IN WATER.

A very interesting paper touching upon a sanitary question of the first importance, was recently read before the Chemical Society, London, by Charles Heisch, of the Middlesex Hospital Medical College. Our views have long coincided with those of Mr. Heisch and many other chemists, viz., that "the deleterious nature of organic matter is dependent upon its containing living germs, which grow and set up a fermentative action within the body," so that the quantity of

such matter which may exist in the water we drink, is not of so much importance as hitherto supposed. If the germs be present in any sensible quantity, the water must prove more or less deleterious. It is in the nature of this class of poisons that the quantity entering into the system does not greatly influence the result, as witness the effects of poison received in wounds in the dissecting room, the poison of rabies, vaccine virus, etc.

Although, as we have said, many have for some time held the belief that organic poison in water was no exception to the above rule, there perhaps existed no very firm grounds upon which these convictions rested. They were arrived at more from theory than from demonstrated facts. But Mr. Heisch has been applying the test of elaborate experiment to the theory, and hence the results of these experiments are of more than ordinary scientific interest.

In his paper, Mr. Heisch says he was first led to a means of determining the characteristic properties and appearances of such germs by being called on to assist a large manufacturer of lemonade, who, some years ago, almost suddenly found it impossible to make lemonade that would keep. After a day or two it became turbid, and its odor anything but agreeable. On examining the liquid under the microscope, he found it full of small, spherical cells, with, in most cases, a very bright nucleus, and after a few days the odor of butyric acid was unmistakable. After examining all the materials employed, he found that the water was in fault. On putting a few grains of the purest crystalline sugar he could procure into some of the water, it became turbid in a few hours, and the same cells were distinctly to be seen with an one-eighth inch object glass; but the butyric odor did not come on for some days. This water was procured from a deepish well; it was hard, and contained a considerable amount of nitrates, but not any unusual quantity of ammonia, or unoxidized organic matter. On inquiry, he found some digging had been going on near the well, and it appeared that some drainage must have got in, though at the moment so small in amount as to be hardly appreciable. When water from the water works was substituted, everything got right again. This led him to try all the samples of water he could procure in the same manner, and in every case where diarrhea or other mischief could with any kind of certainty be traced to the use of a certain water, when that was treated with sugar these same smells made their appearance, usually within twenty-four hours, if the temperature were kept up to between 60° and 70°, and plenty of light admitted to the bottle in which the sample was contained.

During the past year he has been trying what substances contain these particular germs, which are so peculiar as to be quite unmistakable when the observer is once familiar with them. By permitting the action of these germs on sugar to go on, they present uniformly the following appearances: The cells gradually group together in bunches something like grapes, quite differently from the ordinary yeast globules; they next spread out into strings, with a wall surrounding and connecting the cells; the original cell-walls then seem to break, and leave apparently a tubular sort of threads branched together. The strong resemblance of these to, if not identity with, the sewage fungus, coupled with the almost universal properties of water which produced them, led Mr. Heisch to look to sewage as their source, and he found that the smallest quantity of sewage, mixed with a water which might be treated with sugar and remain clear and sweet for weeks, at once produced these germs, or rather set them growing. Water was procured from various sewers, and after standing a few days to settle, six drops of clear water were mixed with 10,000 grains of West Middlesex and New River water. To six ounces of this mixture ten grains of pure sugar were added, a like quantity being mixed with six ounces of the water without the sewage. All these samples were placed in stoppered bottles in a window, where plenty of light could reach them. The water and sugar remained clear and sweet. The water with this trace of sewage did the same. The water, sewage, and sugar became turbid, in times varying from twenty-four to sixty hours, and exhibited the cells and strings before spoken of, and ultimately the odor of butyric acid was always perceptible. One drop of fresh urine in 10,000 grains of water, a mixture which may be kept for weeks without showing any sign of turbidity, produced in twenty-four hours, abundance of cells, and in forty-eight hours, branched strings.

No other substances tried produced the same result, although urea, albumen, nitrates, milk, and other substances of unstable character, were experimented upon. Some of these produced growths of some sort, but none resembled the peculiar and unmistakable cells and strings referred to.

Mr. Heisch asserts that filtering the water through the finest Swedish paper does not remove the germs, as on the addition of sugar they grow as fast as ever. Boiling for half an hour in no way destroys their vitality. Filtration through a good bed of animal charcoal is, as far as he can find at present, effectual in removing them, and if the charcoal be well aired from time to time, it retains its power for several months; but if the water be passed continually through it without this precaution, it soon loses it, and the filtered water is as bad as the unfiltered. The softer the water the faster the germs grow.

In conclusion the author remarks, that he does not think these germs are the only unwholesome kind of organic matter that exists in water, or that water containing small numbers of them might not sometimes be taken with impunity; but he regards with great suspicion any water in which they exist, even in the smallest number, as they increase and multiply with great rapidity. The fact that in multitudes of cases increase of health and comfort has resulted from giving up the use of water in which they could be found, even

where its use had not produced positive disease, confirms this opinion.

STONE CUTTING BY MACHINERY.

All materials except stone are now successfully worked by machinery. We do not, of course, mean to say that stone is not so worked to a limited extent, but, in general, hand work of this material still maintains itself, against all the innovations of inventors.

The general reason for this is, undoubtedly, the abrading action upon tools which do their work by scraping, or by continuous cutting. Steel tools thus used soon wear out, and require a great deal of attention to keep them in working order. There are some kinds of soft stone which may be planed or turned by steel tools to advantage; but with the harder varieties, chipping with hand tools is the only method extensively employed.

A glance at some of the attempts hitherto made at substituting machinery for manual labor in this field, may not be unprofitable in this connection.

One method consists in the employment of a sliding eccentric, connected with a bar, in which a series of chisels is fitted; the chisels being made to adapt themselves to the surface by suitable mechanism, and being forced into the surface of the stone by the revolution of the eccentric.

Another method consists in the employment of rocking beams, carrying tools with serrated edges bearing upon the surface of the stone to be cut, and acting upon it by virtue of the rocking motion of the beams. Disks with serrated edges have also been used, which were caused to press upon and roll backward and forward over the stone, abrading it, and reducing it approximately to the form required. Rolling edges not serrated have also been tried.

Another plan is that of weighted cutters, actuated by wipers, cutting the stone by the force of their fall.

Rotating cutters, operating on the principle of drills worked in gangs, have also been used. To make a long story short, it may be said that scarcely any conceivable form of steel tool, or method of applying it, has not been tried, but without any marked success.

The introduction of the black diamond, or carbon points, as stone-cutting tools, however, seems to re-open the entire field again. In this material we have a substance harder than the hardest flint, and if properly applied to its work, capable of sustaining a vast amount of wear. It can be applied on the principle of either chipping or grinding. Drills pointed by it penetrate the hardest materials with astonishing facility.

Already several important machines for rock drilling, dressing millstones, etc., in which these points are employed, have been invented, patented, and successfully worked. It now remains for some enterprising genius to demonstrate that, by the use of these points, stone moldings may be cut as wood moldings now are, entirely by machinery.

A description of a new English machine, somewhat enthusiastically praised in the *London Builder*, will remind our readers of many attempts unsuccessfully made in this country, and the *Builder's* encomiums will therefore be received with some grains of allowance.

The machine is at work at Battersea, England. It consists of a bed made to travel longitudinally, with a shaft mounted over it for receiving the revolving cutting or molding head. So far, the machinery resembles that used for sawing; the head, however, instead of being a plain disk, with cutters, is shaped to the profile of the required molding, and has the cutters fixed in it according to that outline. The rough block being fixed on the bed, which is made to advance while the head revolves, the upper face of the stone is cut very nearly to the shape of the desired molding; the edges, however, are rather blunt, and the surface shows the tool marks. When this operation has been performed, a scraping tool, formed exactly to the molding, is fixed over the block; and the block being made to traverse several times under this scraper, has its face finished true and smooth, with sharp, clean edges, and the perfect profile required.

The *Builder* says that, by this machine, strings and molded steps are well worked in a remarkably short time. The cutters being built up, as it were, can be made to give any required outline, and their form is such that they work a considerable time without needing grinding. A large amount of work for St. Thomas's Hospital has been done by one of these machines.

The journal referred to also asserts that great saving of money and time is effected by this improvement, and it thinks the machinery can scarcely fail to come extensively into use.

Possibly it may, but we do not share our cotemporary's hopes in regard to it.

THE ELECTRO DEPOSITION OF COPPER AND BRASS.

The above is the title of a paper recently read before the British Association by W. H. Walenn. As we cannot give place for the whole of this paper in our columns, and as a review may be made to contain such portions as are not of purely theoretical interest, we shall endeavor to compress into the present article the practical information contained in it, abstracting perhaps some portions which may be of such a character as to be only properly given in the language of the author.

The commencement of the paper is devoted to a review of Smee's work on Electro-Metallurgy, published in 1851, in so far as it relates to the subject under discussion. Much attention is given by Smee to the electro deposition of copper, from acid as well as neutral solutions, and he alludes to the cyanide of potassium as a menstruum for dissolving copper when articles of iron are to be coated with the first-named metal; but he omits to notice the evolutions of hydrogen

during the deposition of the copper. He also gives five pages of his work to the discussion of the reduction of alloys in which, among other things, he mentions that zinc and copper have been deposited simultaneously by galvanic action, and afterwards alloyed by heat.

Mr. Walenn remarks that Smee was evidently not informed of Professor E. Davy's discoveries in 1830 (see "Phil. Trans," Vol. cxxi, pp. 147-164) or of the labors of M. de Roulz in 1841, or of Mr. C. Walker in 1845. Certain patented inventions also refer to electro-brassing at this early date, e.g., Fontaine Moreau's invention, No. 10,282, A.D. 1844; De la Salzedé's process, No. 11,878, A.D. 1847; Fontaine Moreau's plan, No. 12,523, A.D. 1849; Russell & Woolrich's discoveries embodied in No. 12,526, A.D. 1849; and Steele's patent, No. 13,216, A.D. 1850.

Smee undoubtedly believed that the evolution of hydrogen gas was evidence of the existence of the metal in the non-reguline form. At the present time, however, it is well known that there are solutions which deposit reguline metal during the copious evolution of hydrogen, and this generally takes place during the deposition of alloys. The views of Smee will not stand the test of vigorous experiment when alkaline solutions are employed.

In regard to alkaline solutions, Mr. Walenn remarks that if first principles be consulted, it will appear that, in alkaline solutions, the proneness to evolve hydrogen gas during deposition, arises from the joint action of two causes, one electrical, classified as such by Mr. Smee, the other chemical. The electrical cause is the small quantity of metal in solution in comparison to the electric power employed; this cause can be lessened or removed by using a solution that contains a greater percentage of metal than that usually employed. The chemical cause is the disposition of the metal of the alkali to go to the negative pole along with the heavy metal or metals, and thus, by being electro-deposited for an infinitely small space of time in contact with them, decomposing the water, thereby getting oxidized and setting free the hydrogen as a secondary effect; this cause can be eradicated by providing in excess a decomposable compound radical that will take a certain amount of combined oxygen with it to the cathode, and thus, when decomposed, will enable the hydrogen that would otherwise be evolved to be oxidized into water.

In the case of brass, a solution containing the cyanides of the component metals dissolved in excess of potassic cyanide, possesses the remarkable property of furnishing the copper and zinc to the cathode in such a form that, during deposition, they unite and form a true alloy; this tendency to form a true alloy is increased by the presence of a salt of ammonium, for in connection with copper the gas that would otherwise be given off is replaced by metal, this result being secondary, and, in so far, a chemical reaction. It is usually deemed sufficient to charge the solvent solution (the potassic cyanide and ammoniacal salt solution) with brass by electrolysis, but this will be found on trial to evolve gas, and to be only workable by two Grove's cells. The author finds that it is practically serviceable to add to a solution that is charged with not less than two ounces of brass per gallon, as much of the metallic cyanides as it will take up, and then it will probably take still more of the copper and zinc oxides respectively. Should this treatment not perfectly prevent the evolution of gas, the ammonide of copper is added—about two or three ounces per gallon.

In treating the ordinary cyanide copper solution for the prevention of the evolution of hydrogen, the zinc cyanides and oxides, mentioned in the instance of the brass solution, are left out. When the evolution of hydrogen gas has been stopped by the means above set forth, a single Smee's cell is sufficient to deposit the alloy, thus showing that an intense voltaic current is not absolutely necessary, but that the process requires a certain condition of solution to give a perfect result.

The author prefers to use a menstruum containing potassic cyanide and neutral ammonium tartrate in equal parts, and dissolved in five times their weight of water, to dissolve the brass in. This is then treated, as explained above, to prevent the evolution of hydrogen. This solution is employed in conjunction with heat, and a single Maynooth cell or a magneto-electric machine of suitable power. It has been found, with some electro-brassing solutions, difficult to deposit continuously a given quality of brass; with this solution, the regulation of the proportions of copper and zinc in the alloy is made by altering the heat accordingly. If the solution be kept uniform, as shown by a ready test, it is very easy to deposit a given alloy at all times.

In coating wrought or cast-iron work, it is often advisable to coat with copper prior to electro-brassing; the alkaline bath should be employed at above the temperature of the air, sometimes 160° Fah.; this method of working promotes the contact of the coating. The article should be well cleaned, so as to have a metallic appearance, with a pickle of weak sulphuric acid, scrubbed with sharp sand, washed, scrubbed with a portion of the depositing solution, and then placed in the depositing trough. The electrical connections may then be made, and the coating allowed to form for two hours or more. When a sufficient thickness had been obtained, the article is washed, and dried in hot mahogany sawdust. The "tarnishing" of the coating increases its beauty, and does not impair the article, for the tarnish is not corrosive rust, like the oxide of iron, but is a protective film. Two hours' coating will protect from rust in ordinary indoor work, but the best protection from rust (and this is serviceable even in damp air) is to give two hours' coating in an alkaline bath, and then let the article remain all night in an ordinary acid sulphate of copper bath. If desired, a brass coating may be given over the last-mentioned copper coating. By suitable

mechanical arrangements, the articles in the acid bath, and the dissolving plates therein, may be moved—preferably by a to-and-fro movement—during deposition. This treatment shortens the time of the deposit, and makes the deposit uniform.

The uses to which electro-brassing may be applied have yet to be greatly developed; among the rest may be mentioned: the prevention of rust; the giving of an improved printing surface to type and electro-types; coating the poles of electro-magnets for the prevention of the "residual charge" therein; covering rams, plungers, piston rods, rollers, etc., with an adhesive and durable coating; also lining cylinders, pumps, and iron vessels with copper or brass. The application of the processes that have been described to many purposes of ordinary life, such as railings, architectural ornaments, etc., will exemplify the good results to be obtained by the union of the strength of iron with the beauty of copper or brass.

THE USES OF APATITE.

Since the discovery of phosphate of lime in South Carolina, considerable attention has been bestowed upon the importance of working all similar deposits that may be found in any part of the country, and much inquiry has been made in consequence for mines of apatite, or mineral phosphate of lime. We understand that this mineral has been found in the neighborhood of Crown Point, in this State, also at some point on the Hudson, and quite extensively in Canada. As it is likely to become an important article of commerce, we propose to give some account of its properties and uses. In its crystalline form, the mineral closely resembles the beryl, or emerald; so slight is the difference that mineralogists have been constantly deceived by it, and it early received the name "apatite" from a Greek word signifying "to deceive." It occurs occasionally on our island of New York, in six-sided prisms, and we hear that it has also been met with massive, and in considerable quantity. It is one of our most valuable rocks, very little known to unprofessional men, and yet capable of extensive use in agriculture and the arts. It occurs in altered crystalline rocks, especially in granular limestone, and ores of tin, iron, and other metals, and with gneiss, syenite, and mica rocks. The color is not always the same, but the prevailing shade is green; we have also blue, grayish green, grayish white, and brown.

The Canada deposit is an extensive bed ten feet broad, three feet of which are pure, sea-green apatite. At Crown Point, the deposit is fibrous; in New Jersey, shafts have been sunk, and the apatite brought out in masses weighing occasionally 200 pounds.

The composition of apatite varies almost as much as its color, but it is essentially composed of phosphoric acid, 42.00; lime, 54.00; fluorine, chlorine, etc., 4.00. Many specimens, however, do not have more than 90 per cent of phosphate of lime. The occurrence of phosphorus in association with iron renders the ore useless for metallurgical purposes, but if the apatite be in sufficient quantity, it might be worked for superphosphates and fertilizers.

The uses of apatite are not many, but they are important. It has been proposed and used as a substitute for bone ash, and in the manufacture of porcelain and milk glass, and in England, the apatite from Estremadura is taken for this purpose.

In the manufacture of phosphorus, the pulverized mineral is mixed with twice its weight of silica, in the form of sand or ground quartz, and 25 per cent of charcoal, in a closed vessel, or peculiarly constructed furnace, and the whole heated to approaching white heat. The phosphate of lime is decomposed, and silicate of lime produced, and the phosphoric acid is reduced by the charcoal to the vapor of phosphorus, which passes into proper coolers, where it is condensed. The latest improvement is to add some soda to the quartz, thus producing a silicate of lime and soda, which is more readily fusible and more easily handled than the simple silicate.

The operation is carried on in France in something like a blast furnace, and is made continual by feeding with alternate layers of ore and fuel. In England, a native phosphate from the West Indies, called sonbrerite, is somewhat used in the manufacture of phosphorus; and as this material, together with the South Carolina deposits and the mines of apatite of Canada, is much nearer us, we ought to make an effort to introduce this industry among ourselves. At the present time, very little, if any, phosphorus is made in this country.

The acid phosphate of lime can be made, according to Horsford's patent, from native phosphates. The mineral phosphate is dissolved in nitric acid, of specific gravity 1.23, in the proportion of two nitric acid, by weight, to three of phosphate of lime; and to the filtered solution is added two parts, by weight, of oil of vitriol, diluted with water, for the purpose of removing the lime and other impurities. This process furnishes the acid phosphate of lime in superior condition, for medicinal and culinary purposes.

This use of apatite alone would be of the utmost importance, could it be carried out economically and on a large scale, as chemistry has introduced no compound of greater value in medicine and in food than Horsford's acid phosphate. But the use to which phosphorus has been applied more extensively than to any other, is in the manufacture of a fertilizer known as the superphosphate of lime. The manufacture of this article is carried on in England and Canada, and in some parts of the United States, and is of the utmost importance to our agriculture.

We find in the *American Chemist*, for February, an article by Mr. Gordon Broome, giving the methods employed in Canada for the manufacture of superphosphates from apatite. The mineral is ground by an engine of fifteen horse

power, which also turns the agitators during the treatment of the mineral by acid, and supplies steam to the sulphuric acid chambers adjacent to the mill. After the apatite is well pulverized, it is thoroughly mixed with oil of vitriol of the strength known as pan acid, in a suitable vat or tub, where it is thoroughly agitated until the conversion is deemed to be complete. The pasty mass is allowed to flow out of the bottom of the converter over the floor, where it soon becomes sufficiently dry to be fit for transportation in barrels, each containing about 286 pounds. It is, in this condition, only suited for agricultural purposes, as it is very impure. In a sample analyzed by Mr. Broome, there were found: Superphosphate of lime, 20.33; sulphate of lime (gypsum), 63.84; water, 5.50; other constituents, 10.33. The soluble phosphoric acid amounted to 12.33 per cent.

It is evident that this manufacture cannot be carried on profitably unless the same establishment manufactures its own sulphuric acid. As pan acid can be used, the expense of concentrating in glass or platinum vessels is saved, and the cost of packing and transportation avoided.

There is one serious difficulty encountered in the fumes of hydrofluoric acid that come off during the digestion of the mineral. These are very suffocating and dangerous, and it would be a valuable improvement if they could be condensed and made use of in the arts. This is done where fluor spar is employed as a flux in blast furnaces, and important applications are made of the acid thus economized.

In countries where hydrochloric acid is very abundant and cheap, it is substituted for sulphuric acid in the decomposition of apatite; but the resulting chloride of calcium absorbs water so rapidly, and keeps the mass so wet, that it is difficult to handle, and objectionable in every way. Manufacturers of artificial fertilizers sometimes remedy this evil by mixing various refuse animal matters with the mass, and then drying it, and at the same time adding to its value.

The chief importance of apatite is as a manure upon our crops. The strength of lands in the Eastern States has deteriorated so much that few crops can be profitably raised upon them, and it is becoming a serious question to decide what fertilizers are best adapted to remedy the evil. There seems to be no doubt that the phosphates are among the best enrichers of soil, and it is, therefore, important to have this industry more fully developed. To sum up the case for apatite, it will be seen that it has the following important uses;

1. In the manufacture of phosphorus.
2. Acid phosphate of lime.
3. Superphosphate of lime for manure.
4. Manufacture of porcelain.
5. Manufacture of milk glass.
6. Hydrofluoric acid, as an incidental product.

THE AVERAGE CITY DWELLING HOUSE.

The average city dwelling house of 1871 is not what it ought to be, when contrasted with the vast improvements made in all other departments of construction. Built to make as much show as possible with the least expenditure, it is a delusion to the inexperienced buyer, and a snare to the tenant, who has not yet learned the defects that a year or two of use will be sure to develop.

A young couple beginning their experience in house hunting and house keeping, after spending a week or two in discouraging search, at last find a tenement which seems adapted to their wants, at a rent which does not, perhaps, greatly exceed what they can afford to pay; or the house is, perhaps, purchased at what seems a reasonable price. The house is prettily painted, the walls are clean, white, and unbroken (being new), the modern improvements—including bath room, water closets, and gas fixtures—are seemingly convenient and substantial, and the courtyard is laid out with some show of taste. But ere long the walls show ugly seams and cracks; the doors shrink incontinently; the water fixtures obstinately refuse to be kept in order; the floor planking begins to creak, and the entire structure shows decided evidences of weak constitution.

The boiler which supplies hot water to the bath begins to develop troublesome leaks. The plumber is called to the rescue, and loads it with unsightly heaps of solder, which might almost be silver at the prices charged. It is astonishing how the specific gravity of solder increases in this sort of patching.

Then, by and by, the water is drawn off, and the goddess of the kitchen, through ignorance or neglect, lets the boiler collapse. The plumber is again called, who gives the comforting information that its thinness will not permit it to be re-rolled, at an expense of ten or twelve dollars, but that it is, and always was, a shabby affair, and if the luxury of warm bathing be continued, it must be at the expense of forty or fifty dollars for a new boiler.

Winter comes, and a new difficulty is experienced with the water pipes. Relying upon the fact that these are carried up between two buildings and inclosed in the walls, it is supposed they cannot freeze; but they do freeze, and burst; and walls, carpets, and furniture are injured, if not ruined, by the flood. Again the plumber is called. You can find plumber's shops as plenty as drug stores. No wonder; there is plenty of business going. The plumber is all smiles. He proceeds to demolish the plastering to reach the pipes, so that in addition to the damage by water, there is the damage by lime-dust. His labors completed, and his not small bill settled, the plasterer follows, careful not to let his work be speedily forgotten, by bespattering with mortar every available spot of floor and paint upon which his mark can be left.

Why water pipes should be placed under the plastering is a mystery to us, especially as they seem artfully contrived to give as much trouble as possible to the inhabitants of the average city dwelling house.