on which to put a counter balance, to round up the motion to make it run as steadily as if it were not a crank motion? I am going to make a thorough test, by putting on counter balance to overcome the weight of the gate. What is rour theory as to putting on balance opposite to the wrist, or must a fly wheel be put on of sufficient weight that the momentum will carry it past the dead centers so as to steady the motion and resistance of the cut of the saws?—E. F. J.

19.—THE SEA WAVES.—Can any one oblige me by answering the following questions? What is the average hight of the waves of the ocean, in a heavy sea, and also in an ordinary sea? What is the distance from the center of one wave to the other? What is the difference in the hight of the ends of an ordinary ocean steamer when the stern is in the trough of the sea and the bow on top of the wave in a heavy sea, and also the same in an ordinary sea?—J. G. H.

20.—PLUMBERS' SOLDER.—Will some one please tell me how much time is necessary to thoroughly eat all the impure metals out of plumbers'solder, and thequantity of water to put to the sulphuric acid? My object is to get the metal to retain its heat while in a semi-melted state (while wiping with the cloth) as quickly and at the least expense possible. Such metals as zine, iron, and bismuth give it a tendency to crystallize and to be porous and white instead of having a bright solid metallic shine when thejoint is wiped. We plumbers have always used sulphur with a little rain thrown into the pot while the metal is at a dull red heat, but ; that not only burns the zinc out, but also the tin, lead, and pot together.—W. S.

21.—PURITY OF WATER.—In the SCIENTIFIC AMERICAN for Feb. 17th is reprinted an article by Professor Chas. F. Chandler on the Effect of Animal Excreta in Water." As the majority of our population residing out of large cities is dependent on wells for its water supply, this is a matter of the greatest importance to thousands who, neverthele not aware of its importance. The points of the above article were included in a lecture, delivered by Professor Chandler about a year since, before the American Institute. Atthattime, he stated that there had not then been discovered any chemical test for discovering the presence of sewage contamination in water, nor was it apparent to the senses, except by its influ-ence on health. Has any method since been discovered for its easy detection tion? In villages and country towns especially, privies, cesspools and drains are unavoidably located unpleasantly near the wells, and this is used as a strong argument by those interested in the sale of earth closets. Com paratively few use earth closets at all, and of this number still less apply the system so thoroughly, to all sources of contamination, as to secure the advantages claimed therefor. Can Professor Chandler, or any one, point ou a feasible method of securing immunity (as society is at present constituted) from sewage poison? What amount of filtration through the different soils is necessary to secure perfectly pure water? Or in other words, as a privy or cesspool and a well must often exist within the limited enclosure of a village lot, what would be the nearest approach that would be admissible, while securing freedom from contamination?-J. Q.

## Answers to Correspondents.

SPECIAL NOTE.— This column is designed for the general interest and in struction of our readers, not for gratuitous replies to questions of a purch business or personal nature. We will publish such inquiries, however, when paid for as advertusements at 1 We a line, under the head of "Business and Personal.

ALL reference to backnumbers must be by volume and vage.

INDICATOR OF METALS.—W. H. L. is informed that there is no known substance that will attract gold, silver, or lead.

J. L. J., of R. I.—A. L. D., of Canada.—For the mechanical books you mention, Bourne's "Catechism of the Steam Engine," and Dussauce on "Perfumery," address H. C. Baird, Philadelphia.

CEMENT FOR ALABASTER.—In answer to query No. 7, page 90, Vol. XXVI., I would say that I have had success in cementing different kinds of stone together, and also stone to wood. I use plaster of Paris tempered with glue, mixed up in small quantities as needed. It takes some time to set.—E. B. M.

COPPER DIP FOR IRON CASTINGS.—Query 2, February 10, 1872. Dissolve two pounds sulphat<sup>o</sup> of copper in three gallons of water, and add two fluid ounces sulphuric acid.—K., of Conn.

RUBBER BOOTS.—J. R. M. can patch his rubber boots as follows: Rub the patch and boot thoroughly with sharp sand paper. Smear both with liquid rubber five times, every time letting them dry. Do this once more, and, before they dry, apply the patch, with pressure, if possible, and the boot is mended. If liquid rubber is not obtainable, dissolve small pieces of rubber, not vulcanized, in warm spirits of turpentine to the consistence of molssses in summer.—L. S., of N. Y.

WATERPROOFING BOOTS.—In answer to query 2, page 42 of current volume, I will say: Let C. B. take one pint neatsfoot oil, one pound old rubber boots, and one ounce rosin. Melt slowly, take out the fragments of the cloth of the old boots, and apply warm, say at 100° Fah. The boots will be water and snow proof.—C. E. G.

TENSILE STRENGTH OF SWEDISH IRON.—O. W. is in error in quoting our statement, as to the above, as from 120,000 pounds to 160,-000 pounds. Our figures (see page 107) are from 70,000 pounds to 112,000. Knut Styffe bears us out in this statement. On pp. 124 and 125 of the Enghsh edition of his work, he gives the breakingweight of puddled steel and puddled iron from Surahammer as ranging from 72,737 pounds to 111,857 pounds, and the average of all the results in this table is about 85,000.

HYDRAULIC CEMENT.—J. A. T., on page 106, can take lime which contains from twenty to thirty per cent of clay or finely divided silica and make it into mortar with water. Should he wish to make watertight joints for a slate cistern, or aquarium, or for filling up metallicjoints, let him take equal parts of red aud white lead and work them to a thick paste with boiled inseed oil. This hardens slowly.—R. T., of Ill.

VOLUME OF HYDROGEN.-W. W., page 90, current volume, will find 22,429 97-107 cubic inches in one ounce of hydrogen, being '0214 of a grain to one cubic inch.-R. T., of Ill.

SLIDE VALVE QUESTIONS.—Query 17, page 90, current vol. I more than agree with C. G. concerning the engine he has been repairing. I think there must have been some heavy rotary motion, either in the sh pe of fly wheel or mill stone, to carry the engine over the centers. I claim that any amount of lead that forces back against the crank before it gets to the center is a resistance; all the lead that is required is to overcome the *inertia* of the reciprocating parts, and this is **partially** accomplished by the lap of the valve cutting off the exhaust. I think that one thirty-second of an inch would be lead enough on the feed side, and about one sixteenth on the exhaust side. The more exhaust lead and lap of the valve there is, the less feed lead is required.—E. W. K.

W. C. A., of Mass.—The reason that low steam will not dry yarn as readily as high steam is that the yarn holds its moisture by adhesive attraction with such force as to require greater heat than the ordinary boiling point to expel it. The conditions for the evaporation of water under any circumstances are very different from those of heating a gas or mixture of gases. The force of the vapor of water at 212° is just that of the atmospheric pressure, and thus only surface evaporation from moist yarn could take place at this temperature. With higher temperatures, the water is converted into steam exceeding in expansive force the pressure of the air, and is thus expelled with greater or less rapidity.

LIGHT ENGINES FOR SAW MILLS.—In the SCIENTIFIC AMER ICAN of January 20, query 16, inquiry is made how can an engine of light power be made to run a saw and cut lumber in proportion to the po used. This is a subject which should be better understood than it is by many. There is no reason why a ten horse power should not be made to cut one half as much as a twenty, or a five horse power to cut one fourth as much. The common mistake made when engines of limited power are used is to run the saw with too high a motion. If a twenty horse engine can revolve a forty inch saw successfully at 300, a ten horse power should revolve the same saw at 150 revolutions in the same time, and a six horse power should revolve the same saw at 90. The difference in the power of the engines mu t be made in the revolutions of the saw, and not in the feed. Or, inother words, the cut of the saw for each revolution should be the same with the ten as with the twenty horse power engine. A fifty inch saw.run by the same power as a forty inch, should revolve one fourth slower, but should be made to cut one fourth more to each revolution Perhaps some will ask why the ten horse power may not run the saw with same number of revolutions as the twenty, making the difference in feed. But in this case it would have the same friction to overcome as the twenty, and consequently but a small part of its effective power would remain. One of the first things to do in applying a small power engine to run a saw mill is to enlarge the saw pulley. With an eight or ten horse powerportable engine of the usual order, the saw pulley should be made nearly or quite the size of the saw. If the saw is forty inches diameter the pulley should be made nearly the same.-S. W., of Ga.

G. L., of Vt.—In the long run you will find it better to carry the water to drive your proposed factory through a canal sixty rods than to attempt to transmit the power through that distance by compressed air and the aid of an engine. The expense of pipe and engine will nearly or quite construct the canal, unless very adverse circumstances in cutting the latter exist; and a canal will cost little or nothing for repairs.

POUNDING OF PISTON.—Query 12, February 3, 1872. To W. M. T. Your engine may be out of line, so that tightening any of the bearings may be only temporary relief. Engines that have run some years, working full capacity, frequently pound when passing centers from the shaft wearing flat in the crank bearing on the side next the crank pin, as this portion of the shaft takes the heaviest strain on either center. There is no remedy except to true up the shaft in a lathe, and refill the box. Watch the main bearing carefully, when the engine is running with a heavy load on, and see if the lost motion is not in the main box.— C. T. S.

E. S. E., of N. J.—I contend that it is impossible for a player of ball, in throwing or pitching the ball, by any particular "twist" or "screw" of the wrist, or by any possible device, to cause the ball to describe a curve in the air, that is, to turn to the right or left in the track of a curve after leaving his hand. Of course the parabolic curve which it makes in its fall to the earth is not referred to. I maintain that any regular body, such as a sphere or cube, hurled by the hand cannot be, unless blown by wind, made to go inany line except one in a strai ht vertical plane, and that the famous slow and deceptive pitchers in base ball have never yet succeeded in making a ball deflect to the right or left, in the form of a curve. The boomerang I suppose is irregular in form, and its motion, like all deviations of a flying body, is produced really by a compound force. Please settlethis point, as there is a wide diversity of opinion "about it among me who set themselves up as authorities.—E. S. E. Answer: You are right in every particular.

D. W. H., of Mo.—The friction of the earth upon the ordinary plow is greater upon the mold board than upon the land side and bottom together. Therefore, one half of the power used in drawing a plow is not wasted by friction on the land side and bottom.

R. G., of Nova Scotia.-We advise you to use steam pipes for your lumber drying room.

FACING OIL STONES.—The most convenient way to face oil stone that I have yet tried is to use No. 3 sand paper. I have used it for about six years, and have always found it effectual; and it is generally soconvenient that it can be done at short intervals, and thestone at all times kept in a good condition. I lay the sand paper upon a smooth and true surface, and in rubbing I confine myself to one half of the sheet until it is nearly rubbed down, to leave a sharp surface to finish up with. One sheet of sand paper ha; always answered for me, and it can be done in from the to twenty minutes.—H. W., of Ill.

# Becent Imerican and Loreign Latents.

Under this heading we shall publish weekly notes of some of the more prom nent home and foreign vatents.

CAR COUPLING.-John A. J. Chapman, Kansas city, Mo.-When two cars are uncoupled a dart headed link is held by one or the other, the free end of said link being held by springs in such a position as to freely enter the jaws of the opposite draw head. The spring, adjusted in strength and positio if r the purpose, presses against the inclosed dart head beneath it, and thus sustains the outer 'or free end of the link. The invention consists in at arrangement, of the springs described, with the pivot jaws and a combination with a car coupling, of bars, a compression spring, ratchet, and pinion, by which the proper movements and the desired attachment are made.

UPRIGHT PIANO FRAME.—Justin Whitney, Boston, Mass.—The frame stands upright, and forms the back, which supports the strings of the instrument, the strings being drawn across it over the bridge and sounding board. The sides and bottom of the frame are made in double angle form, and the trusses are of iron in the form of double Ts in cross section. The top is of Brregular form, the front portion being the bridge over which the strings wass. Like some other parts of planos—the legs, for instance, for square or horizontal planos—these frames are made for the "trade" and sold as an is drawn into a pocket formed in the stern of the boat, the projecting frames being dispensed with. In this case two rudders are preferably used near the sides of the boat.

CLOTH PLAITING MACHINE.—Joseph A. Sawyer, Worcester, Mass.—This very ingenious invention relates to a new mathine for plating fabrics to be used in the manufacture of shirt bosoms, and for other purposes. The invention consists in the use of several appliances for imparting and regulating the necessary motion and suiding the fabric. Seven distinct claims have been allowed on this invention which shirt manufacturers would do well to examine, as we regard it as one of much importance to this line of business.

WASHING MACHINE.—Henry S. See, Evansburg, Pa.—The clothes to be washed are placed upon the bed, and a reciprocating motion is given to a rubbing frame, which carries a rubber over the clothes. The rubbing frame acts as a lever, the rubber being the fulcrum. A reciprocating frame, in combination with spindles, rollers, standards, springs and pins, is employed in combination also with a board pivoted to side pieces and arranged with the bed.\_

WAIL GUARDS FOR FURNITURE.—James L. Brander, Boston, Mass.—The object of this invention is to provide a cheap, safe, and convenient means for preventing the defacement of the walls of parlors and other apartments by the backs of sofas, lounges, or other simil *i* articles of furiture. It consists in a guard, of crescent shape, screwed to the floor so that the front or concave side shall receive the leg of the sofa, lounge, or other article, and so that the guard shall act as a stop to prevent the back of the article from touching the wall of the room.

WASHING MACHINE. - Martin Wayand Frank Way, of Springfield, Ohio. --ThisInvention relates to a new washing machine of extremely simple construction. A frame supports the wash tub, which has a cover, the cover having a hinged lid over a central aperture. Vertical posts are attached to and under the cover, extending not quite to the bottom. A crank shaft, swipelled in thelid, carries a forked frame. By operating the crank, the frame rubs the clothes against the posts and thereby cleanses them from dirt.

TIME LOCK FOR BURGLAR PROOF SAFES. -- John Burge, of Circlevil'e, Ohio. -- This lock is placed upon the inside doors of vaults or safes, and moved and operated by clock work, so that no keyhole or other aperture through the door is necessary. A mechanism composed of a revolving cam wheel and actuating plate and springs is employed, by means of which a continuous motion in one direction locks and unlocks the door. The inventor does not confine himself to asy peculiar clockwork or mechanism for this purpose, but designs to use any motive power within the safe or vault by which the purpose may be effected. Neicher does he limit or confine himself to the precise form or arrangement of any of the parts described, as they may be varied in many ways without departing from the invention.

BEER FORCING APPARATUS.—William H. Otto and Peter Korper, of Tremont, Pa.—This invention has for its object to furnish an improved apparatis for forcing beer out of the kez. It consists in the construction and combination of an apparatus by which, on opening a stop cock and the faucet of the beerkeg, the beer will be forced out violently from the keg. The beer keg may be placed at any desired distance from the operating parts of the apparatus, which may be placed beneath the bar, or in any other convenient place.

BIN FOR STORING AND DRYING GRAIN.-Jarvis Royal, of White Rock, Ill. -This invention is an improvement in the construction of bins, boxes, ships. boats, etc., in which grain or other substances are placed for storage or transportation, so that the substances placed in them-whether grain, fruits, flesh or fish, salt or sugar-may be dried and thus preserved from injury from dampiess; and it consists in lining the inside of the bins with porous pricks or tiles. The bricks or tiles may be secured in place by a slight frame work, or in anyother convenient manner. In case plain brick or tile are used to line the bin when made close, thin laths should he placed along the sides and bottom of the bin for the bricks or tiles to rest against, so as to form channels or openings for the ingress of the air. In some cases—as, for instance, in grain boats and ships-it may be advisable to line the lower part of the bin with thicker and heavier brick or tile than is necessary for the sides or upper parts. By this construction the porous bricks or ti es will, it is claimed, absorb the water from the grain or other substance, which, com-ng in contact with the air in the chamber or corrugations, is evaporated. ng in contact with the air in the chamber or corrugations, is This process of absorption and evaporation continues until all the grain in the bin is sufficiently dried. The claim is based upon the interposition of theselaths so as to form the open spaces oetween the bricks or tiles and the outer walls of the bin.

CARRIAGE WHERES.—Charles H. Appel, of Allentown, Pa.—This invention pertains to an improvemen in the devices for securing the spokes of carriage wheels in the sockets of their wooden hubs; the invention consists of  $\varepsilon$  detachable metallic ring or collar, provided with dovetailed lngs, in combination with the spokes and wooden hub.

FISHING APPARATUS.—Orange M. Fuller, of Catasauqua, Pa.—This invention consists of a float from which the line is suspended by a trip lever and spring in such a manner that when a fish takes hold of the hook and pulls on the line, the spring will be tripped by the lever and the fish will be nooked; also a weighted arm, held in a horizontal position by the spring, will be let fall to raise a flag as a signal that a fish is taken, and the hook will be pulled in by the spring, so as to fasten the fish, the said float being connected by a long line to a reel in the hands of the operator, to be pulled in by him to secure the fish.

ORE AND STONE CRUSHER.—Robert Learmouth. of Buffalo, N. Y.—A method of adjusting the stationary law, by means of detachable links formed of different lengths, constitutes this invention. In other respects the construction does not differ from other stone crushers in use.

VISE.—John Peace, of Camden, N. J.—The vise is placed on horizontal and vertical swivels, so it can be turned in suitable direction to hold the work in convenient position. The invention consists in a new general arrangement of parts, and also in a new application of the proper jaws. A flaoged and flat sided screw, provided on opposite sides with jaws, when combined with and swiveled to a nut, constitute the claim on which a patent has been obtained.

CASTERS FOR FURNITURE.-William Ireland Blackman, of Columbus, Miss.-This invention relates to an improvement in casters for furniture. It consists in the mode of confining the ball and securing the caster to the leg. A shell in which the ball is confined, having a shank, a fastening ring, a thimble, and a holding pin are the several parts of the device. The shell and shank are made in two pieces, forming a globular opening for the ball and a tapering shank for the leg. The main bearing or the ball is at the center of the globular opening shove; but, to reduce the frictional surface of the shell, there is a small rib with which the center of the ball comes in contact. fourth of the r of the ball projects bottom of the thimble rests up in a shoulder and a collar of the thimble ests upon the top of the fastening ring, while the ring itself rests upon the shoulder. The fastening ring is secured to the end of the leg. The ends one or both) of the holding pin project from the shank over the edge of the thimble, which prevents the caster dropping from the leg when the piece of urniture is raised. In some cases the entire shell and shank will be let into theleg, in which case a larger ring will be used. STONE LIFTER AND STUMP EXTRACTOR.-Josiah Knoop, Casstown, O. -The invention consists in several improvements, upon the portable stone lifters and stump extractors heretofor e known to the public, by which the inventor has produced a durable and convenient machine, peculiarly well adapted to its purpose. It seems to provide pretty effectively for all the accidents to which such machines are liable, and to economize the power required in producing the desired effect.

POUNDING OF PISTON.—Query 12, page 90, current volume. To W. M. T. I hink the pounding in your engine arises from the connection of the piston rod and the cross head; if this is the case, there will be some difference in sound; for, as the engine starts on the front stroke, it forces the piston rod into the beveled socket in the cross head; whereas when it commences its return stroke, it withdraws from the socket against the key. A very little play in this joint will make a good deal of noise.—E. W. K.

D. S., of Pa.—The insurance companies have good reason to charge higher rates for woolen mills heated by steam pipes, in which buildings woolen waste, wood, and other rubbish about the mill are allowed to come in contact with the pipes. Woolen waste often takes fire spontaneously when oily, and so will wood shavings. The danger of this is much increased by artificial heat, even though the latter is not intense enough to ignite these substances directly.

or horizontal planos—these frames are made for the "trade" and sold as an article of commerce, the form or size of the frames being varied to suit different plano manufacturers.

PROPELLING BOATS. -Charles Dancker, Hoboken, N. J.-In the stern portion of a canal boat is hung a transverse crank shaft, to which oscillating motion is imparted by means of steam or other power. The cranks of the shaft are connected to the front ends of rods that extend backward through the stern of the boat, where they are packed water tight. The motions of the rock shaft serve to move the rock back and forth. To the outer end of sach rod, behind the stern of the vessel, is pivoted a metallic or wooden blade, or suitable width and length the pivot pin being rigidly attached to the rod. To said pin is also secured a metal or wooden plate, which has its ends guided in grooves or tracks provided in backwardly projecting frames of the boat. The said frames also hold transve se pins or friction rollers, upon which the propeller blades rest. As the rods move outwardly they push the blades back, and cause them to gradually drop from a horizontal into a vertical position by bringing its pivot gradually nearer to the supporting pin. The blade crowds the more against the water the more it is brough into a vertical position, the covering plate to which it is attached preventing the water from escaping over the top. In moving forward, the rod draws the blade gradually into a horizontal position, and prevents it from hindering an advance of the boat. The rudder is hung in cross pieces that connect with the projecting frame. One or more rods, blades and plate may be applied to one boat. The space inclosed by the frames maybe closed on top if desired. A modification of the invention is one in which the blade i small cost of about 30 cents a panel.

CULTIVATING PLOW.—Cealy Billups, Norfolk, Va.—The invention consists in constructing two wing mold boards so that they can be reversed on the cultivator plow and thus made to represent two different sizes and widths. The same wings will thus serve for all stages in the growth e of the plant and never require to be left off the plow.

FENCE.—Alfred M. Aplin, Chetopah, Kan.—The invention consists in forming a fence of tubular clay posts placed close together in the ground and hel' in line by top caps at suitable intervals. This fence dispenses entirely with rails, is almost imperishable, and yet may be made at the small cost of about 30 cents a panel.

# Scientific American.

. 123,948 5,554 and 5,555.-CARPETS.-D. Paton, New York city. . 123,774 5,556 .- CROQUET IMPLEMENT.-J. W. Pettengill, Rockford, Ill. , 123,914 TRADE MARKS REGISTERED. . 123,860 . 123,787 658.-GIN.-Adams & Taylor, Boston, Mass. . 123,819 659. -WHISKEY. -Adams & Taylor, Boston, Mass. . 123,784 660 and 661.-KNITTING COTTONS.-J. Attwell, Jr., New York city. 662.-WELTING CORD.-J. Atwell, Jr., New York city. 663.-CALICO PRINTS.-Coffin & Altemus, Philadelphia, Pa. . 123,851 . 123,885 . 123,906 664.—Refrigerators and Water Coolers.—A. M. Lesley, New York city. 123,834 665.-CONCENTRATED AMMONIATE. -Navassa Phosphate Co., New York city. 666. -CUTLERY.-G. Wostenholm & Son, Sheffield, England. . 123,940 . 123,929 123,917 APPLICATIONS FOR EXTENSIONS 123,80 Applications have been duly filed and are now pendingfor the extension . 123,835 of the following Letters Patent. Hearings upon the respective applications . 123,817 are appointed for the days hereinafter mentioned : 20,227, -HARVESTER.-J. S. Troxel. April 24, 1872. . 123.863 . 123,880 28,512. -CAR WHEEL -S. P. Smith. May 1, 1872. . 123.804 20.249.-HULLING CLOVER, ETC. -J. C. Birdsell. May 1, 1872. 123,923 20,306.—Affixing Stamps to Letters.—G. K. Snow. May 1, 1872. . 123.958 . 123,952 EXTENSIONS GRANTED. . 123,949 19,384.-BANK CHECK CANCELER.-William M. Simpson. . 123,86 19,377.-HARVESTER.-F. Nishwitz. 19,377.-HARVESTER.-F. Nishwitz. . 123.905 . 123,810 19,483.-HARVESTER.-J. S. Butterfield. . 123,931 19,347.-RUBBER MAT.-E. F. Chaffee. . 123,899 19,846.-PROPELLING BOAT.-H. Camp. 123.934 19,398.-HYDRAULIC VALVE.-C. and G. M. Woodward. . 123,837 19,870.-KNITTING MACHINE .-- J. K. and E. E. Kilbourn. 4,765 19,849.-SHINGLE MACHINE.-G. Craine. . 123,94 123.819 SCHEDULE OF PATENT FEES: 

 SCHEDULE OF PATENT FRES:
 510

 On each Caveat
 510

 On each Trade-Mark.
 555

 On listing each orginal Patent.
 510

 On asport to Examiners-in-Chief.
 510

 On appeal to Commissioner of Patents.
 520

 On application for Relasue
 520

 On application for Relasue
 530

 On spille to Commissioner of Patents.
 530

 On spilleation for Relasue
 530

 On grading the Extension of Patent.
 530

 On an application for Design (three and a half years).
 515

 On an application for Design (corteen years).
 515

 On an application for Design (fortree years).
 515

 On an application for Design (seven years).
 515

 On an application for Design (fortree years).
 530

, 123,814 123,839 122,864 123,96 123,831 128,823 123,907 128,85 123,821 123,927 123,96 For Copy of Claim of any Patent issued within 30 years..... 123,811 ....\$1 A sketch from the model or drawing, relating to such portion of a machine 123,812 123,90 123,78 123,850 The full Specification of any patent issuedsince Nov. 20, 1866 at which time 123,841 123,827 123.92 involved and the number of views. 123,94 Full information as to price of drawings in each case, may be had by 123,954 addressing 123,89 MUNN & CO., 123.957 Patent Solicitors, 37 Park Row, New York, 123,85 123.838 Value of Extended Patents. 123,86 Didpatentees realize the fact that their inventions are likely to be more 123,873 productive of profit during the seven years of extension than the first 123,80 all term for which their patents were granted, we think more would avail 123,875 themselves of the extension privilege. Patents granted prior to 1861 may be 123,921 extended for seven years, for the benefit of the inventor, or of his heirs in case 123,935 of the decease of the former, by due application to the Patent Office, ninety 123,76 days before the termination of the patent. The extended time inures to 123,922 thebenefit of the inventor, the assignees under the first term having no 123,93 rights under the extension, except by special agreement. The Government tee for an extension is \$100, and it is necessary that good professional service 123,763 123,88 be obtained to conduct the business before the Patent Office. Full informa-4.763 , 123,945 tion as to extensions may be had by addressing MUNN & CO., 37 Park Row 4.764 123,95 Inventions Patented in England by Americans. 123,964 From January 26 to February 8, 1872, inclusive. [Compiled from the Commissioners of Patents' Journal.] ALARUM FOR GRIST MILL.-T. Glasspool, Minneapolis, Minn. BURNING HYDROCARBONS.-J. K. Cald well, Philadelphia, Pa. 123,92 123.892 123,852 123,775 CARPETS, ETC .- W. Webster, Morrisania, N. Y., and C. M. Meserole, New 123,910 York city. 123.788 COMBINING MINERALS AND VEGETABLES. - A. Hitchcock, New York city. 123,772 DETECTING LEAKAGE, ETC.-A. G. Myers, New York city. 123,915 ENGINE OPERATED BY EXPLOSION .- J. S. Foster, Salem, Mass. 123,802 FIRE ARM.-A. Burgess, Owego, N. Y. FLUTING MACHINE, ETC.-T. M. Tucker, Newark, N. J. 123.871 123,956 GLOVES, ETC.-J. Harrison, Chicago, Ill. IRON AND STEEL.-C. M. Nes, York, Pa. 123,867 123,843 KILN.-A. R. Morgan, New York city. 123,855 LAMP BURNER.-A. G. Myers, New York city. METAL KNITTED FABRICS, ETC.-W. Edge, Newark, N. J. 123,916 123,842 NAIL MACHINE.-J. Lawrence, Philadelphia, Pa. 123,900 ORDIANCE.-D. Macomber, Utlea, N. Y. PACKING PAVEMENT, ETC.-B. B. Hotchkiss, New York city. 123,773 128,856 PAVEMENT.-B. B. Hotchkiss, New York city. 123,80 PEGGING MACHINE.-L. R. Blake, Fort Wayne, Ind. 123,829 PREPARING HOPS, ETC. - D. A. Clarke, Baltimore, Md. 123,818 SEWING LEATHER, ETC.-G. V. Sheffleld, Providence, and G. K. Mello 123,878 Woonsocket, R. I. 4,970 \_\_\_\_\_ 123.881 Foreign Patents. 128,909 The population of Great Britain is \$1,000,000; of France, \$7,000,000; Bel-gium, 5,000,000; Austria, 86,000,000; Prussia, 40,000,000; and Russia, 70,000,000 123,760 123,790 Patents may be secured by American citizens in all of these countries. Now is the time, while business is dull at home, to take advantage of these 123,936 123,779 immense foreign fields. Mechanical improvements of all kinds are always

ANIMAL TRAP. -- Lawrence Lewis, of Tuskegee, Ala.-This invention has for its object to furnish an improved trap for catching rats, mice, and other animals. The animal, in trying to reach the bait, steps upon a platform, which withdraws a catch from the door of a box and allows the door to be revolved, through a quarter of a revolution, into a vertical position, when its upper edge is caught and held by another catch. The slam of the door frightens the animal, which, seeking to escape, rushes through the passage way leading into a rear compartment, raising another door in his passage which movement operates a lever, releases the first door, and allows it to be revolved into a horizontal position, again setting the trap.

HAY LOADER.-Thomas Giffin, of Perrysville, Ohio.-Thisinvention has for its object to furnish an improved machine for loading hay spread upon the ground directly upon the wagon. It consists in the construction and arrangement of bearings and castings arranged upon an axle and the frame work of the machine, with a combination of rake teeth and guides with a frame work and a carrier.

HARVESTER. - Ernst Henry Ruwe, of Walcott, Iowa, - A revolving rake or scraper, having mechanism to carry it over a double track is employed in this invention. The platform is projected beyond the divider and is turned upon a curve corresponding to the orbit described by the passing scraper. By this construction not only is an auxiliary divider furnished which will press the standing grain out of the way of the revolving rake, but an extension which effectually prevents, by its acclivity, the strawfrom working over the edge of the platform. A rod placed longitudinally across the platform and directly in the rear of the cutter bar, holds up the butts of the straw and prevents the scraper from passing over them. A cross bar, with its fingers and a double rail, causes the endles chains to move uniformly and without wabbling.

## [OFFICIAL.]

# **Index of Inventions**

# For which Letters Patent of the United States were granted

FOR THE WEEK ENDING FEBRUARY 20, 1872, AND EACH

# BEARING THAT DATE.

Amalgamator, Langtry and Emmett	123,918	P
Amalgamator for gold and silver, voltaic, J. H. Ráe/	123,982	P
Auger, well, F. Spees	123,847	P
Bag, traveling, F. Lagowitz	123,830	Р
Bale tie, cotton, G. W. Adams	123,853	Р
Baling short cut hay and straw, w. Hadwin	123,824	Р
Bee hive. J. E. Moore	123,924	Р
Bench, folding wash, J. N. Valley	123,935	P
Billiard fables, leveling jack for, Paxton and Hull	123,791	Ŗ
Bisulphiles, apparatus for the manufacture of, w. J. Turner	100,009	P
Boller culinary J. Gibba	123,500	P
Boller culinary J. D. Durham	123,000	P
Boiler, steam M Smart	123,845	P
Boiler, sectional steam. D. Renshaw	123,793	P
Boiler low water alarm and fire extinguisher, steam, B. R. Singleton	123,795	
Bolts, machine for forging heads of. J. Greenwood	123.822	r D
Book binding, G. Smith	123,947	Г
Bootjack, T. Anthony	123,759	P
Boot and shoe heels, burnishing, A. C. McKnight	123,785	P
Boring tool, G. W. Moore	123,786	p
Bottlestopper, Malmstrom and Dummer	123,920	P
Bottle stopper, P. R. Higley	123,898	R
Bracket, leader, S. J. Dwyer	123.877	R
Brakes, coupling for steam or air, S. N. Goodale	128,776	'S
Brush, blacking, N. Eisenmann	123,815	S
Buckle, bridic, D. S. Butler	123,866	S
Burner, vapor, H. Fayette	123,879	S
Burners, suspending glass bowls under gas, J. C. Conner	123,870	S
Car brake, G. H. Reynolds	123,840	S
Car, dumping, C. Barrett	123,762	S
Car window, w. McCauli	123,833	8
Car link guide for compling N. J. Post	123,919	S
Car wheels upon a view adjusting. I. Keiser	198 013	S
Carbureters sinhon can for R.S. Oshorn	123 926	S
Carding machines, roll for, E. J. Worcester	123 968	Se
Carriage. L. W. Coe	123,809	8
Carriage wheel. A. M. Ocobock	123.836	81
Carriage spring and mode of attachment, C. W. Saladee	123,937	8
Carriage tops. slat iron for. J. W. Sheppard	123.942	8
Carriages, handle for children's, J. H. White	123,960	2
Cartridge box, J. W. Frazier123,883,	123,884	8
Caster, pickle, H. C. Wilcox	128.961	81
Chair, folding, C. Marcher,	123,832	S
Chill for casting chilled rolls, R. Tolmie	123,953	S
Chimney, steamboat, C. and R. Hawthorn	128,896	SI
Chimney, steamboat, W. J. Hamilton	123,825	S
Cloth, method of drying napped, W. Chapin	123,768	S
Cock, valve, S. Adams (reissue)	4,762	т
Comin from paper or other pulp, F. Keenan	123,781	Т
Corn sheliers, A. Adams	123,758	Т
Cultivator seeder and stalk cutter combined J and W Whait	192 050	Т
Curtain france E T Briggs	193 961	Т
Cutter head A Van Vleek	123,800	Т
Desk school W A Slavmaker 193796	123 797	Т
Digger. notato. Wing and Green	128,966	T
Digger, potato, W. W. Speer	123,846	T
Diseases in vacuo, treating, R. S. Gee	123.887	T
Drawing frames, stop motion for, D. W. Hayden	123,826	T
Dredge box, W. S. Potwin	123,792	T
Drilling machine, W. and J. Gardam	123,886	T
Earth closet, A. A. Jaqua	123,780	T
Electromagnetic annunciator, C. E. Chinnock	123,808	
	400 844	ιU

Horse collar, A. Snively	123,948
Horse power, L. R. Faught	123,014
Iron, etc., machinery for puddling, V. S. Bloomhaft	123.860
Iron, manufacture of metal coatcd sheet. B. Morison	123.787
Ironing machine, A. G. Gardner	123,819
Jack, lifting, C. A. Masterson	123,784
Jar, preserve, A. Q. Withers	123,851
Knapsack, J. W. Frazier	123,885
Label gumming apparatus, J. H. Hudson	123,906
Ladder, extension, L. N. Millener	123,884
Lamp, I. W. Shaler	123,940
Lamp, carbureting, Porter and Gray	123,929
Lamp wick, C. P. Ladd	123,917
Lamp or holder, candle, M. Weis	123,803
Last, W. J. B. MIIIS	100,000
Lather solf contaring chuck for C. O. Proklar	192 062
Lattices, self-centering chuck for, G. O. Buckley	123,003
Lifting apparatus G. B. Windshin	123,804
Light electric. A. A. Mevnial	123,923
Lightning rod, D. F. Welsh	123,958
Loom picking mechanism. E. P. Terrel	123,952
Lubricator, axle, Soellinger and Noetzli	123,949
Lubricator, car axle, W.P. Burrow	123,865
Match, safety, H. Howse	123,905
Mattress, etc., material forfilling, F. C. Cone	123,810
Measure, lumber, W. S. Poulson	123,931
Meat mincer, Holzwarth, Froelsch and Gerhards	123,899
Medical compound, P. Roskopf	123,934
Metal vessels, collar for sheet, J. M. Patterson	123,837
Metal ware, machine for stamping sheet, W. D. Grimshaw, (reissue)	4,765
Meter, water, G. Sickles	123,946
Milk cooler, C. A. Douglas	123,813
Mill, fanning, J. Drummond	123,814
Moustache guard, E. J. F. Randolph	123,839
Mowing machine, J. J. and F. Bulfinch	122,864
Musical instrument, A. Young	123,969
Nuts, device for locking, S. B. Lowe	123,831
Nuts, manufacture of screw threaded, C. H. Guard	128,823
Dil, distilling coal, S. Hudson	123,907
Jii tanks, apparatus for ning and emptying, D. Birdsail	128,859
Du abasa dia far manufasturing B. S. Barker	123,821
Data shoes, die for manufacturing, B. S. Parker	123,927
Papar hag I C Crowell	100 611
Paper Dag, L. C. Crowell	102 010
Paper ontting machine P. H. Honking	100,016
Paper Cutting machine, I. I. Hopkins	100,001
Paper, agure inited, Da Monte and Saxe	123,10
Perging mechine awi for E. P. Richardson	123 841
Pen. ruling. E. Ingram	123.827
Pencils, press for stamping lead. T. H. Muller	123.925
Perch irons, die for making, J. W. Sheppard	123,948
Pipejoint. S. Trumbore	123,954
Piston packing, G. Gwynn.	123,891
Plow. J. Wallace	123,957
Plow, C. Billups	123,858
Plow colter, J. Pinkham	123,838
Plow, gang, F. G. Charles	123,869
Plow, ice, J. H. Cutter	123,873
Plowshares, apparatus for forming, E. Ball, Jr	123,805
Potash, etc., manufacture of sulphates of, H. Deacon	123,875
Printing yarn, W. McAllister	123,921
Printing machinery, plate, J. T. Robertson	123,935
Pump, ste am, G. F. Blake	123,766
ump valve, D. Metz	123,922
Sack, tollet, D. A. Russell	123,935
siveting machine, J. Berry	123,703
an mill granter I. P. Grassenor (reigene)	160,000
Saw grinding machine. C. T. Shoemaker	±,103
aw mills head block for D. Lane (reissne)	4.764
crew cutting machine. L. W. Stockwell	123,951
Scythe blades, manufacture of, N. P. H. Willis	123,964
eats and desks, joint for, J. Peard	123,928
ewing machine, T. Hall	123,892
lewing machine, Q. M. Youngs	123,852
ewing machine treadle, C. A. Foster	123 <b>,7</b> 75
ewing machines, ruffling attachment for, A. Johnston	123,910
ewing machines, ruffling attachment for, H. Moschcowitz	123,788
lewing machines, thread cutter for, G. H. Dimond	123,772
haft socket, F. Kern	123,915
hutter, rolling, Von Langen and Robb	123,802
lign, J. H. and C. W. Crane	123,871
oldering gas sock for, Walker and Jones	123,956
pinning machines, spindle and whorl for, W. T. Carroll	123,867
prings for doors and gates, C. W. Saladee	123,843
tone little and stump extractor I. Frace	190 010
there eaching C. Bider	100 040
toye, looking, G. Ryner.	102 000
ugar plums, machine for manufacturing. Dniour and Couppe	120 9
unnorter, uterine, L. A. Rahcock	123,900
	123,900 123,773 128,856
able, folding, A. C. Ballard	123,500 123,773 128,856
able, folding, A. C. Ballard	123,500 123,773 128,856 123,806 123,890
able, folding, A. C. Ballard	123,500 123,573 128,856 123,806 123,829 123,818
able, folding, A. C. Ballard able, sofa, and bed, combined, D. Katzenstein fables, drop leaf attachment for sewing machine, E. F. French elegraph insulator, D. R. P. Emminger	123,900 123,773 128,856 123,806 123,829 123,818 123,818
'able, folding, A. C. Ballard	123,900 123,773 128,856 123,806 123,829 123,818 123,878 123,878 4,970
'able, folding, A. C. Ballard	123,500 123,773 128,856 123,806 123,829 123,818 123,878 4,970 123,881
"able, folding, A. C. Ballard	123,900 123,773 128,856 123,806 123,829 123,818 123,878 4,970 123,881 128,909
"able, folding, A. C. Ballard	123,500 123,773 128,856 123,806 123,829 123,818 123,878 4,970 123,881 128,909 123,760
'able, folding, A. C. Ballard	123,500 123,773 128,856 123,829 123,818 123,818 123,878 4,970 123,881 128,909 123,760 123,790
'able, folding, A. C. Ballard	123,530 123,773 128,856 123,829 123,818 123,878 4,970 123,881 128,909 123,760 123,790 123,936
'able, folding, A. C. Ballard	123,500 123,773 128,856 123,806 123,829 123,818 123,878 4,970 123,881 128,909 123,760 123,790 123,936 123,779
"able, folding, A. C. Ballard"      "able, sofa, and bed, combined, D. Katzenstein"      "ables, drop leaf attachment for sewing machine, E. F. French"      "elegraph insulator, D. R. P. Emminger"      "elegraph insulator, D. R. P. Emminger"      "elegraph, signal box for fre, Wright, Holley and Miles, (reissue)"      "hill coupling, W. G. Foster"      "balco, treating, J. Ashcroft"      "cop joint, etc., C. W. Saladee"      "trap, anima, J. M. Hill"      "trap, fiy, D. Henderson"	123,500 123,773 128,856 123,829 123,818 123,878 4,970 123,881 128,909 123,760 123,790 123,936 123,779 123,897
Pable, folding, A. C. Ballard	123,500 123,773 128,856 123,826 123,828 123,818 123,818 123,878 4,970 123,881 123,878 123,790 123,936 123,779 123,897 123,807
'able, folding, A. C. Ballard	123,500 123,773 128,856 123,829 123,818 123,818 123,818 123,818 123,818 123,878 123,790 123,936 123,779 123,897 123,807 123,807 123,807

Electromagnetic annunciator, C. E. Chinnock 123,808	Imprellag device for opening or closing E.P. Jones 193.919	
Elevator, C. W. Baldwin 123,761	Value aloba E Theren 199.942	
Engine, compound reciprocating, H. Bertieaux 123,857	Valve, globe, E. Illayer	
Engines, valve for direct acting, G. F. Blake	Valve, self-acting water, J. N. Deck.	
Fastener, door or shutter, W. Fields 123,816	Ventilator, car, w. G. Creamer 123,770	
Faucet, bush for, Netzow and Heck 123,789	Vise, Crawley and Baylies 123,872	
Fence, A. M. Alpin	Washing machine, J. C. Hallenbeck 123,898	
Fence flood R S Gilcrest 123 839	Washing machine, P. B. Bristol 123,862	
Files, machine for cutting, A. Weed	Watch case spring, C. Tribby 123,798	
Fire arms projectile for S E Jones 123828	Water wheel, J. Tort, (reissue) 4,766	
Fire extinguisher C. L. Levey 193783	Weeding machine, A. H. Sherwood 123,944	
Fire extinguisher for steam boilers A. C. Davids 199.974	Wells, formation of drive, E. S. Hovey 123,903	
Fine excloguisher for steam bollers, A. G. Davius	Whip socket, L. C. Clark 123,769	
Fruit DOX, J. Shepsiu	Wood, etc., composition for preserving, G. A. and P. C. Vivien 128.801	
Fuero ateam boiles O II For	Wringer, clothes, E. P. Russell 123,794	
Furnace, steam boller, C. H. Fox	Yarn, machine for drying, R. Hartman 123,895	
Furnace for smelting fron, S. W. Harris		
Furniture, fender for, G. R. Wilmot 123,965		
Gas from petroleum, manufacture of, W. H. Spencer 123,950	DESIGNS PATENTED.	
Gate, J. J. and J. T. Hoss 123,902		
Gate, children's nursery, E. Howard 123,904	5,548.—CUTLERY BOLSTER.—M. Chapman, Greenfield, Mass.	
Gin, cotton, J. G. Case 123,868	5,544. — CHAIN LINK. — V. Draper, North Attleborough, Mass.	
Governor, automatic, Jones and Hall 123,911	5,545.—CHAIN BAR.—V. Draper, North Attleborough, Mass.	
Governor, steam engine, I. S. Schuyler 123,939	f. S. Schuyler	
Grain binder, C. B. Withington 123,967	23,967 5,547PARLOR STOVEJ. Martino and J. Currie, Philadelphia, Pa.	
Hair curling pin, J. Hall 123,778		
Harvesters, machine for grinding cutter bars for, J. H. and J.S. Griffin 123,890	resters, machine for grinding cutter bars for, J. H. and J.S. Griffin 123,890   5,549 to 5,552. — CARPETS. — W. McCallum, Yonkers, N. Y.	
Heater boiler, steam, F. Brackney 123,767	5,558Sopa FountainG. F. Meacham, Newton, Mass.	

in foreign countries by Americans are obtained through our Agency. Ad-123,912 dress MUNN & Co., 87 Park Row, New York. Circulars with full informa-tion on foreign patents. furnished free.

in demand in Europe. There will never be a better time than the present

to take patents abroad. We have reliable business connections with the

principal capitals of Europe. A large share of all the patents secured

## FOREIGN PATENTS ... A HINT TO PATENTEES.

It is generally much better to apply for foreign patents simultaneously with the application in the United States. If this cannot be conveniently done, as little time as possible should be lost after the patent is issued, as the laws in some foreign countries allow patents to any who first makes the application, and in this way many inventors are deprived of valid patents for their own inventions. It should also be borne in mind that a patent is issued in England to the first introducer, without regard to the rights of the real inventor; therefore, it is important that all applications should be entrusted to responsible agents in this country, who can assure parties that theirvaluable inventions will not be misappropriated. The population of Great Britain is 31,000,000; of France, 37,000,000; Belgium, 5,000,000; Austria, 36,000,000; Prussia, 40,000,000; and Russia, 70,000,000. Patents may be secured by American citizens in all of these countries. Mechanical improvements of all kinds are always in demand in Europe. There will never be a better time than the present to take patents abroad. We have reliable business connections with the principal capitals of Europe. A large share of all the patents secured in foreign countries by Americans are obtained through our Agency. Address

#### MUNN & CO.,

#### 37 Park Row, N. Y.

IF Circulars. with full information on foreign patents, furnished free.