

Business and Personal.

The Charge for Insertion under this head is \$1 a Line.

Buy Gear's Improved Car Boring Machines, Boston, Mass.

Royalty—Manufacturers and Inventors, have your Machinery, &c., made in the west for western use.

\$2,500.—I will sell two Patent Rights to each State for \$2,500. Cures Piles and Dyspepsia. Send for Circular to Dr. L. Helms, Brunswick, Ga.

Wanted—A machine to whip or finish with yarn the ends of Colored Blankets. Address Box 3667, New York Post Office.

Stencil Dies, cheapest and best. Warranted. Catalogue with samples free. E. M. Douglas, Brattleboro', Vt.

Back gear, screw cutting Lathe, 26 inch bed, 6 inch swing. Price \$95. G. F. Shedd, Waltham, Mass.

For best Power Picket Header manufactured, address William P. Duncan, Bellefonte, Pa.

Portable Steam Engines for Plantation-Mining, Mill work, &c. Circular Saw Mills complete for business. First class work. Simple, Strong, Guaranteed. West Terms. Address the Old Reliable John Cooper Engine Mfg. Co., Mt. Vernon, O.

Machinery selected by Gear, Boston, Mass., always gives satisfaction.

Richards' Treatise on the Care of Wood-working Factories and Machinery is invaluable. Costs only \$1.50. Booksellers generally.

Much attention is now attracted throughout the country by the remarkable qualities of the new Elastic Truss, which retains the rupture under all circumstances and at all times. Worn with ease night and day, and kept on till a perfect cure is effected. Sold cheap. Very durable. It is sent by mail everywhere by the Elastic Truss Co., No. 653 Broadway, N. Y. City, who send Circulars free on application.—N. Y. Independent, March 27, 1873.

Makers of Machines for Sawing Sleigh Dash Boards, address J. A. Whelpley, Dartmouth, Halifax, N.S.

Models, Patterns, Jobbing, &c., S. 1st, near 11th St., Williamsburgh, N. Y.

Monitor Leather Belting you can always rely on. Send for Circular. C. W. Arny, 301 Cherry st., Phila.

3 Winn's Pat. Improved Portable Steam Brick Machines. Averages 40 m per day. Fully guaranteed. For sale cheap. John Cooper Engine Manufacturing Company, Mount Vernon, Ohio.

Nickel Salts and Ammonia, especially manufactured for Nickel Plating, also "Anodes," by L. & J. W. Feucht wanger, 55 Cedar Street, New York.

Oxide of Manganese, best quality, for Steel and Glass Makers, Patent Dryers, etc. We are first hands for this article. Supply any quantity at lowest rates. L. & J. W. Feucht wanger, 55 Cedar Street, New York.

Water Glass, Soluble Glass and Silicates Soda and Potash—for Artificial Stone and Cements—fire, water, damp and mildew proof. Manufactured by L. & J. W. Feucht wanger, 55 Cedar Street, New York.

Machine Shop for Sale—For particulars, address Abbott Manuf'g Company, Seneca Falls, N. Y.

Domestic Machinery Manufacturers and Dealers are requested to send their Catalogues, &c., with very best terms to Agents, for Cash with orders, (per first mail) to J. Begbie, Machine Agent, Haddington, near Edinburgh, Scotland.

"The Railroad Gazette, the best railroad newspaper in the country."—(Springfield Republican.) Subscription \$4 per year; single numbers, 10 cents. Address A. N. Kellogg & Co., 72 Broadway, New York.

Large Stock second hand tools just received. Charles Place & Co., 60 Vesey St., New York.

Buy First & Prybil's Bandsaw machines, which are more used than any other in the country. Also, Shafting and Pulleys a specialty. 467 W. 40th St., New York City.

Hand Fire Engines, Price \$300 to \$2,000. Also, over 800 different Style Pumps for Tanners, Paper Mills, and Fire Purposes. Address Rumsey & Co., Seneca Falls, N. Y., U. S. A.

Artists' Combined Rubber and Ink Eraser. Very Superior article. Size No. 1, price 30 cts; No. 2, 15 cts.; No. 3, 10 cts. Sent postpaid to any address, J. H. Green, 26 Beekman Street, New York City.

The Best Smutter and Separator Combined in America. Address M. Deal & Co., Bucyrus, Ohio.

For Re-pressing Brick Machines, apply to Anderson Brothers, Peekskill, N. Y.

Shingle Machinery. T. R. Bailey & Vail.

Dickinson's Patent Shaped Diamond Carbon Points and Adjustable Holder for dressing emery wheels, grindstones, etc. See Scientific American, July 24 and Nov. 20, 1869. 64 Nassau St., New York.

Mills for Grain, Paint, Ink, &c. Ross Bro's, Williamsburgh, N. Y.

Damper Regulators and Gage Cocks—For the best, address Murrill & Keizer, Baltimore, Md.

All Blacksmith Shops need a Holding Vise to upset bolts by hand. J. R. Abbe, Manchester, N. H.

Parties desiring Steam Machinery for quarrying stone, address Steam Stone Cutter Co., Rutland, Vt.

Brown's Coalquarry & Contractors' Apparatus for hoisting and conveying material by iron cable, W. D. Andrews & Bro. 414 Waterst. N. Y.

The Berryman Heater and Regulator for Steam Boilers—No one using Steam Boilers can afford to be without them. I. B. Davis & Co.

Circular Saw Mills, with Lane's Patent Sets; more than 1200 in operation. Send for descriptive pamphlet and price list. Lane, Pitkin & Brock, Montpelier, Vermont.

Peck's Patent Drop Press. Milo Peck & Co., New Haven, Conn.

Key Seat Cutting Machine. T. R. Bailey & Vail.

Tree Pruners and Saw Mill Tools, improvements. Send for circulars. G. A. Prescott, Sandy Hill, N. Y.

Five different sizes of Gatling Guns are now manufactured at Colt's Armory, Hartford, Conn. The larger sizes have a range of over two miles. These arms are indispensable in modern warfare.

For Steam Fire Engines, address R. J. Gould, Newark, N. J.

Plow Shares, Mold Boards, Cultivator Teeth, &c., cast to order, by Pittsburgh Steel Casting Co., Pittsburgh, Pa., of steel which can be worked same as wrought steel. All work warranted.

The Manufacturer and Builder for April is just out, splendidly illustrated. Send to Publishers, 37 Park Row, for Specimen copy free, P. O. Box 4379. \$2 a year, with elegant Chromo.

Boring Machine for Pulleys—no limit to capacity. T. R. Bailey & Vail, Lockport, N. Y.

Cabinet Makers' Machinery. T. R. Bailey & Vail. 40 different Bandsaw machines, 60 turning and improved oval lathes, shaping, carving and moulding machinery, for sale by First & Prybil, 461 W. 40th St., New York City.

For best Presses, Dies and Fruit Can Tools, Bliss & Williams, 118 to 120 Plymouth St., Brooklyn, N. Y. Gauge Lathe for Cabinet and all kinds of handles. Shaping Machine for Woodworking. T. R. Bailey & Vail.

Shafting and Pulleys a specialty. Small orders filled on as good terms as large. D. Frisbie & Co., New Haven, Conn.

All Fruit-can Tools, Ferracube, Bridgeton, N. J. The Berryman Manuf. Co. make a specialty of the economy and safety in working Steam Boilers. I. B. Davis & Co., Hartford, Conn.

Tool Chests, with best tools only. Send for circular. J. T. Pratt & Co., 50 Fulton St., New York.

Mining, Wrecking, Pumping, Drainage, or Irrigating Machinery, for sale or rent. See advertisement, Andrew's Patent, inside page.

Hydraulic Presses and Jacks, new and second hand. E. Lyon, 470 Grand Street, New York.

Machinists—Price List of small Tools free; Gear Wheels for Models, Price List free; Chucks and Drills, Price List free. Goodnow & Wightman, 23 Cornhill, Boston, Mass.

Lathes, Planer, Shaper, Shafting, 30 Boilers, Engines and Stock of Machine Shop, for sale very low. Henry McCollum, Long Island City, N. Y.

Gauges, for Locomotives, Steam, Vacuum, Air, and Testing purposes—Time and Automatic Recording Gauges—Engine Counters, Rate Gauges, and Test Pumps. All kinds fine brass work done by The Recording Steam Gauge Company, 91 Liberty Street, New York.

The Berryman Steam Trap excels all others. The best is always the cheapest. Address I. B. Davis & Co., Hartford, Conn.

Absolutely the best protection against Fire—Babcock Extinguisher. F. W. Farwell Secretary, 407 Broadway, New York.

For Solid Wrought-iron Beams, etc., see advertisement. Address Union Iron Mills, Pittsburgh, Pa., for lithograph, etc.

Steam Boiler and Pipe Covering—Economy, Safety, and Durability. Saves from ten to twenty per cent. Chalmers Spence Company, foot East 9th St., New York—1202 N. 2d St., St. Louis, Mo.

A Superior Printing Telegraph Instrument (the Selden Patent), for private and short lines—awarded the First Premium (a Silver Medal) at Cincinnati Exposition, 1872, for "Best Telegraph Instrument for private use"—is offered for sale by the Merchants' Mfg and Construction Co., 50 Broad St., New York. P. O. Box 6363.

Williamson's Road Steamer and Steam Plow, with rubber Tires. Address D. D. Williamson, 32 Broadway, N. Y., or Box 1809.

Manufacturers and patentees of Iron and Wood Working Machines, Agricultural Implements and Household articles, can have their inventions illustrated in the SCIENTIFIC AMERICAN on favorable terms, after examination and approval by the editor. Civil and mechanical engineering works, such as bridges, docks, foundries, rolling mills, architecture, and new industrial enterprises of all kinds possessing interest can find a place in these columns. The publishers are prepared to execute illustrations, in the best style of the engraving art, for this paper only. The engraving will be subject to patentee's order, after publication. (No orders executed for engravings not intended for this paper.) They may be copied from good photographs or well executed drawings, and artists will be sent to any part of the country to make the necessary sketches. The furnishing of photographs, drawings, or models is the least expensive, and we recommend that course as preferable. The examination of either enables us to determine if it is a subject we would like to publish, and to state the cost of its engraving in advance of its execution, so that parties may decline the conditions without incurring much expense. The advantage to manufacturers, patentees and contractors of having their machines, inventions, or engineering works illustrated in a paper of such large circulation as the SCIENTIFIC AMERICAN is obvious. Every issue now exceeds 45,000 and the extent of its circulation is limited by no boundary. There is not a country or a large city on the face of the globe where the paper does not circulate. We have the best authority for stating that some of the largest orders for machinery and patented articles from abroad have come to our manufacturers through the medium of the SCIENTIFIC AMERICAN, the parties ordering having seen the article illustrated and described or advertised in these columns. Address

MUNN & CO., Publishers, 37 Park Row, N. Y.

Best Mode of Introducing New Inventions.

Manufacturers and patentees of Iron and Wood Working Machines, Agricultural Implements and Household articles, can have their inventions illustrated in the SCIENTIFIC AMERICAN on favorable terms, after examination and approval by the editor. Civil and mechanical engineering works, such as bridges, docks, foundries, rolling mills, architecture, and new industrial enterprises of all kinds possessing interest can find a place in these columns. The publishers are prepared to execute illustrations, in the best style of the engraving art, for this paper only. The engraving will be subject to patentee's order, after publication. (No orders executed for engravings not intended for this paper.) They may be copied from good photographs or well executed drawings, and artists will be sent to any part of the country to make the necessary sketches. The furnishing of photographs, drawings, or models is the least expensive, and we recommend that course as preferable. The examination of either enables us to determine if it is a subject we would like to publish, and to state the cost of its engraving in advance of its execution, so that parties may decline the conditions without incurring much expense. The advantage to manufacturers, patentees and contractors of having their machines, inventions, or engineering works illustrated in a paper of such large circulation as the SCIENTIFIC AMERICAN is obvious. Every issue now exceeds 45,000 and the extent of its circulation is limited by no boundary. There is not a country or a large city on the face of the globe where the paper does not circulate. We have the best authority for stating that some of the largest orders for machinery and patented articles from abroad have come to our manufacturers through the medium of the SCIENTIFIC AMERICAN, the parties ordering having seen the article illustrated and described or advertised in these columns. Address

MUNN & CO., Publishers, 37 Park Row, N. Y.

Notes & Queries

E. B. H. asks how to galvanize sheet iron.

E. M. D. asks how old zinc can be made pure for use in a battery.

A. F. V. wants to know the best and quickest mode of kiln drying lumber.

E. J. C. asks: What is the preparation and process of burnishing gilding on china.

D. P. asks: How can I toughen horse hair so that it will not be brittle?

G. G. F. asks how to remove slight scratches off the face of a looking glass.

T. Y. S. asks how to bleach China grass. It can be made as white as snow.

R. R. asks: At what speed should a band saw run to cut saw logs best?

S. H. H. asks how to remove the rough back off the shell of the pearl oyster.

A. S. asks if it is possible to draw wire from a gold dollar to reach the length of a mile? If not, what length can it be drawn to?

W. W. C. asks: Is there anything that will make leather stick to iron and form a water tight joint for hydraulic rams?

C. H. R. asks for a recipe for an elastic polish or varnish that will give a patent leather finish, or one that will resemble it. It should bear bending and not break.

A. F. S. asks for the precise method by which gold fish are made to spawn. "I have a pond in which I have kept the same gold fish for over three

years, and up to the present time they have not multiplied."

W. S. asks: 1. What will remove black ink from writing paper without injury? 2. What is the easiest way to make a hole in a watch spring, without taking the temper out?

J. R. C. asks: What is the best kind of material for a float for petroleum? "I want something that will float freely on the oil and that will not become affected by it."

C. M. D. asks for a rule for measuring painter's works on iron bridges; for instance, a bridge 800 feet long x 100 feet high x 20 feet wide on top. Are the sides, length, and height measured as lattice work or once through?

R. R. asks: 1. What is the best time of the year as regards health to go to the Isthmus of Panama, and what sanitary course should be pursued?

C. J. F. says: I have a flat roof covered ten years ago with pitch and gravel. It now begins to leak a little. I have been thinking of scraping off the loose gravel and then applying a coat of Rosendale cement, say half cement and half sand. What do you think of it? Will it crack?

R. R. asks: If somebody buys a tract of land with a watercourse through it, and pays tax on the whole tract, water and all, has he a right to close up the creek with a dam, or must he let other people from below float their saw logs through his land? The logs could not float if the man had not dammed the creek some.

A. F. O. asks: What is bichromatized gelatin? How is it prepared, and what are its properties and uses? 2. How can I make a quickly drying cement that will resist the action of boiling alcohol, or with what varnish can I cover ordinary cements to accomplish the same object? 3. Is there any work in which are minutely described the manipulations of thermometer making, especially blowing the tubes and graduating the scales?

G. H. H. asks: Why is it that, in putting the finger on either the in or outside of the closed eye, a dark spot will appear on the opposite side of the ball in daylight, and a bright, luminous spot about the size of a gold dollar in the dark? It is an experiment which all can try; perhaps thousands have noticed it before; but what is it that appears so bright where all else is dark, because of a little manipulation of the closed eye and lid by the finger?

D. S. says: On page 52 of your current volume in answer to P. S. K. Malers, you direct him to break stones into small pieces and then to mix sand (sharp grit), etc. I have no stones on or near my place, and I wish to know whether river gravel which I have in abundance (from the size of a goose egg to fine sand) would answer instead. Also, will it make a sufficiently strong cellar wall, and if so, would cement mixed with lime be better for a cellar wall than cement without the lime?

J. G. K. asks: 1. Where can I obtain the exact standard measure of the American foot or yard? Is there any place or office in the city of New York where such a standard or model measure is kept open for the public? 2. Could some correspondent give me some practical details concerning the system of irrigation as practiced by the Mormons in Utah, and also about irrigation generally for agricultural and gardening purposes? 3. Is there not a kind of oak with edible acorns which may be used as food, or are acorns actually used as food? If so, where and how? I wish to know the botanical or other name and some characteristic description of such oaks and where they grow.

M. E. P. says: Can there be any such thing as a steam boiler that is absolutely safe? I do not claim to be an engineer myself; but suppose a boiler should be made in the usual manner except that the safety valve should be set on the top of another larger safety valve. For instance, the whole top of the steam dome might form a valve, fitted and made steam tight and arranged with a sufficiently long lever and heavy weights to stand an internal pressure of say one hundred pounds to the square inch, while the small safety valve was set to blow off at eighty. Would that be practicable? Or would several smaller ones attached to one boiler be of any use?

E. A. S. says: Nearly two years ago I tore up an old coal chute, that had been built for eighteen years, and found the sleepers and cross trees as sound as when first laid. The timber was laid in our common sand, and some of it was round, just as cut in the woods, with the bark on, and this was as sound as the rest. There were pine, hemlock, spruce and oak. The slack coal had worked through the cracks, and water had leaked through and formed a crust about six inches thick. We had to use a pick to break through the crust. The earth was saturated for about two feet down and looked like iron ore. Could slack coal and sand be used to lay Nicholson pavement, and be cheaper and better than the old process? And would it last till it were out, without regard to the kind of timber used? I claim that this can be done, and, if so, the discovery of the same.

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to

J. H. C. asks what per cent of the water supplied to a hydraulic ram can be returned to the point from which it fell? Does a ram give as good results under a given head of water as a turbine wheel? Answer: See article on page 257 of this issue.

L. & D. W. C. ask: How can we ascertain the quantity of power transmitted by belts of different widths, and pulleys of various diameters and speed? Answer: See the editorial columns of this issue.

W. H. C. asks: Would a pressure of steam hold up a column of cold water under the following circumstances: Suppose I have a tank of cold water 3 feet high connected by a 3/4 pipe to my boiler above the waterline (the tank also sitting above the water line), what pressure of steam, if any, would hold the water back; or would the cold water condense the steam and the difference in temperatures create a current and allow the water to run in the boiler under any pressure, the steam taking its place? Would the same result take place (the tank being closed and able to sustain the pressure of the steam in the boiler) if the tank were full as if half full? Or would the same result take place if the water in the tank was at a temperature of 30° as at 200°? Answer: A pressure of one and a half pounds would equilibrate that of the column of water. In the case supposed, the water, if cold, and if the pipe conducting it to the boiler were large enough, might condense the steam. If that were to occur, the water in the tank would then flow into the boiler with the same rapidity that it would issue from the pipe were the pipe led into the open air and a hole made in the top of the tank. The steam could only take the place of the water when the pipe was made of sufficient size to allow the steam to bubble directly up into the tank. With heated feed water, condensation of the steam would not be likely to