

happened, and the arrangement has, in that shape, been used as an automatic feed, with some success.

D. G. says: We have a new kind of a pump lately introduced into this (mining) district; this pump was originally intended for a 14 inch pump, plunger and bucket combined, the object of which is to discharge one half the water on the down stroke and the other half on the up stroke, thus making what is claimed to be a balance pump, with a great saving in power in working in deep mines. The parties who use this pump discarded the bucket and changed the plunger to a 12 inch one, which makes the pump now a 12 inch plunger pump. The builder of this pump has discovered an advantage in discharging the water through the jack head over pump barrel, and a saving of ten feet travel of water, over the old fashioned plunger pump. This pump we call B and the former, A. We place the two pumps in a shaft, 200 feet deep; the foot valves are on a level with one another. Now the best talent in the county claims that the water in B will travel 10 feet further than it does in A, in other words that B raises a column of water 200 feet in height, while A only raises a column 190 feet, and spills water 10 feet in advance of B. I claim that the water in B does not travel any further than it does in A, that they both pump against a column of water of the same height, and that A does not discharge water 10 feet in advance of B. Will you give us your highly valued opinion? Answer: We are inclined to agree with our correspondent on this point. We think, with him, that if, by any contrivance, water is raised from one level and discharged into a reservoir at a level 200 feet above, no modification of the machine will be able to make the lift anything less than 200 feet. We differ from the said "best talent" holding opposite views, and should prefer to accept the opinion of some of the intelligent apprentice boys who read the SCIENTIFIC AMERICAN, rather than subscribe to the views of said "best talent." Any two pumps, pumping against equal heads, will require the same power to do their work, provided frictional resistances are equal.

J. K. says: We have a steam mill for sawing logs, planing matching, etc.; our feed water is hard and causes a great deal of scale on the boiler. Now we have contracted for a new boiler of 30 horse power and wish to know what arrangement we can make to condense the exhaust steam to use for feed water. Answer: We presume that the most satisfactory arrangement will be found to be the usual condenser and air pump, which can be attached by any competent constructing engineer. There are one or two forms of "siphon condenser" in the market which are less expensive, however, and are said to perform well.

J. M. says: I have charge of a nest of three 42 inch boilers, 22 feet long, with 24 fourteen inch flues in each; the shells are made of 3/4 inch iron and the flues are made of iron of the same gage. They have been in use for 12 years, and I inspected them this week; the scale that is deposited on them is no thicker than a sheet of writing paper and is black and glossy; there are no leaks and they appear to be in as good condition as though they were only two years in use. I am expected to press them to 65 lbs. per square inch. I have had charge of boilers for the last sixteen years and I have read the SCIENTIFIC ALL that time; but as this is the first time that I have had to deal with boilers with large flues, I wish you to give me information in regard to what you believe would be the highest safe strain that I could carry, and whether the shell or the flues will stand the most pressure before giving way. Will you tell me how to compute the strains on flues in plain arithmetic, as I have no knowledge of algebra? Answer: The shell of the boilers described, if perfectly sound and of good iron, is safe at the pressure of 65 lbs., and the steamboat law has generally allowed 110 lbs. on boilers of that size and of 3/4 inch metal. The flues, if in equally good condition should collapse at about 806,000 x 1/4 x 1/4 - 22 x 14 = 163,5 pounds. One quarter of this pressure, or 40 pounds, is generally named by engineers as the limit of pressure to be carried, and we, ourselves, should object to carrying more than one sixth, 23 pounds. The flues will, therefore, give way first, under the conditions assumed, and should not be subjected to more than 40 or 45 pounds, although they may stand four times that pressure. The weak spot in large numbers of boilers is the flues, and, as our correspondent probably knows quite as well as we do, many accidents occur from collapsing flues. To determine the strength of any flue, made of good iron, well put together, and perfectly cylindrical: Divide 806,000 times the square of the thickness in inches by the square of the diameter in inches and the length in feet.

D. says: Suppose a party owes me. I sue and get judgment entered up against him, and the sheriff reports "no property, except letters patent in the defendant's name for a valuable invention" (cannot say if it is his own or purchased). Can I have said letters patent attached and sold at sheriff's sale? Answer: A patent cannot be taken and sold under an execution in an ordinary action for debt in which judgment has been recovered.

P. L. asks: Would sleeping always with your head to the north tend to magnetize the metallic constituents of the fluids and solids of the human body? If so, would it increase nervousness? Answer: Persons having the "iron constitution" might be so affected.

P. L. asks: How can you construct a pump that will draw water from a well that is 45 or 50 feet deep? Answer: Use a common lift and force pump, the latter placed in the well, say, 25 feet above the water.

L. W. C. asks: Can you give me an explanation of how Chas. G. Page (or his heirs) could take out letters patent in 1868 on electrical instruments which, according to history, were discovered by Professors Henry, Wheatstone and Morse, as early as between 1836 and 1842? Also, could that patent be enforced and thereby close opposition telegraph companies? Answer: The Page patents were granted by special act of Congress. Their validity has not yet been determined by the Courts.

N. B. D. says: I wish you could tell me what is the matter with my magnet. The cores are made of soft iron, about 5/8 inches at one end and 3/4 inches at the other, and are 6 inches long; they are joined at the smaller end by being screwed into a small piece of iron and are wound with about 600 feet of fine covered wire. When I attach the wires of a local battery to them, they have scarcely any attractive power. My magnets are considerably larger than those on my sander, but do not possess any attractive power. Can you tell me where the trouble lies? Answer: Your mistake may be in the connection of the terminal wires of the two spools forming the electro-magnet. If the two spools are wound in one direction and slipped on the cores, at the end furthest from the armature, connect either the two outside, or the two inside, terminal wires with each other. If we had your magnet here, we would correct your mistake, if not too great, without cost.

W. M. E. sends a mineral and asks what it is. Answer: The mineral sent is iron pyrites, or fool's gold. Of no value.

A. M. R. says: 1. What proportion of the weight of a car and load is the measure of adhesion of a 33 inch chilled cast iron wheel and an iron rail? 2. Of brakes with shoes of cast iron 4 x 12 inches, what proportion of car and load must be applied to the brakes to make the adhesion of wheel to brake equal to wheel on rail? 3. All things being equal, what is the measure of difference of adhesion between a rolling wheel and a sliding wheel on an iron rail? Answer: From fifteen to twenty per cent when dry, about ten per cent when greasy, and about five per cent for very light loads on a very greasy rail. 2. The friction is about the same as the preceding, and the same proportion of weight should be applied, rather less if it is desired that the wheels should not slide without turning. 3. Rolling friction of trains on a level being about one third of one per cent, the ratio of rolling to sliding will be 45 or 60 to 1 for dry, 30 to 1 for greasy, and 15 to 1 for very light weights and a very greasy rail. The sliding friction of a rolling and a sliding wheel are about the same.

W. H. C. asks: 1. How can zinc lining in bath tubs be kept bright, or brightened when tarnished? 2. Is there a durable paint or varnish for stoves, to be used in place of black lead? Answers: 1. Use elbow grease and whiting. 2. There is nothing equal to first quality finest ground black lead for stoves.

N. N. says: 1. I have a fire box boiler 18 feet by 42 inches, containing 5 seven inch flues, 3 near the center and 2 nearer the bottom. At about 2 1/2 or 3 inches from the outside shell, a crack has occurred in one of the bottom flues, near the lower side where the flue joins the boiler head, on the under side of the flue and next to the adjoining flue. How can I instruct a blacksmith to repair the break? 2. The flues, from burning light wood, are incrustated with a thick coating on the fire surface of each, apparently deposited from the smoke; how can I remove it? It materially interferes with making steam, being a non conductor of heat. 3. What will precipitate cellulose from its cupro-ammonium solution? 4. What is celluloid? Answers: 1. Take a piece of boiler plate large enough to cover the crack completely, with width enough to allow room for flange through which to bolt. Fit very carefully, working it hot and finally bolt it in place with 1/2 inch head and nut bolts, making the joint tight with a cement of red and white lead and oil. 2. Make a scraping tool for the purpose and remove it with that, if it cannot be detached by a stream of water, or by a brush. 3. Precipitate by neutralizing with excess of hydrochloric acid. 4. From the Latin cellula, little cells, and oid, like.

W. A. P. says, in answer to S. P. S. who asked what are the diameters of English locomotive drivers: Their express locomotives have a single driving wheel on each side, the diameter of which differs on different railroads. I enquired concerning them while in London last summer, and was told that the largest on the London and Southeastern Railway were about 9 feet in diameter; those on the Midland railway from 8 to 8 1/2 feet; and on the London and North Western railway and others, they varied from 6 1/2 to 8 1/2 feet. Those on the L. & N. W. railway are chiefly from 7 to 7 1/4 feet in diameter. Their freight locomotives have driving wheels of less diameter; but from what I saw, I should say that they were generally larger than those used on freight locomotives in this country.

J. J. B. says that W. D. O.'s question as to the commencement of the day is a perfectly legitimate one, and the answer is very simple: By the common consent of nations, the 180th degree of longitude from Greenwich is the starting point (or line) for each separate day in turn, and consequently this is the line sought for by W. D. O. When a ship going west crosses this line at noon on Friday, she crosses over to noon on Saturday, and vice versa; when a ship going east crosses this line at noon on Saturday, she finds, after she is across the line, that it is only Friday noon. This arrangement is, of course, purely artificial, but I believe is universally adhered to.

G. L. B. says, in answer to E. M. B.'s question on calculating speeds and diameters of pulleys: Multiply the diameter of the pulley (in inches) by the speed that it runs and divide by the diameter of the driven pulley. The answer will be the speed of the driven pulley. He says that machines come to him marked to run at so many revolutions per minute. Let him multiply the diameter of the pulley by the speed that it is marked to run and divide by the speed that his line of shafting runs, and the answer will be the diameter of the pulley required in inches.

J. C. H. says, in answer to T. G. who asks for directions to make a solid emery wheel: Take coarse emery, 2 lbs., Stourbridge loam, 1 lb.: mix to a thick paste and press into a metallic mold, then dry and bake or burn in a muffle to a white heat.

S. T. W. replies to S. L. D. who asked for a method of transferring pictures to glass: My method of transferring pictures is to use balsam of fir and alcohol; varnish the glass, place the picture face down upon it and then, instead of letting it dry for 24 hours, immediately commence rubbing off the back with water and forefinger; of course it requires a little more care, and it should be rubbed very lightly the closer you get to the picture. When allowed to dry for 24 hours, the paper absorbs a portion of the varnish, which prevents its being rubbed down thin, while the other way, with care, will secure a much finer and quicker job.

A. O. says, in reply to J. B. M., who asked what is the result produced by hardening cast steel in water strongly impregnated with salt, and what would be the difference if sal ammoniac were used in place of salt: All substances which increase the conductivity of heat of the water produce also a higher degree of hardness in the steel. This is the case with salt and sal ammoniac. The percentage of calcareous matter exerts no certain influence; so we can explain why the ancients considered certain rivulets and wells especially suitable for hardening steel. For this reason, according to Pliny, steel works were often erected in their vicinity, and at a distance from the mines. There are now used nitric acid, potash, nitre, prussiate of potash, crystals of tartar, etc. The English file cutters add 1 part of oil of vitriol to 30 or 40 parts of water. In some cases where no fresh cold water is at hand, such additions may be very useful, but they may in general be dispensed with.

A correspondent replies to T. E. B., who asked how to remove clinkers from the inside of a stove: Throw three or four oyster shells in the stove, while the fire is hot, and leave them there. They work like a charm.

A. H. M. says, in reply to J. C. C.'s query about cleansing feed water: If you will place your heater and filter above your pump a foot or two, so the hot water will flow to it, and then insert a small pipe in the suction close to the pump, of sufficient height to extend above the head of hot water, leaving the upper end open for the steam to escape, I think you will be able to force your hot water without cooling it again, and thus you will not lose the advantage of heating and filtering.

MINERALS.—Specimens have been received from the following correspondents, and examined with the results stated:

- S. H.—It is galena, the ore of lead.
J. W. T.—It is a siliceous rock, containing either carbonaceous matter or oxide of manganese; analysis would be necessary to determine.
A. H.—It is calcareous marl.
G. C. S.—They are pyrites and mica.
J. F. S.—The specimens contain neither cobalt nor nickel, but considerable iron.
J. A. C.—The metal is lead; but is J. A. C. sure that it came from the dark colored rock sent?
D. H. W.—It is not gold, but iron pyrites.
E.—It is yellow ochre, which is useful as a coarse paint and for polishing. If there is an abundance of it, it should not lie idle.
W. P. H.—The specimen is interesting as being a relic of the superstitious arts practised by the "medicine men" of Africa. We cannot think of any drug, certainly one with which the negroes are acquainted, which would produce the symptoms mentioned. If any other correspondents of the SCIENTIFIC AMERICAN know of the use of the "Hoodoo," or any things similar, among the negroes in the Southern States, we wish they would communicate.

COMMUNICATIONS RECEIVED.

The Editor of the SCIENTIFIC AMERICAN acknowledges, with much pleasure, the receipt of original papers and contributions upon the following subjects:

- On the Atlantic Disaster. By C. D. O.
On a Plan for an Underground Telegraph. By W. F.
On the Solarity of the Magnetic Needle. By H. S.
On a Railroad Accident near Memphis, Tenn. By A. C.
On a Hydraulic Ram. By J. P.
On Professor Haeckel's Opinion of the Embryo State of Man. By J. L.
On Trying Circles with a Square. By G. B. D.
On Moonites. By W. L. D.
On Double Action Friction Gear. By J. B. H.
On Clarifying the Water of Kansas City. By H. R.

Also enquiries from the following:
J. G.—G. W. S. & Co.—C. E. R.—J. J. E.—J. H. W.—W. J. S.—A. K.—R. D. B.—H. A.—G. S.—E. M.—J. D.—F. S. J.—E. F. O.—F. R.—W. G.—J. H. W.—J. S. M.—W. H. C.—T. C. J.—A. H.—J. B.—B. A. C.—A. C.—H. J. N.—R. W. S.—C. D. F.—G. M. E.—A. M.—J. S.

INDEX OF INVENTIONS FOR WHICH LETTERS PATENT OF THE UNITED STATES WERE GRANTED FOR THE WEEK ENDING MARCH 25, 1873, AND EACH BEARING THAT DATE.

Table listing various inventions and their patent numbers, including items like 'Acid, boracic', 'Adding machine', 'Air, expelling', 'Alarm, etc.', 'Alkali, incising', 'Amalgamator', 'Asphina compound', 'Bale tie', 'Bed, spring', 'Bedstead', 'Binder, temporary', 'Biscuit, cutting', 'Boats, propelling', 'Boiler, culinary', 'Bolt cutter', 'Books, etc.', 'Boot sole presser', 'Bran dust', 'Bread pan', 'Brick machine', 'Broiler', 'Bromine, producing', 'Butter rolls', 'Can opener', 'Car brake', 'Car coupling', 'Car coupling', 'Car coupling', 'Car wheel', 'Carpet fastener', 'Carriage spring', 'Carriage capper', 'Casks, pitching', 'Caster, furniture', 'Caster, furniture', 'Caster, table', 'Chair, reclining', 'Chair, tilting', 'Chair, table', 'Chest protector', 'Cock, stop', 'Cock, weighted gage', 'Collar, G. F. Rice', 'Collar, pad', 'Cotton, etc.', 'Coupling, friction', 'Crib or hammock', 'Cultivator', 'Cultivator O. M. Pond'.

Table listing various inventions and their patent numbers, including items like 'Cultivator, hand', 'Desk, school', 'Door bolt', 'Door check', 'Doughnut mold', 'Earth closet', 'Engine, dummy', 'Engine, hot air', 'Engine or pump', 'Engine, steam', 'Engine, steam', 'Engine, rotary', 'Engine, rotary', 'Engine, vapor', 'Engine, valve', 'Engine, eccentric rod', 'Fabrics, etc.', 'Fan, automatic', 'Feather renovator', 'Feed cutter', 'Feed apron', 'Fertilizers', 'Fifth wheel for carriages', 'Fireproof shutter', 'Fluting machine', 'Fountain and sprinkler', 'Funnel, measuring', 'Furnace, hot air', 'Furnace, etc.', 'Game table top', 'Gas, etc.', 'Gas governor', 'Grain weighing', 'Grappler', 'Hammer, power', 'Harness, hame for', 'Harrow', 'Harvester', 'Hinge, spring butt', 'Hoe and roller', 'Hoist, differential gear', 'Hoist, I. Smith', 'Hoist, safety', 'Hoop skirt', 'Horseshoe', 'Horse collar', 'Horses, cleaning', 'Hose pipe and sprinkler', 'Hydraulic motor', 'Hydrocarbon, burning', 'Jack, carriage', 'Kiln, R. Connable', 'Kiln, malt', 'Lamp burner', 'Lantern', 'Latch, reversible knob', 'Latch, reversible knob', 'Latch, reversible knob', 'Leather, etc.', 'Lock, indicator', 'Loom, C. J. Kane', 'Loom, power', 'Loom take up', 'Lubricator, steam', 'Lubricator, steam', 'Mandrel, buffing', 'Meat chopper', 'Mechanical movement', 'Mensuration apparatus', 'Metal castings', 'Metal lined vessels', 'Metal vessels', 'Metal vessels, beading', 'Mill, fanning', 'Mill pick', 'Mucilage', 'Musical instrument', 'Musical instrument', 'Organ treadle', 'Organ stop action', 'Package register', 'Pail, dinner', 'Paper, ornamental', 'Pencil, lead', 'Petroleum oil', 'Photographic bath', 'Pitcher top', 'Planter, hand', 'Plow, T. J. & G. M. Clark', 'Plow clevis', 'Post driver', 'Pressing machine', 'Printing press feeder', 'Propeller, chain', 'Pulley, M. K. Whipple', 'Pump, rotary', 'Pump, rotary', 'Pump, rotary', 'Pump and engine', 'Pump clack valve', 'Purifier, middlings', 'Railroad frog', 'Railroad rail joint', 'Railroad switch', 'Rake, horse hay', 'Rake, revolving', 'Refrigerator', 'Register, counting', 'Register, measuring', 'Register, etc.', 'Road steamer wheel', 'Sad iron', 'Sad iron', 'Sail and marine drag', 'Safe, burglar proof', 'Saw filing machine', 'Saw setting device', 'Saw, attaching handle', 'Scissors, sharpening', 'Seeding machine', 'Separators, sieve for', 'Sewing machine winder', 'Sewing machine, butt on hole', 'Sewing machine easter', 'Sewing machine quilt', 'Sewing machine treadle', 'Sewing machine tucker', 'Sewing machine tucker', 'Sewing machine creaser', 'Shearing animals', 'Shells, etc.', 'Skirts, etc.', 'Sifter, ash', 'Spark arrester', 'Spindle bolster', 'Spindle for machine', 'Spool blanks, making', 'Soda water apparatus', 'Soldering apparatus', 'Soldering tool'.

Sole trimmer, Gallagher & Coyle..... 137,066
 Stone, composition, T. Carson..... 137,127
 Swing, child's, W. H. Alcorn..... 137,121
 Table, extension, A. Reed..... 137,148
 Table leaf supporter, A. C. Johnson..... 137,210
 Table leaf support, A. Marchand..... 137,067
 Tag holder, Stillman & Burrows..... 137,257
 Telegraph, printing, C. J. Wiley..... 137,117
 Thill coupling, W. Cable..... 137,176
 Thill coupling, J. Martin..... 137,143
 Ticket, duplex, T. A. Jebb..... 137,081
 Ticket, duplex, T. A. Jebb..... 137,208
 Ticket book, Jebb & Brush..... 137,209
 Tobacco, etc., favoring, J. Kerr..... 137,084
 Tobacco, etc., shearing, Bisbing & McCune..... 137,170
 Toe nail clasp, E. B. Stedman..... 137,106
 Torpedo, well, A. Hamar..... 137,198
 Torpedo, self tamping, M. Gotham..... 137,196
 Toy, W. R. Withers..... 137,119
 Toy gun, A. James..... 137,080
 Trap, insect, J. McN. Smith..... 137,255
 Traps, casting, M. Gafney..... 137,133
 Treadle, J. H. Osborn..... 137,090
 Truck, hand, H. S. La Tourette..... 137,086
 Tubes, brazing metal, Gorman & Peregoy..... 137,068
 Umbrella handle, A. Oberdorf, Jr..... 137,233
 Umbrella runner necks, cutting, O. M. Smith..... 137,256
 Urinal, bed, Knight & Coburn..... 137,214
 Valve, etc., R. T. P. Allen..... 137,163
 Vehicle wheel, P. Jones..... 137,083
 Wagon loader, J. Johnson..... 137,138
 Washing machine, J. Ballard..... 137,046
 Washing machine, H. H. Case..... 137,177
 Washing machine, F. Hulet..... 137,206
 Washing machine, J. H. Kruse..... 137,218
 Washing machine, A. O'Dell..... 137,234
 Washing machine, G. Seymour..... 137,151
 Washing machine, B. A. Williams..... 137,161
 Water closet, J. G. Jennings..... 137,082
 Water wheel, J. Nolan..... 137,146
 Water wheel, B. Roof..... 137,242
 Water wheel, J. E. Stevenson, (r)..... 5,341
 Water cut off, rain, J. W. Wetmore..... 137,268
 Whiffletree attachment, A. Soursin..... 137,108
 Windmill, G. A. Swartz..... 137,111
 Window shade clip, F. Muller, (r)..... 5,338
 Wrench, etc., S. B. Dexter..... 137,129
 Wrench heads, forming, L. Chapman..... 137,052
 Wrench heads, forming, L. Chapman..... 137,053

themselves of the services of MUNN & Co. during the TWENTY-SIX years they have acted as solicitors and Publishers of the SCIENTIFIC AMERICAN. They stand at the head in this class of business; and their large corps of assistants, mostly selected from the ranks of the Patent Office: men capable of rendering the best service to the inventor, from the experience practically obtained while examiners in the Patent Office: enables MUNN & Co. to do everything appertaining to patents BETTER and CHEAPER than any other reliable agency.

HOW TO OBTAIN PATENTS

This is the closing inquiry in nearly every letter, describing some invention which comes to this office. A positive answer can only be had by presenting a complete application for a patent to the Commissioner of Patents. An application consists of a Model, Drawings, Petition, Oath, and full Specification. Various official rules and formalities must also be observed. The efforts of the inventor to do all this business himself are generally without success. After great perplexity and delay, he is usually glad to seek the aid of persons experienced in patent business, and have all the work done over again. The best plan is to solicit proper advice at the beginning. If the parties consulted are honorable men, the inventor may safely confide his ideas to them; they will advise whether the improvement is probably patentable, and will give him all the directions needful to protect his rights.

How Can I Best Secure My Invention?

This is an inquiry which one inventor naturally asks another, who has had some experience in obtaining patents. His answer generally is as follows, and correct: Construct a neat model, not over a foot in any dimension—smaller if possible—and send by express, prepaid, addressed to MUNN & Co., 37 Park Row, together with a description of its operation and merits. On receipt thereof, they will examine the invention carefully, and advise you as to its patentability, free of charge. Or, if you have not time, or the means at hand, to construct a model, make as good a pen and ink sketch of the improvement as possible and send by mail. An answer as to the prospect of a patent will be received, usually, by return of mail. It is sometimes best to have a search made at the Patent Office; such a measure often saves the cost of an application for a patent.

To Make an Application for a Patent.

The applicant for a patent should furnish a model of his invention if susceptible of one, although sometimes it may be dispensed with; or, if the invention be a chemical production, he must furnish samples of the ingredients of which his composition consists. These should be securely packed, the inventor's name marked on them, and sent by express, prepaid. Small models, from a distance, can often be sent cheaper by mail. The safest way to remit money is by a draft, or postal order, on New York, payable to the order of MUNN & Co. Persons who live in remote parts of the country can usually purchase drafts from their merchants on their New York correspondents.

Value of Extended Patents.

Did patentees realize the fact that their inventions are likely to be more productive of profit during the seven years of extension than the first full term for which their patents were granted, we think more would avail themselves of the extension privilege. Patents granted prior to 1836 may be extended for seven years, for the benefit of the inventor, or of his heirs in case of the decease of former, by due application to the Patent Office, ninety days before the termination of the patent. The extended time inures to the benefit of the inventor, the assignees under the first term having no rights under the extension except by special agreement. The Government fee for an extension is \$100, and it is necessary that good professional service be obtained to conduct the business before the Patent Office. Full information as to extensions may be had by addressing MUNN & Co., 37 Park Row, New York.

Caveats.

Persons desiring to file a caveat can have the papers prepared in the shortest time, by sending a sketch and description of the invention. The Government fee for a caveat is \$10. A pamphlet of advice regarding applications for patents and caveats is furnished gratis, on application by mail. Address MUNN & Co., 37 Park Row New York.

Preliminary Examination.

In order to have such search, make out a written description of the invention, in your own words, and a pencil, or pen and ink, sketch. Send these, with the fee of \$5, by mail, addressed to MUNN & Co., 37 Park Row, and in due time you will receive an acknowledgment thereof, followed by a written report in regard to the patentability of your improvement. This special search is made with great care, among the models and patents at Washington, to ascertain whether the improvement presented is patentable.

Reissues.

A reissue is granted to the original patentee, his heirs, or the assignees of the entire interest, when, by reason of an insufficient or defective specification, the original patent is invalid, provided the error has arisen from inadvertence, accident, or mistake, without any fraudulent or deceptive intention. A patentee may, at his option, have in his reissue a separate patent for each distinct part of the invention comprehended in his original application by paying the required fee in each case, and complying with the other requirements of the law, as in original applications. Address MUNN & Co., 37 Park Row, New York, for full particulars.

Design Patents.

Foreign designers and manufacturers, who send goods to this country, may secure patents here upon their new patterns, and thus prevent others from fabricating or selling the same goods in this market. A patent for a design may be granted to any person, whether citizen or alien, for any new and original design for a manufacture, bust, statue, alto relievo, or bas relief any new and original design for the printing of woolen, silk, cotton, or other fabrics, any new and original impression, ornament, pattern, print, or picture, to be printed, painted, cast, or otherwise placed on or worked into any article of manufacture. Design patents are equally as important to citizens as to foreigners. For full particulars send for pamphlet to MUNN & Co., 37 Park Row, New York.

Trademarks.

Any person or firm domiciled in the United States, or any firm or corporation residing in any foreign country where similar privileges are extended to citizens of the United States, may register their designs and obtain protection. This is very important to manufacturers in this country, and equally so to originers. For full particulars address MUNN & Co., 37 Park Row, New York.

Canadian Patents.

On the first of September, 1872, the new patent law of Canada went into force, and patents are now granted to citizens of the United States on the same favorable terms as to citizens of the Dominion. In order to apply for a patent in Canada, the applicant must furnish a model, specification and duplicate drawings, substantially the same as in applying for an American patent. The patent may be taken out either for five years (government fee \$20), or for ten years (government fee \$40) or for fifteen years (government fee \$60). The five and ten year patents may be extended to the term of fifteen years. The formalities for extension are simple and not expensive. American inventions, even if already patented in this country, can be patented in Canada provided the American patent is not more than one year old. All persons who desire to take out patents in Canada are requested to communicate with MUNN & Co., 37 Park Row, New York, who will give prompt attention to the business and furnish full instruction.

Foreign Patents.

The population of Great Britain is 31,000,000; of France, 37,000,000; Belgium, 5,000,000; Austria, 36,000,000; Prussia, 40,000,000, and Russia, 70,000,000. Patents may be secured by American citizens in all of these countries. Now is the time, when business is dull at home, to take advantage of these immense foreign fields. Mechanical improvements of all kinds are always in demand in Europe. There will never be a better time than the present to take patents abroad. We have reliable business connections with the principal capitals of Europe. A large share of all the patents secured in foreign countries by Americans are obtained through our Agency. Address MUNN & Co., 37 Park Row, New York. Circulars with full information on foreign patents, furnished free.

Rejected Cases.

Rejected cases, or defective papers, remodeled for parties who have made applications for themselves, or through other agents. Terms moderate. Address MUNN & Co., stating particulars.

Copies of Patents.

Persons desiring any patent issued from 1836 to November 26, 1867, can be supplied with official copies at a reasonable cost, the price depending upon the extent of drawings and length of specification. Any patent issued since November 27, 1867, at which time the Patent Office commenced printing the drawings and specifications, may be had by remitting to this office \$1. A copy of the claims of any patent issued since 1836 will be furnished for \$1. When ordering copies, please to remit for the same as above, and state name of patentee, title of invention, and date of patent. Address MUNN & Co., Patent Solicitors 37 Park Row, New York. MUNN & Co. will be happy to see inventors in person, at their office, or to advise them by letter. In all cases, they may expect an honest opinion. For such consultations, opinions, and advice, no charge is made. Write plain; do not use pencil or pale ink; be brief. All business committed to our care, and all consultations, are kept secret and strictly confidential. In all matters pertaining to patents, such as conducting interferences, procuring extensions, drawing assignments, examinations into the validity of patents, etc., special care and attention is given. For information and for pamphlets of instruction and advice Address

MUNN & Co.,
 PUBLISHERS SCIENTIFIC AMERICAN,
 37 Park Row, New York.
 OFFICE IN WASHINGTON—Corner F and 7th streets, opposite Patent Office.

Advertisements.

RATES OF ADVERTISING.
 Back Page - - - - - \$1.00 a line.
 Inside Page - - - - - 75 cents a line.
 Engraving may head advertisements at the same rate per line, by measurement, as the letter-press.

THE FOURTH CINCINNATI Industrial Exposition

—WILL OPEN—
WEDNESDAY, SEPTEMBER 3,
 AND CONTINUE UNTIL
SATURDAY, OCTOBER 4, 1873.

Largest and most complete Exhibition ever held in the United States.
 Send for Rules and Premium List.

WHALEN TURBINE. No risks to purchaser. Pamphlet sent free. SETH WHALEN, Ballston Spa, N. Y.

“Worcester Free Institute of Industrial Science.”
 Entrance Examinations July 30 and September 9. For catalogues, address PROF. C. O. THOMPSON, Worcester, Mass.

SILICATE OF SODA.

Liquid Silica—Soluble or Water Glass—manufactured by L. & J. W. FEUCHTWANGER, New York.

THE BOSS

is better, in every respect, than any other Drill Chuck. Will hold to 3/8. List price, \$7.
 One sample will be sent by mail, prepaid, on receipt of \$5.50; and if you don't like it, the money will be refunded. Address the maker, A. F. CUSHMAN, Hartford, Conn.

WOOD-WORKING MACHINERY GENERALLY.

Specialties, Woodworth Planers and Richardson's Patent Improved Tenon Machines. Central, corner Union st., Worcester, Mass. WITHERBY RUGG & RICHARDSON.

TAKE NOTICE.

BOSTON, MASS., March 15, 1873.

The Suit in Equity in the United States Circuit Court of Massachusetts—ALONZO S. GEAR *et al.* of Boston, Mass., vs. JONATHAN P. GROSVENOR *et al.*, of Lowell, Mass.—after a long and thorough investigation, has been decided in FAVOR OF THE PLAINTIFFS, and a Decree for a Perpetual Injunction, establishing the validity and ownership of the Patent, has been accordingly entered. All persons who have built, used, and sold Variety Moulding or Upright Shaping Machine, are hereby notified that amicable settlement can be made by promptly addressing

A. S. GEAR,
 Manufacturer and Sole Owner,
 56 Sudbury St., Boston, Mass.

WANTED! Agents to sell our Rubber Stamps and other Novelties. Address U. S. MANUFACTURING COMPANY, 97 W. Lombard Street, Baltimore, Md.



CHAMPION SPRING MATTRESS

The latest and best improvement. Do you want a healthy and comfortable bed? Here it is. The softest, easiest, cheapest, most popular, and durable Spring Bed in market. Sold by all leading dealers. No stock complete without it. Wholly composed of tenacious tempered steel springs, so united that the pressure is equally distributed. Easily moved or carried about the house. Can be lifted, turned, or rolled up like a blanket. Both sides alike. No frame or wooden slats, no straps. May be used on floor without bedstead. No under bed required. Needs only half thickness of hair mattress. The regular size double bed, 4 ft. 6 in. by 6 ft., contains 132 tempered steel upholstery springs and weighs only 25 lbs. More springs for your money in this bed than in any other. Warranted noiseless. Any size made to order. Send for pictorial circular. Retail price of double bed, \$13. Shipped by single bed or quantity, to all parts of the world. Liberal discount to the trade. Agents wanted. F. C. BEACH & CO., Makers, 131 and 133 Duane Street, New York.

WOODWARD'S COUNTRY HOMES.

150 DESIGNS and PLANS for Houses of moderate cost \$150, post paid.
ORANGE UDD & CO.,
 PUBLISHERS 245 Broadway, N. York.
 Send for Catalogue of all books on Architecture, Agriculture, Field Sports and the Horse

SAW GUMMERS, Single and Double Up sets, Saw Tooth Swages, Mill Dog Holders, Sliding Holders, Railroad Spike Pullers, and Tree Pruners. Send for circular.

G. A. PRESCOTT, Sandy Hill, N. Y.

Beautiful inventions for marking Clothing and printing Cards, &c. One will do for a whole family. Movable Type. Profitable, amusing and instructive for the young. Jet Printer \$1. Silver \$1.25, with Ink. Type and neat Case, delivered by mail anywhere. 3 Alphabets extra 60c. Agents wanted. Golding & Co. 14 Kilby St. Boston.

FREY'S SAW GRINDER

Will Gum and Sharpen Saws better and in less time than any other device. Saves time and Labor; Shapes mill, and auger Bits; Grinds and polishes Metal, &c. &c. Manufactured by Frey, Shackler & Co. Bucyrus, Ohio.

WOOD-WORKING MACHINERY.

New and Improved Woodworth's, Daniels's, and Dimension Planers, Moulding, Mortising, Tenoning, Sawing Boring, Upright Shaping Machines, etc. Machine Chisels and Augers, Moulding Cutters and Farmer's Celebrated Patent Mather Heads and Cutters, constantly on hand and made to order.
 R. BALL & CO., 36 Salisbury St., Worcester, Mass.

MILLERS AND GROCERS—Gray's Flour

and Yeast Company, 60 West 4d St. New York. Manufacturers of Gray's Pure Hop Yeast Powder, for Family and Millers' use, owners and grantors of Patent Right of manufacture of Pure Hop Yeast, Self Raising Flour, and Gray's Superior Family Flour. Agents Wanted. Samples and circulars, 25c. Gray's Wheat and Yeast Feeder.

PRICE \$290. You ask WHY we can sell First Class 7 Octave Pianos for \$290? We answer—It costs less than \$300 to make any \$600 piano sold through Agents, all of whom make 100 per cent profit. We have no Agents, but ship direct to families at factory price, and warrant 5 Years. Send for illustrated circular, in which we refer to over 500 Bankers, Merchants, &c. (some of whom you may know) using our Pianos, in 44 States and Territories. Please state where you saw this notice.
 U. S. Piano Co., 855 Broadway, N. Y.

Milling Machines.

STANDARD, UNIVERSAL, INDEX AND PLAIN. Send for illustrated catalogue to the BRAINARD MILLING MACHINE COMPANY, 115 Water St., Boston, Mass.

AMERICAN ROLLED NUT & TUBE CO.,

Richmond, Va. Nuts from 1/2 in. to 3 in., hollow Shattering, Turnbuckles, &c., manufactured by Ostrander's process. Better, and thirty per cent cheaper than any others made. Send for circular. WM. E. TANNER, Pres.

SHINGLE AND BARREL MACHINERY.

Improved Law's Patent Shingle and Heading Machine, simplest and best in use. Also, Shingle Heading and Stave Jointers, Stave Equalizers, Heading Planes, Turners, &c. Address TREVOR & Co., Lockport, N. Y.

VALUE OF PATENTS

And How to Obtain Them.

Practical Hints to Inventors

PROBABLY no investment of a small sum of money brings a greater return than the expense incurred in obtaining a patent even when the invention is but a small one. Large inventions are found to pay correspondingly well. The names of Blanchard, Morse, Bigelow, Colt, Ericsson, Howe, McCormick, Hoe and others, who have amassed immense fortunes from their inventions, are well known. And there are thousands of others who have realized large sums from their patents. More than FIFTY THOUSAND inventors have availed