

THE ADVOCATE OF INDUSTRY, AND JOURNAL OF SCIENTIFIC, MECHANICAL AND OTHER IMPROVEMENTS.

VOLUME 6.1

NEW-YORK, NOVEMBER 23, 1850.

[NUMBER 10.

Scientific American, CIRCULATION 16,000. PUBLISHED WEEKLY

THE

At 128 Fulton, street, N. Y., (Sun Bailding,) and 13 Court street, Boston, Mass.

BY MUNN & COMPANY, The Principal Office being at New York.

A. T. Hothkiss, Boston. Geo. Dexter & Bro., New York City. Stokes & Bro., Philadelphia. Barlow, Payne & Parken, London. Responsible Agents may also be found in all the principal cities and towns in the United St tes.

-\$2 a-year---\$1 in advance and the remainder in 6 months. TERMS.

Rail-Road News.

Our Lines of Railroads.

In about two years from the present date it may be predicted with certainty that we will be able to step on board of a railroad car at the corner of Hudson and Chambers street, this city, and proceed on our way, by uninterrupted railroad, to the Mississippi River in Illinois. From New York to Galena, on the Mississippi River, Illinois, the distance is 1200 miles, and railroads are now in the course of construction, which, along with those in operation, will complete the whole chain in about the time we have specified, The New York and Erie road will be opened to Dunkirk, on Lake Erie, next year, and a road will soon be constructed from that to Toledo, and then the road from Toledo to Chicago, at the head of Lake Michigan, through part of Indiana, will be completed 250 miles by the time mentioned, which will carry the line entire to Chicago, from which the Galenaroad, 40 miles of which are constructed, will then be finished, fording the longest and most splendid internal railroad communication in the world, excepting it may be the great Russian line. In the course of ten years from the present moment, it is not too much to expect an interior line of railroad communication from New York to San Francisco.

True Heroism.

On the occasion of the late breaking down of the tressel-work over the Wateree river on the line of the Camden Railway, a conductor, fearing that a passenger train that was approaching would run into a chasm, wounded as he was, crawled along the broken timbers a considerable distance, and succeeded in making signals, which prevented any subsequent disaster. This is a real act of heroism. exhibited under circumstances of a peculiarly trying nature, yet nobody thinks it worth while to learn the name of the actor. It is vaguely given, with a "we belive his name is Spell." Had he been a military hero, who had destroyed a thousand lives, ' his name and his fame would have been blazoned abroad, and inscribed upon the pages of history.

Ogdensburg Railroad. A bill has been reported to the Vermont



This Engine is the invention of Mr. A. A. | engines; G is the steam-box. The top is con-Wilder, of Detroit, Michigan, the inventor of nected with the steam boiler, and is the inlet the Lee Way Indicator, and the Hand Copy- passage, the lower part, G, is the ejection or ing Press, which have been illustrated and described in our last two numbers. Notices of this invention have spread far and wide, but we suppose that not one has derived anything like a correct idea of its action. We have seen rotary disc engines, steam wheels and oscillating cylinder engines, but we never saw a rotary cylinder steam engine, before this one of Mr. Wilder-it is a novelty to us in engineering.

Figure 1 is a perspective. view ; figure 2 is side elevation, and figure 3 is a vertical section of the steam box. The same letters represents a frame; B is an axle, or shaft of the cylinder, C, on one side, and F is a shaft on the other side, but not opposite to B. The shaft, F, is attached to long crank, E, which is connected by a crank-pin to the top of the



piston rod, D. It will be observed, by figure 2 that the axle, B, is not in the same line with the axle, F. The two are at such a distance apart as describes the leverage, or what would be the length of the crank in common

exhaust. The inner part of the axle, B, is cast on the cylinder, and is hollow, divided by a partition in the middle, seen in fig. 3. This hollow axle has two openings indicated by the dark marks, which openings become the injection and exhaust passages alternately. This will be easily understood by referring to figure 3. The top passage, G, of the steam-box, is the inlet steam passage, and the lower passage, G, is the exhaust. Allowing the arle to revolve, it will be observed, that the two dark openings in the axle, will alternately be in communication with the inlet and exhaust fer to like parts, on all the figures. A A re- passages, and thus allow the same passages alternately to receive and exhaust, at both ends of the cylinder, under and above the piston. The openings and passages to the ends of the cylinder under the piston, are the same as in ordinary cylinders : the axle, therefore, is the valves of the engine. It will be observed that the piston, although it has a stroke from end to end of the cylinder, does not travel far either way from the central axle, B, and it describes a somewhat curious figure. Mr. Wilder has taken measures to secure a

patent for his invention, and an engine of the same kind is now in operation in Detroit. We have seen a number of letters from very respectable authorities who have seen it in operation, and who speak highly of its operative qualities. We have seen a neat model of the engine, but have not had the pleasure of seeing a working engine in operation. It should be observed that the length of the long crank, E, is such as to be equal in length with the piston rod, from the centre of the piston; and the distance between the centre of the axle, B, to the centre of the axle, F, is just the half length of the stroke (or cylinder.)

To give Copper Goods a Coating of Bronze or of Brass.

FOR BRONZE.-Tin the surface of the copper by the process adopted for pins, that is, by boiling them in grain tin, in a clear solution of cream of tartar. Half an hour will usually suffice for this, if the boiling has been kept up, especially if a few drops of chloride of tin are added to the mixture. The copper having been thus tinned, well washed and cleaned, is to be moderately heated until it acquires the tint of bronze which may be desired.

For BRASS .- Instead of the mixture above mentioned, use granulated zino, with a saturated solution of sal ammoniac, and boil in the same way. When the copper has acquired the appearance of zinc, it must be washed, cleaned, and carefully heated until it acquires the yellow color of brass. A small quantity of chloride of sino may be added, to facilitate the zincage.

Pentenkofer's Copper Amalgam.

Copper, 30 parts; mercury 70 parts. This amalgam is much used by the Paris dentists as a succedaneum for the teeth. It may be readily made by taking finely divided copper, obtained by precipitation, from solution of sulphate of copper, by means of metallic iron, sprinkling over it nitrate of mercury, adding a email quantity of metallic meroury, and well triturating. The mass which is at first brittle, quickly softens, and assumes the degree of consistence desired the moment that it is incorporated with a suitable quantity of mercury.

Liquid Saleratus.

Put the salts into a bottle, and add water till nearly the whole is dissolved, and cork up for use. A little experience will show you the quantity to use, and it insures a perfect and uniform distribution of the alkali in every part of the flour, and avoids those unsightly and disagreeable tasting spots in biscuits, that can hardly be avoided when used in the other state.

Malleable Brass.

By M. Reich. Copper, 33 parts; silesian zinc, 25 parts. Melt the copper, and then add the zino, previously purified from sulphur; stir well and run into bars, by means of sand moulds.

Fine alcohol can be manufactured from the peel of the sour orange. It has been tried successfully in Savannah, Ga. A sample is to be sent to the London fair.

The Races of Man.

Dr. Charles Pickering, an English author of a book entitled as above, describes eleven distinct races of man, founded on what he deems essential differences He thus enumer-

tes	them and t	he p	opul	ation	of each race:
	White,				350,000,000
	Mongolian,				300,000,000
	Malayan,		-	•	120,000,000
	Telingan,				60,000,000
	Negro,	•			55,000,000
	Ethiopian,		-	-	8,000,000
	Abyssinian	•		•	3,000,000

