# Scientific American.

## Scientific Museum.

#### Improvement in Diving Bells.

The annexed engraving is a view of an improvement in diving bell apparatus, invented by E. W. Foreman, of New Rochelle, N. Y., a young man who lost his life last year while bathing. A patent was granted to his brother as administrator on the 23d of last month, the claim for which will be found on page 406, vol. 8. The assignee of the patentee is H. W. Sears of this city.

We consider that all improvements relating to submarine apparatus are of much importance to such a great commercial country as ours hence we have always endeavored to spread abroad much useful information on the subject. In the first number of our last volume we presented an illustrative description of blasting rocks under water by the electric spark, without the use of a diving bell; but the diving bell is for the purpose of doing under water what no other machine nor apparatus is capable of doing; hence it will always be used, and every improvement made in it should attract attention.

The figure of the dividing chamber, A, is made up of the frusta of two cones joined at their bases. At the top is an opening by which the workman enters, having a cover fitting airtight, which may be secured from within. The bottom also has a hole in it, with a cover. Around the edge is a rim. The use of this rim is to retain within the vessel any object the explorers may take in through the bottom. There are a series of tanks arranged around the sides of the diving-chamber: these are the air and water reservoirs for regulating the specific gravity of the chamber. Each tank is connected with the others by two sets of pipes; the one set being at the top, and the other at the bottom. The upper pipe is for the supply of air, and the lower one for water. The supply of air is obtained from a reservoir (carried upon a boat or float) by means of a flexible tube, C, extending from it to the diving chamber, where B is the reservoir, and it is by filling the tanks with water, wholly or partially, that the buoyancy of the chamber, A, is regulated; g is the end of a pipe to which the flexible air-tube, leading from the reservoir, B, is connected outside, whi e it communicates within by means of a branch having a stop-cock with one of the tanks, and then the main pipe passes down near the bottom, and discharges by another stopcock into the general chamber A. There is a pipe for discharging air from the tanks. This pipe has a stop-cock in it, and is beside covered by a valve of common construction on the outside, and opening outwards. There is a pipe for emptying the tanks of water, which discharges outside and also through the bottom; there being here a valve of common construction opening outwards. The air may likewise be introduced into and discharged from the tanks by separate pipes; an arrangement which will sometimes be required, as the proper balancing of the vessel will depend upon it. The chamber is further supplied with an arrangement for anchoring it to the bottom for holding it in one place, or to afford the means of shifting its position. The anchor, which may be of common construction, is attached by a cable,  $k_{,}$ through a traversing sheave or block, k', and the end, after passing over k', is taken in through a. hole in the bottom, where it may be wound. upon a windlass. The block k' is fixed to an: endless chain passing over two rollers, one near the bottom, and the other near the middle of

der. This is a common screw, fixed upon a for this purpose it is combined with a hollow propelled within a certain arc in various direcble air tube is exhibited at C. It is so concoiled without interrupting the passage of air; great degree of pressure.

shaft passing through into A, and having a crank shafted reel. The end fixed upon the reel opens to set it in rotation. The box supporting the | in the hollow shaft, one end of which is stopped, shaft is formed on the principle of a ball and the opposite end entering the reservoir, B, socket joint, thus any direction may be given to through a stuffing-box, by which means the air the shaft, so that by it the chamber, A, may be may pass out of B through the shaft, thence through the tube coiled upon it, and be thence tions, the anchor forming the centre about discharged into A, so that no more tube need which the motion would take place. The flexi- be in the water than is sufficient to reach the diving-chamber. The air-reservoir, B, must be structed as to be capable of being coiled or un- constructed of a material capable of sustaining a

#### FOREMAN'S DIVING BELL.

will be as follows : The diving-chamber, floating a communication with the outside. upon the surface of the water, is anchored so as to stand over the bed of the wreck or other object to be explored, or as nearly so as may be. The reservoir, B, is then charged by means of an air-pump with as much air as can be forced fer-dam.\* into it, and the flexible tube, C, is attached to A. The workmen enter with such tools as they require, and the top is shut down and fastened. The tanks, at first, contain only air at the pressure of the atmosphere. The air-cock is then opened, and also a cock at f; the latter of which allows water to flow into the tanks, and forces the air out, which decreases the buoyancy of A so much that it sinks. As the chamber demeends, the cock, g, is opened so far as to allow a sufficient amount of air to be sent in from the reservoir, B, to sustain respiration, and also to counterbalance the pressure of the water outside, for the ascertainment of which proper gauges will be employed. The specific gravity of the vessel may be regulated for any depth of water it is to go, by properly proportioning the watter and air in the tanks, so that it may be held in suspension at any depth the operators may please. In this manner the upward and downward motions are effected, while the traversing motion along the bottom is obtained by means of the anchor and the rudder.

If the apparatus lie in a current, it can be worked along it by means of the cable, k, being wound or unwound within, while to go from

The mode of operating with the apparatus out by the bottom pipe, f, from which there is

It is intended to combine with the divingchamber a second chamber, placed below the lower opening, and to be formed of several pieces, which is intended to act as a moveable cof-

\* We refer our readers to the claim to see what is new to this apparatus.

#### The American Yacht Silvie Beaten.

The American Yacht Silvic, the property of a gentleman at New Rochelle, was beaten this year in the race for the Royal Prize. The successful Yacht was the Julia, of only one half the tonnage of the Silvie, and is quite new, having been built on improved lines. The Silvie came in second; the time was 7 hours, 7 minutes, 3 1-2 seconds for the Julia, the Silvie's time was 6 minutes, 38 1-2 seconds longer. The owner of the Silvie, L. A. Depaw, at once challenged the Julia for another race; we do not know if the challenge was accepted.

#### Serious Steamboat Accident.

The steamboat Bay State, while on her pasage to this city from Fall River, on the night of the 8th inst., broke her crank pin, by which the cylinder lid was smashed to pieces, and a great discharge of steam took place into some of the rooms where the passengers were sleeping, by which four persons lost their lives .-The verdict of the Coroner's Jury threw no blame on any of the officers of the boat, or the \$50 for

#### Heat and Comets.

When some persons get notions of a peculiar character into their heads, it is curious to witness the reasons they advance, and the proofs they bring forward in support of their opinions. The recent comet has called forth the philosophic deductions of a correspondent of the "New York Tribune," in proof of great heat as the usual accompanyment of such visitations. He asserts that the comet of 1811 was accompanied with a highly heated atmosphere, and that the present comet was the same that Beilas discovered in 1826, and that its periodical revolutions were calculated by E. Clausen, and found to be 6 8-4 years, which he says would make it cross the ecliptic on the 29th Oct., 1852. How he makes out the recent comet to be Beilas', in order to prove its connection with the great heat of our atmosphere this summer, by his own proofs, is enough to puzzle the best spiritual medium in our country. Beilas' comet appeared last year and was seen at Rome, consequently the present comet cannot be the same, and his conclusions about heat and comets are simply erroneous.

### Inventions.

Some one thus sums up a few of the advantages of modern inventions :--- " One boy, with a Fourdrinier machine, will make more paper in a twelvemonth, than all Egypt could have made in a hundred years during the reign of the Ptolemies. One girl, with a power-press, will strike off books faster than a million scribes could copy them before the invention of printing .--One man, with an iron foundry, will turn out more utensils than Tubal Cain could have forged, had he worked directly to this time.

In the course of one month there will be a double track all the way to Albany on the Hudson River Railroad. Good.



Manufacturers and Inventors.

The present Volume of the SCIENTIFIC AMERICAN mences under the most gratifying assurances, and appearances indicate a very marked increase to the subscription list. This we regard as a flattering testimonial of the usefulness and popularity of the publication so generously supported. We are greatly indebted to our readers for much valuable matter, which has found a permanent record on its pages. The aid thus contributed has been most important to our success, and we are grateful for it.

From our foreign and home exchanges-from the workshop<sup>5</sup>, fields, and laboratories of our own country, we have supplied a volume of more than four hundred pages of useful information, touching every branch of art. science, and invention, besides hundreds of engravings executed by artists exclusively in our employ.

The present Volume will be greatly improved in the style and quantity of the Engravings, and in the character of the matter, original and selected. Having every facility for obtaining information from all parts of Europe, we shall lay before our readers, in advance of our cotemporaries, a full account of the most prominent novelties brought forward.

The opening of the Crystal Palace in this city, forms an interesting subject for attraction. We shall study it faithfully for the benefit of our readers, and illustrate such inventions as may be deemed interesting and worthy.

The Scientific American is the Repertory of Patent Inventions : a volume, each complete in itself, forms an Encyclopedia of the useful and entertaining. The Patent Claims alone are worth ten times the subscription price to every inventor.

#### **PRIZES!! PRIZES!!**

The following Splendid Prizes will be given for the largest list of mail subscribers sent in by the first of January next: \$100 for

r the largest list.	aso for the run la	rgest list.
the2d largest list.	\$25for the 8th	ditto
the 3d ditto	\$20 for the 9th	ditto

the diving chamber A. The upper roller is side to side the propeller-rudder is worked. As fixed to a shaft which passes through the side soon as the chamber is over the proper spot, the cover to the bottom hole is taken off, when the of the chamber. A. and terminates in a crank, by water will be kept back by the pressure of the | luable improvement has recently been made in which it can be turned round. This movement: from within effects the traverse of the pulley  $k'_{,*}$ air from within, and the workmen can then begin their operations. Light is admitted within up and down, and so changes the angle or directhe vessel by the insertion of heavy plate glass, tion of the pull upon the anchor. The various: positions which may thus be given to the block, or bulls'-eyes, in the top and sides. The buoyk', afford a means of regulating the degree of ancy of A should be such that on emptying the force with which the chamber is held to the tanks of water and filling them with air, it will | lbs. extra on the square inch. The improveground; for if the cable be adjusted to pull from. rise to the surface with the additional weight of the bottom of the chamber, A, it will exert littles such articles as may have been taken from the plicable to all kinds of iron. force in keeping it upon the ground; and, om bottom. As soon as it is desired to rise to the surface, water is expelled from the tanks by the the contrary, if the block, k', be raised, the amchor will act more effectually to hold the cham- force of the air from the reservoir, B, which is at all, and only pass in the world like straws on ber upon the ground. At l is a propeller rund- then admitted in at the top, the water passing a river-they do not go, but are carried.

Production of the second second second

makers of the machinery.

Improvement in the Manufacture of Iron. The "Pittsburgh Dispatch" states that a vathe manufacture of iron by J. Finch, of that city. The nature of the improvement is not described, but it is stated that the common grey iron of Pittsburgh has improved so much in strength by it, as to sustain more than 20.000 ment is made in the puddling process, and is ap-

There are some that live without any design

45 for the 4th ditto \$15 for the 10th ditto \$40 for the 5th ditto \$10 for the 11th ditto \$35 for the 6th ditto \$5 for the 12th ditto The cash will be paid to the order of the successfu ompetitors immediately after January 1st, 1854. These prizes are worthy of an honorable and energetic ompetition, and we hope our readers will not let an opportunity so favorable pass without attention.

TERMS! TERMS!! TERMS!!! One Copy, for One Year Six Months \$1 Five copies, for Six Months Ten Copies, for Six Months, for Ten Copies, for Twelve Months \$15 Fifteen Copies for Twelve Months \$22 Twenty Copies for Twelve Months \$28 Southern and Western Money taken at par for Subscriptions, or Post Office Stamps taken at their par value. Letters should be directed (post-paid) to MUNN & CO. 128 Fulton street, New York.