



[Reported Officially for the Scientific American.]

LIST OF PATENT CLAIMS
Issued from the United States Patent Office
FOR THE WEEK ENDING JANUARY 31, 1854.

COPYING PRESS.—By Calvin Adams, of Pittsburg, Pa.: I claim the combination of the lever, bar and upper pressing plate, connected by means of the adjusting screw, and the mode of communicating pressure to the upper pressing plate by means of a cam at the end of a lever, working at the end of a lever bar which sustains the upper pressing plate, also the use of the finger at the end of the cam lever in combination with the rest and other parts of the press for the purpose of raising the upper platen of the press and sustaining it in its place while the copying book is inserted or withdrawn as set forth.
WOOD SAWS.—By Romeo Andrews & Albert F. Andrews, of Ayer, Conn.: We claim the peculiar form and relative position of the planing teeth in combination with the sawing teeth, as set forth.
RAILROAD CAR BRAKES.—By L. B. Batcheller, of Arlington, Vt.: I claim operating the levers which are attached by two rods to the cross bars, L M, by means of vibrating bars C G, said bars C, being moved or operated either by turning the standards E E, or by the action of the buffer-ropes upon the two levers, both devices being attached to the trucks and otherwise constructed and arranged, as set forth.
DUMPING CARS.—By C. P. Bailey, of Zanesville, Ohio: I claim hanging or connecting the bodies of dumping cars or wagons to the trucks, axles or bolsters, which usually support the bodies of similar carriages, by means of hinged cross braces or arms which pass transversely from end to end, or crosswise of the body as the case may be, one end of each of said arms or braces being hinged to the body and the other ends to the bearing or support beneath them, for the purpose of allowing said bodies to swing or dump either way, as described.
FANCY CHECK LOOMS.—By Enoch Burt, of Manchester, Conn.: I claim hanging the levers or jack lifters below the web and on a shaft parallel with, and at or about a vertical plane with the "fell" or cloth making line so as to produce an even shed both at the top and bottom and render the shifting of the jacks from the said levers sure, avoiding the jar of the machinery and obviating the liabilities of the jacks to hang on the flanges of the levers, as set forth.
ROBINSON OIL LAMPS.—By Silas Constant, of Brooklyn, N. Y.: I claim enclosing the portion of the wick which rises above its guide, within a perforated conical tube M, for the purpose of causing a portion of the air that enters the chamber between G and H, to be brought in contact with the wick which is thereby rendered uncompressed, and to rise in and about the same to the flame, as set forth.
Second, I claim the draught tube placed within the burner, and having the button and the perforated and deflecting head combined therewith, substantially in the manner and for the purpose hereinafter set forth.
Third, I claim the lip projecting downwards from the under side of the cap within the series of air holes in the same for the purpose of preventing gusts of air from producing puffs of smoke up the chimney, as set forth.
WASHING MACHINES.—By Wm. Cunningham, of Holliday's Cove, Va.: I do not claim the general features of the rubbing frames and plunger; but I claim the roller frames hung in adjustable boxes and connected by weighted arms, as described.
BEE HIVES.—By John H. Dennis, of Boston, Mass.: I claim a moth trap consisting of a close chamber, having no communication with the rest of the hive and in which may be placed a vessel containing some fluid attractive to the bee-moth, in combination with a conical or tapering entrance tube, as set forth.
ATTACHMENT TO PIANOFORTES.—By S. B. Driggs, of Detroit, Mich.: I claim, first, the combination of a series of metallic tongues or springs with the pianoforte or other stringed instrument, in such a manner that a tongue and a string are struck simultaneously by hammers actuated by a single key, as described.
Second, actuating the hammers which strike the tongue, by means of a jack of any suitable form, attached to the damper of its corresponding string, whereby the said hammer is caused to strike by the raising of the damper, when the pianoforte action is brought into play, and thus the tongue and string are struck simultaneously.
AIR-HEATING FURNACES.—By C. R. Harvey, of New York City: I do not claim adding flue, or a coil of heating pipe, as they are both well known devices; but what I do claim as my invention, is constructing the bonnet or top of the chamber, with a depression at the centre, into which the smoke or exit pipe enters, so that the heat is equalized all around and the expansion and contraction is made uniform, as specified.
STOVE.—By D. G. Littlefield, of Lowell, Mass.: I claim the cylindrical grated fire pot in combination with the gas receptacle constructed and operating in the manner substantially as described, by which I am enabled to burn the gaseous and more inflammable elements of the coal in immediate contact with its more refractory portions and thus ensure the complete combustion of them both.
VENTILATING RAILROAD CARS.—By George Neilson, of Boston, Mass.: I claim two or more ranges of sponges or capillary particles as arranged and combined with the outer and open mouthed case made to communicate with the interior of the car and the surrounding atmosphere and to operate when the car is in movement, as specified.
HOLLOW SLABS AND FLANGED METALLIC PLATES.—By Thomas Prosser of New York City: Although I have used the term wrought iron, I mean to apply the same to any and any of the valuable metals particularly steel and platinum, that I do not confine myself to any particular form or configuration by the term hoop or ring, as that may mean annular, round, square, oval or any irregular form whatever.
What I claim is the manufacture of hollow slabs when the same are made by welding together pieces of metal as described, or in any manner analogous thereto.
I also claim the manufacture of flanged metallic plates when the same are made by welding together pieces of metal in the manner fully set forth.
FEED APPARATUS OF STRAW CUTTERS.—By Harvey Trumbull, of Central College, Ohio: I claim the device for securing the clear passage of the straw &c. over the intervals between the trough and mouth piece and the lower roller, consisting of fingers attached to the trough, and passing over the said roller into or upon the mouth piece, secure from interference with the passage of the straw &c. by grooves in the face of the roller in which the fingers lie.
MILLS FOR GRINDING SUMAC.—By Peter and W. S. and J. J. Hench, of Fort Royal, Pa.: We do not claim the grinding by balls as that has long been known, but not in conjunction with a roller in the manufacture of sumac, which is necessary to detach and partially pulverize and sift the material before carrying it to the balls.
We claim the employment of a cylinder having projecting points or teeth on its internal surface with a roller having heads on its ends, on which it rolls and is kept above said teeth, said roller also having teeth projecting from its surface interlocking with those first named on the cylinder, by which the better portions of the sumac are beaten off and passing through the aper-

tures in the cylinder enter another when they are ground fine, as described.
MACHINERY FOR FULLING CLOTH.—By J. H. Jennings and Thomas Briery, of Clayville, N. Y.: We do not claim the individual parts thereof, nor the combination of the gatherer and horizontal and vertical rollers or fold breakers with a cylinder or wheel or cylinders or wheels having a groove therein or flanges on each side and a cylinder or wheel fitting a d working in such groove or between such flanges nor the weights and springs to be used upon any or all of such rollers or fold breakers and pressure rollers, but we claim the named rollers formed with flat surfaces in combination with the gatherer the horizontal and vertical rollers or fold breakers and guide, as set forth.
PISTON VALVES AND STEAM PASSAGES IN CYLINDRICAL STEAM CHEST.—By Joseph Marks, of Boston, Mass.: First, I claim constructing a steam chest with continuous circular ports or passages, both for the induction and exhaust steam, arranged as herein above described so as to keep a constant and equal pressure of steam upon both ends and the periphery or outer surface of a cylindrical piston valve which travels in the bore of the same, and by which also is secured a large area of port by a very small movement of the valve, and this I claim whether the said valve be used as a main valve, cut off or throttle valve, as set forth.
Second, I claim the combination of a piston valve composed of two heads, which fit closely in the bore of the circular steam chest and are united by a cylindrical portion of less diameter than the said heads with a steam chest constructed with circular ports or passages as specified, in the foregoing claim, by which a large exhaust space is secured without increasing the size of the said steam chest or making it very large, and by which means alone provision is made for the escape of the exhaust steam into the exhaust chamber.
THRESHERS AND CLEANERS OF GRAIN.—By James Robinson, of West Hebron, N. Y.: I claim the mode of checking the motion of the carriage when under headway, and steering the same by means of the tightening pulleys combined as described, with the threshing cylinder and a two wheel cart with double gearing.
I also claim the employment, in the manner described, of the adjusting rods in combination with the feed roller for the purpose of regulating the amount of material to be taken up by the feed roller, as explained.
I also claim the employment of said adjusting rods in combination with the feed roller and threshing cylinder for the purpose of regulating the amount of material to be taken up by the feed roller and of keeping up the material to the threshing cylinder.
I also claim the combination of the adjusting rods, feed roller, and gauge rods, substantially in the manner herein above set forth.
I also claim the combination of the gauge rods, with the feed roller and concave or mouth of the concave of the threshing machine, substantially, as described.
PIANOFORTES.—By Alexander Hall, of Lloydsville, Ohio: I do not claim the employment of extra strings or extra bridge or bridges for the introduction of the lower octave notes as they are set forth in the patent of Simon Drexler granted June 30, 1845, in which an extra bridge is used outside the regular bridge, thereby elongating the instrument.
I claim, first, the mode substantially as described, of introducing upper octave notes in pianofortes, said mode consisting essentially in the employment of extra strings and extra bridges as set forth, so that the performer can play in either of the octaves at the same time with the same facility as he could execute ordinary music on the common piano.
Second, I claim the arrangement of the dampers for the octaves, in combination with the alternate changes of the two upper octave strings to the right and left of the leading strings in each set, for the purposes set forth.
ATTACHING SHAFTS TO WAGONS.—By Daniel Haight Jr., of Clinton, N. Y.: I claim attaching the shafts or tongue by the lateral insertion of the cylindrical headed draw iron into the circular socket of the jack, by which I am enabled to form a safe and ready detachable connection between the shaft or tongue and axle without the use of bolt and nut or bar or any intermediate means.
MACHINE FOR WETTING PAPER.—By William Overend, of Cincinnati, Ohio: I claim, first, the yielding gauges constructed as described.
Second, the combination of the endless bands, the rippers, the roller M, the rollers U, and their bands the roller Y, in combination and counterbalance, the carriage with its vertical arm, the pieces, the bent levers and the cams constructed and combined substantially as described, for taking the wetted paper from the blanket and conveying it to the movable platform, as set forth.
Third, the combination of the sliding pieces moving in the vertical guides and the rollers of the rollers, constructed and combined substantially as described, for adjusting the depositing apparatus to the height of the pile of paper.
Fourth, the combination of levers with the roller and curved groove, arranged substantially as described, for maintaining a uniform tension of the bands in every position of the depositing apparatus.
GRAIN HARVESTERS.—By Aaron Palmer, of Brockport, N. Y., and Stephen G. Williams, of Janesville, Wis.: We do not claim the discharging the cut stalks and heads of grain from a platform, by means of the combination of a rake with a lever, and the co-operation therewith of a series of teeth on the face of the main driving wheel, and an inclined rail rising above the curved guide of the platform, as these are already secured to us by letters patent.
But we do claim the method of transferring motion to the rake on a platform from the driving wheel, by means of the double curved rack and pinion on the axle of the driving wheel, the iron arm, latch and spring, as described.
Also, the method of hanging the reel so as to dispense with any post or reel bearer next to the standing grain, as herein described, thereby preventing the grain from getting caught and held fast between the driver and a reel supporter.
ROLLING AXLES AND SHAFTS.—By Jacob Reese, of Sharon, Penn.: I claim the method of shaping bars of heated iron into axles and shafts of the usual proportions, and with collars and journals, by rolling them on their own axes and under pressure between properly shaped converging surfaces, substantially as described, but I make no claim to mere converging surfaces, whether fixed or movable.
THRESHERS AND SEPARATORS OF GRAIN.—By C. R. Soule, of Fairfield, Vt.: I claim, first, the spring at the end of the lead board, to prevent damage from stones getting into the machine; secondly, the straw carrier and separator, consisting of the notched bars being an end way motion, and the beater as specified, combined with the moveable conducting board for insuring the descent of the grain.
I also claim the mode of hanging and moving the shoe, as described.
MACHINE FOR MAKING WINDOW BLINDS.—By M. C. Stiles and Tristram S. Lewis, of Hollis, Maine: We do not claim the cutter, chisel or any part of the machine separately; but we claim the combination of the cutter and chisel worked simultaneously by the foot of the operator or by other power, in the manner set forth.
DISTILLING APPARATUS.—By Carl E. Werner, of New Castle, Ill.: I claim, first, the rim rising from the floor of the chamber and encircling the discharging opening of the conducting pipe for prevention of the interference of steam with the discharging action of said pipe.
Second, surrounding the entrance of the conducting pipe with an open tubular screen which rises above the pipe entrance to a height greater than any possible ebullition of the liquid, and terminates below at such portion of the liquid as it is desired to discharge from.
MORTISING MACHINE.—By J. E. Brown and Stephen S. Bartlett, of Woonsocket, R. I.: We claim operating the chisel by the graduated conical cam, in combination with the mechanism described, or its equivalent, which enables the operator to vary the length of the stroke made by the chisel while it is in operation or suspends its motion at pleasure without disconnecting the driving power applied to operate the machine.
REISSUE.]
PORTABLE HORSE POWERS.—By J. A. Taplin, of Fishkill, N. Y.: Patented originally, Dec. 30, 1841: I do not claim the making of the large wheel of a horse power in segments merely, but I claim such wheel and axle composed of a number of parts arranged and connected as described, so that the wheel can readily be taken

apart and put together again, to facilitate the frequent removal of the horse-power from place to place to bring it near the work on which it is to be used.
I also claim connecting the segment of the rim of the horse-power by means of clamps constructed, as set forth.
DESIGNS.
DINING ROOM STOVE.—By Conrad Harris and Paul W. Zoimer, of Cincinnati, Ohio.
COOKING STOVE.—By Conrad Harris and P. W. Zoimer, of Cincinnati, Ohio.
SHOVEL AND TONGS.—By Charles Zenner, of Cincinnati, Ohio, assignor to M. Greenwood & Co., of same place. Two designs.
NOTE.—A number of the patents in the above list were secured through the Scientific American Patent Agency.
Recent Foreign Inventions.
MANUFACTURING PAPER.—Geo. Stiff, of London, Eng., patentee. In carrying out his invention, the patentee makes use of straw, or grass, "gunney bagging" and "hemp bagging," preferring however, the employment of straw.—When straw, grass, or vegetable fibre of any similar kind is employed, the first process made use of is to cut the straw or fibre into lengths of about half an inch,—which may be done in a chaff-cutting machine or any similar apparatus heretofore employed for the purpose; after which, the straw or fibre is winnowed, by any suitable contrivance, in order to separate the knots and other portions of the fibre which could not be readily reduced to the consistency of pulp. The straw or fibre, thus treated, or the gunney bagging, or hemp bagging, after having been suitably prepared, is placed in a boiler or vessel, together with a sufficient quantity of clear water to cover the fibre or other material, and boiled for the space of one or two hours. This boiler or vessel is furnished with partition or diaphragm, finely perforated, or composed of gauze or similar material, through which the water may be drained off from the fibre or other material, and carried away through a discharge-pipe, which is brought into connection with the lower surface of the boiler or vessel. After this process, the fibre or other material is to be immersed in lime-water, in the proportion of about 1 cwt. of lime-water to every cwt. of material, and to remain so immersed for the space of about 24 hours, the mixture being occasionally stirred. After the expiration of this time, the lime water is to be drained off, and a fresh solution poured on, which is again drained off, as before. When this operation has been continued during about three days, the fibre or other material is to be placed in water, to which alkali has been added, in the proportion of about 10 lbs. of alkali to every 1 cwt. of water, and boiled for the space of two or three hours; the alkaline solution is then drained off, in the manner before described. After the fibre of the material has been thus treated, it is washed and bleached in the same manner as when bleaching rags; that is to say,—by running it into tanks or vessels, with a quantity of chlorine or bleaching powder, sufficient to bleach it to that degree of whiteness which is required for the quality of paper to be made. After being thus bleached, the straw or other fibre or material, may be washed and beaten, and reduced to pulp or half stuff, in the usual manner; and the pulp or half stuff may be converted into such paper as shall be required by the process heretofore in use.
The patentee claims the substitution of lime-water for other alkaline solutions heretofore employed in the maceration of straw, grass, or other vegetable fibre, or gunney bagging, or hemp bagging, used to form the pulp or half stuff, in the manufacture of such descriptions of paper as are produced from the aforesaid materials.—[Newton's London Journal.]
FIRE-PROOF PAPER.—E. Maniere, of London, patentee. This invention consists in applying asbestos to the manufacture of paper. The asbestos is rendered very fine and pulpy, and mixed along with the pulp of rags.
Tanning Cotton and Linen.
English and French fishermen have been long in the habit of tanning their sails, &c. in bark liquors, in order to render them more durable. Millet states that pieces of linen, treated for 72 hours with an oak bark liquor, at 150°, and stretched on frames, remained unaltered in a damp cellar for 10 years; while untanned linen in the same place and for the same time had entirely rotted. The one frame, also called, was perfectly preserved, and the other, untanned, had rotted. It was further shown

that linen, which had begun to moulder, might be preserved from further change by being tanned. It seems to be only necessary that the articles should be kept 2 or 3 days in a warm solution of tannin.
Awnings may be treated in this manner with either oak bark, or sumac,—both will answer. This will afford a useful hint to our sail-cloth manufacturers.
Ocean Steamers.
Within a short time three new steam lines have been formed to connect Liverpool severally with Maine, New Foundland and New Brunswick, and which will comprise 10 steamships as follows: Liverpool and Portland line 3; Liverpool, Glasgow and Montreal, 5; Liverpool and St. Johns, 2. The first mentioned will be semi-monthly. The pioneer of the line, the Sarah Sands, has already made her first trip.—The steamers of the Montreal line will measure 2,000 tons each, and one of them will be ready in June next. The line to St. Johns is projected by the proprietors of the St. Johns and Liverpool line of packet ships, which consists of eight vessels. The steamers now proposed are iron screw steamships, of 1,600 tons, to be bark-rigged, and to cost \$250,000 each. They will each cross the Atlantic once a month, touching at St. Johns, New Foundland, on every trip.
Cast and Wrought Iron Rails.
It has been proposed to employ cast instead of wrought iron rails, on our railroads. The reasons given for the substitution of the former for the latter are, greater power of resisting crushing pressure; and also greater cheapness. The cast iron rail was the first and consequently it is the oldest. If the action of locomotives and trains upon rails was merely a crushing pressure, then the cast iron rail would be the best—but the action of a train upon the rails is frequently like that of a number of heavy and rapid blows upon an anvil. As cast-iron is very brittle, and breaks very easily during severe frosts by a blow, it would not be suitable in our climate during the winter season.
Pittsburg Statistics.
There are in Pittsburg and its vicinity seventeen large rolling mills; twelve principal or large foundries; twenty glass manufactories; about twenty engine and machine shops; five large cotton factories; four large flouring mills, besides some smaller ones; and it is estimated that there are more than one hundred steam engines in operation in the city and vicinity.
Cold in England.
By the last news from Europe, it appears that England has been visited with the severest cold ever recorded in history, namely, 4° below zero. A number of persons have been frozen to death, as no preparations are ever made by the people for such severe weather.
The New Patent Law of England.
By the new patent law of England, the heirs of a deceased inventor can take out a patent. This could not be done under the old law, if the inventor died between the periods of filing his application and the enrollment of the patent.
Tracing Paper.
A sheet of fine thin white paper dipped into a thick solution of gum arabic and then pressed between two dry sheets, renders the three transparent when dry; it is very useful for tracing purposes as it can either be written or painted upon.
There are on the earth 1,000,000,000 inhabitants; of these 33,333,333 die every year, 91,824 every hour, and sixty every minute, or one every second. These losses are about balanced by an equal number of births.
Elastic Varnish for Leather.
Take two parts by weight of resin, and one of india rubber, and heat them in an earthen ware vessel until they are fused together, after which they should be stirred until they are quite cold, a little boiled linseed oil may be added while the materials are hot.
If ivory becomes brittle by age, it will recover its original quality by being boiled in a solution of pure glue.